


# SPEED REDUCER



**Table of dimension**

Type	Style	Prebored	Finish bores		I	E	S	b	L	M	D <sub>H</sub>	D	d <sub>H</sub>
			d <sub>min</sub>	d <sub>max</sub>									
Aluminium Diecasting(Al-D)													
JTC9	1a		4	9	10	10	1.0	8	30		20		6
JTC14	la		4	16	11	13	1.5	10	35		30		10
JTC19	1		6	19	25	16	2.0	12	66	20	40	32	18
	la6	24											
Steel													
JTC19	la		6	24	25	16	2.0	12	66		40		18
JTC24	1a		8	28	30	18	2.0	14	78		55		27
JTC28	la		10	38	35	20	2.5	15	90		65		30
JTC38	1	11	12	38	45	24	3	18	114	37	80	66	38
	1a		12	45									
JTC42	1	13	14	42	50	26	3	20	126	40	95	75	46
	la		14	55									
JTC48	1	14	15	48	56	28	3.5	21	140	45	105	85	51
	1a		15	60									
JTC55	1	18	20	55	65	30	4	22	160	52	120	98	60
	la		20	70									
JTC65	1	20	22	65	75	35	4.5	26	185	61	135	115	68
	1a		22	75									
JTC75	1	28	30	75	85	40	5	30	210	69	160	135	80
	1a		30	90									
JTC90	1	38	40	90	100	45	5.5	34	245	81	200	160	100
	1a		40	100									

## Summary

- Applicable to all types of machinery and hydraulics.
- Small volume and large transmitted torque.
- To be plugged in axially,easy assembly,maintenance-free.
- Balancing axial,radial and angular misalignment.
- Dimensions of bore d available on customer's request.
- Applicable from -40°C to +100°C ,temperature peaks up to 120°C .

