

DIMENSIONAL SPECIFICATIONS

MODEL	2S - 110	2S - 125	2S - 160	2S - 200	2S - 250	\$2S - 315	\$2S - 400	\$2S - 500
Size Ø	110	125	160	200	250	315	400	500
AØ	110	125	160	200	250	315	400	500
B1Ø	45	60	78	97	97	120	180	180
C	31.5	61	81	93	93	98	127	127
C1	38.5	69.5	87	100	103.5	109	131	136
C4	—	104	135	154	163.5	174.5	212	225
D Jaw stroke	2.1	4.2	4.2	5.4	5.4	5.4	8	8
EØH6	92	115	150	185	185	300	300	460
F	3	6	6	6	6	6	6	6
G PCD	80	92	125	160	140	250	250	300
H	4 x M8	2 x M12	2 x M12	2 x M12	2 x M16	4 x M20	4 x M24	4 x M24
H1	* M 20 x 1.5	M12	M16	M20	M20	M20	M24	M24
J	15.5	18	24	29	30	39	34	36
J1	—	43	60	70	70	68	54	54
K min	25	25	22	30	30	28	18	18
K max	33	44	41	52	52	50	48	48
N	8	19	19	22	22	22	30	30
OØ	—	27	31.5	35	35	35	46	46
O1Ø	—	35	40	48	48	52	75	75
TØ	65	52	68	89	89	98	145	145
V	—	—	102	130	170	200	280	280
Z1	25	25	25	30	30	30	30	30
b	25	25	38	45	45	45	60	60
d	M6	M8	M10	M12	M14	M16	M20	M20
g	25	40	45	55	60	70	70	70
j1 x 90°	1/16"	1/16"	1/16"	1/16"	1/16"	1/16"	3/32"	3/32"
n	12	15	25	30	30	30	30	30
q H7	—	10	12	14	17	21	25.5	25.5
Clamping Range	Outer min	4	10	18	20	24	50	108
	max	110	125	160	200	250	315	500
	min	22	34	34	56	60	72	106
	Inner max	110	125	160	200	250	315	500
RPM	4000	3200	2800	2300	2000	1700	1400	900
Drawbar pull in kgs	465	620	860	1420	2450	3590	5810	5810
Wt in Kgs. (Approx)	2.1	5	7	14	22	45	78	100

\$ Sizes are special

* Drawbar will be threaded on to wedge