## GA-72Cd-ML

#### **MAGNETIC LOCATOR**







## **SCHONSTEDT**

# GA-72Cd-ML

### **Quickly Locates Buried Ordnance, Mines and Weapons**

- Patented HeliFlux® sensors
- No response to aluminum, brass, or copper
- Analog output for data logger entry

Comes with Case, Battery Charger, Carry Strap

OUTPUT
SIGNAL
+ OR +
Signal patterns from vertical and horizontal targets aid in determining their orientation.

- Rechargeable batteries\*
- Full one-year warranty for EOD/military use


GA-72Cd-ML Specifications	
Audio Output	Switch at "A" Signal increases or decreases in volume with gradient-field intensity Switch at "B" Signal increases or decreases in frequency with gradient-field intensity
Visual Indicator	Digital readout and expanding bar graphs indicate polarity (+ or-) and relative strength of the magnetic field
Analog Output	Yes
Sensitivity	4 settings
Input Power	Two rechargeable 9V NiMH batteries
Battery Life	60 Hours (intermittent use)
Weight	~2.6 lbs (1.18 kg)
Operating Temperature	-13° to 140°F (-25° to 60°C)
Overall Length	34.5" (87.6 cm)
Waterproof Length	21" (53.3 cm)
Sensor Spacing	14" (35.6 cm)
Housing Material	Polycarbonate/ABS Blend

SIGNAL ABOVE GROUND

SIGNAL AT GROUND

SHRAPNEL

Raising the locator eliminates unwanted signals.



Contact Us: 800-999-8280 info@schonstedt.com

Find Your Local Dealer: schonstedt.com





<sup>\*</sup> Other battery options available