



TECHNICAL DATA SHEET

PRODUCT NAME: KAB-40® MULTI-PURPOSE RUST REMOVER

ISSUED DATE: 25 APRIL 2025

MANUFACTURER: LOOKMANI ENTERPRISE

ADDRESS: B-5 B-6, ARMAN INDUSTRIAL ESTATE, GOLANI NAKA, WALIV, VASAI (E), PALGHAR, MAHARASHTRA, INDIA – 401208

+91 8850105253

kablubricants@gmail.com

www.kablubricants.com

PRODUCT DESCRIPTION

KAB-40® is a high-performance, multi-purpose aerosol lubricant engineered for effective rust removal, lubrication, moisture displacement, and surface protection. The product rapidly penetrates stuck mechanisms and displaces moisture, making it suitable for automotive, industrial, electrical, and marine applications.

FEATURES & BENEFITS

- **Rust Loosening:** Penetrates corroded threads and metal parts to release seized components.
- **Moisture Displacement:** Excellent water-repelling characteristics for drying wet electrical systems.
- **Lubrication:** Reduces friction and wear on moving parts without attracting dirt.
- **Corrosion Protection:** Leaves behind a thin, anti-corrosive film on treated surfaces.
- **Multi-surface Use:** Compatible with most metals, plastics*, and painted surfaces.

*Always test on sensitive plastics and elastomers before full application.

TYPICAL APPLICATIONS

- **Automotive:** Nuts, bolts, door hinges, locks, and electrical contacts
- **Industrial:** Bearings, shafts, valves, fasteners, production equipment
- **Electrical:** Ignition systems, connectors, fuse boxes, terminals
- **Marine:** Outboard parts, rigging, mechanical joints, connectors etc.

PHYSICAL & CHEMICAL PROPERTIES

Appearance : Clear, low-viscosity liquid

Delivery Form : Pressurized Aerosol

Odour : Characteristic organic solvent

Propellant : Propane/Butane Blend

Base Composition : Petroleum distillate blend

Flash Point (Propellant) : -40°C

Auto-Ignition Temperature : 410°C

Water Solubility : Insoluble

Specific Gravity : Approx. 0.78 – 0.82 @ 20°C

pH Value : Not applicable

Flammability Limits (LFL/UFL) : Not available

VOC Content : Approx. 65% (w/w)

REGULATORY & SAFETY INFORMATION

- UN Number: UN1950
- Transport Class: Flammable Aerosol – Limited Quantity
- GHS Classification: Flammable Aerosol (Category 1), Aspiration Hazard (Category 1)
- Precautionary Statements: Keep away from heat/sparks/open flames. Avoid inhalation. Use with adequate ventilation.

Refer to the Material Safety Data Sheet (MSDS) for full safety and first aid instructions.



STORAGE & HANDLING

- Store in a well-ventilated area below 50°C.
- Keep away from direct sunlight, sparks, and open flames.
- Do not puncture or incinerate container, even when empty.
- Shelf life: 2 years from manufacture date (if unopened and stored properly)

