



CLOUD VIDEO SURVEILLANCE

Eagle Eye Cloud VMS Camera & Accessory Catalog





COMPANY OVERVIEW

Smart, Simple, Cloud Video Surveillance for Your Business

Your security system should not only protect your people and property, it should also provide insight to help your business grow and thrive. It's Eagle Eye Networks mission to help you do just that.

We're leaders in delivering the power, flexibility, and cost-savings of cloud technology to the video surveillance market, helping you improve operations and enhance customer service, all while keeping an eye on what truly matters.

Whether you run a small business, global enterprise, or something in-between, you need a video solution capable of adapting to your needs – today and tomorrow. The Eagle Eye Cloud Video Management System (VMS) simplifies video surveillance through the flexibility of cloud paired with the convenience of easy, affordable installation and remote management.

TABLE OF CONTENTS

CAMERAS	3
ENCODER	7
ACCESSORIES	7
Eagle Eye SD Cards	8
Eagle Eye Junction Boxes	8
Eagle Eye Wall Arms	9
Eagle Eye Pendants and Poll Mounts	9
Eagle Eye Corner Mounts	9
Eagle Eye Camera Caps	10
ACCESSORY SELECTION	11





DON'T LOSE YOUR INVESTMENT, CHOOSE YOUR INVESTMENT


Eagle Eye Cameras

Don't get locked into any one camera brand or model, or get forced into ripping and replacing your existing cameras. The Eagle Eye Cloud VMS supports more than 4,000 cameras from all the leading manufacturers, but if you're looking to buy new cameras, Eagle Eye Cameras offer a secure, plug-and-play installation.

Camera models are suitable for indoor and outdoor use for a wide range of applications. The cameras come pre-configured to securely operate with the Eagle Eye Cloud Security VMS and Eagle Eye CameraManager.


	CAMERA DB10	CAMERA DB11	CAMERA DB12	CAMERA DB13
				
Description	Ultra-lowlight, indoor/ outdoor, waterproof mini bullet.	Ultra-lowlight, indoor/ outdoor, waterproof mini bullet.	High-performance, indoor/outdoor, waterproof mini bullet.	High-performance, indoor/outdoor, waterproof bullet.
Resolution	4 Mega Pixels	4 Mega Pixels	8 Mega Pixels	8 Mega Pixels
Lens	2.8mm	2.7 - 13.5mm Motorized Lens	2.8mm	2.7 - 13mm Motorized Lens
Night Vision	Smart IR LEDs with up to 30m range	Smart IR LEDs with up to 40m range	Smart IR LEDs with up to 30m range	Smart IR LEDs with up to 40m range
Dynamic Range	WDR (120dB) and HLC/BLC	WDR (120dB) and HLC/BLC	WDR (120dB) and HLC/BLC	WDR (120dB) and HLC/BLC
Housing	Durable All Aluminum	Durable All Aluminum	Durable All Aluminum	Durable All Aluminum
Ingress Protection	IP67	IP67	IP67	IP67
Streaming Protocol	Quad RTSP Streams	Triple RTSP Streams	Triple RTSP Streams	Triple RTSP Streams
Applications	Best for small indoor areas: stock room, lobby, hallways, elevators, IT closets, storage rooms, entrances, interview rooms.	Best for modest outdoor areas or large indoor areas: Small Parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses.	Best for small indoor areas: stock room, lobby, hallways, elevators, IT closets, storage rooms, entrances, interview rooms.	Best for modest outdoor areas or large indoor areas: Small Parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses.

	CAMERA DD07	CAMERA DD08	CAMERA DD09	CAMERA DD10
				
Description	Ultra-lowlight, indoor/outdoor, waterproof vandal dome.	Ultra-lowlight, indoor/outdoor, waterproof vandal dome.	High-performance, indoor/outdoor, waterproof vandal dome.	High-performance, indoor/outdoor, waterproof vandal dome.
Resolution	4 Mega Pixels	4 Mega Pixels	4 Mega Pixels	8 Mega Pixels
Lens	2.8mm	2.7 – 13.5mm Motorized Lens	2.7 – 13.5mm Motorized Lens	2.8mm
Night Vision	Smart IR LEDs with up to 30m range	Smart IR LEDs with up to 30m range	Smart IR LEDs with up to 30m range	Smart IR LEDs with up to 30m range
Dynamic Range	WDR (120dB) and HLC/BLC	WDR (120dB) and HLC/BLC	WDR (120dB) and HLC/BLC	WDR (120dB) and HLC/BLC
Housing	Durable All Aluminum	Durable All Aluminum	Durable All Aluminum	Durable All Aluminum
Ingress Protection	IP67 & IK10	IP66 & IK10	IP67 & IK10	IP67 & IK10
Streaming Protocol	Quad RTSP Streams	Triple RTSP Streams	Triple RTSP Streams	Triple RTSP Streams
Applications	Best for small indoor areas: stock room, lobby, hallways, elevators, IT closets, storage rooms, entrances, interview rooms.	Best for modest outdoor areas or large indoor areas: Small Parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses.	Best for modest outdoor areas or large indoor areas: Small Parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses.	Best for small indoor areas: stock room, lobby, hallways, elevators, IT closets, storage rooms, entrances, interview rooms.

	CAMERA DD11	CAMERA DF04	CAMERA DM08	CAMERA DT01
				
Description	High-performance, indoor/outdoor, waterproof vandal dome.	Indoor/outdoor, fisheye with integrated microphone, 360° view.	High-performance, indoor/outdoor, mini dome with integrated microphone.	High-performance, indoor/outdoor, turret with integrated microphone.
Resolution	8 Mega Pixels	12 Mega Pixels	4 Mega Pixels	4 Mega Pixels
Lens	3.3 - 12mm Motorized Lens	Fixed 1.8mm	3.6mm or 2.8mm	Fixed 2.8mm Lens
Night Vision	Smart IR LEDs with up to 30m range	Smart IR LEDs with up to 15m range	IR LEDs with up to 15m range	Smart IR LEDs with up to 30m range
Dynamic Range	WDR (120dB) and HLC/BLC	DWDR	WDR (120dB) and HLC/BLC	DWDR and HLC/BLC
Housing	Durable All Aluminum	Durable All Aluminum	Durable All Aluminum	Durable All Aluminum
Ingress Protection	IP66 & IK10	IP66	IP66	IP66
Streaming Protocol	Triple RTSP Streams	Triple RTSP Streams	Triple RTSP Streams	Triple RTSP Streams
Applications	Best for modest outdoor areas or large indoor areas: Small Parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses.	Best for medium size open areas: hallways, intersections, lobbies, and retail. Optimal view is 25 ft radius from camera placement.	Best for small indoor areas: stock room, lobby, hallways, elevators, IT closets, storage rooms, entrances, interview rooms.	Best for modest outdoor areas or large indoor areas: small parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses.



	CAMERA DT02	CAMERA DT03	CAMERA DX01	CAMERA DZ04
				
Description	High-performance, indoor/outdoor, turret with integrated microphone.	Ultra low light with integrated warm light LEDs, indoor/outdoor, turret with integrated microphone.	High-performance, indoor/outdoor, 180° stitched panoramic bullet with integrated microphone.	High-performance, indoor/outdoor, weatherproof dome.
Resolution	4 Mega Pixels	4 Mega Pixels	8 Mega Pixels	5 Mega Pixels
Lens	2.7 - 13.4mm Motorized Lens	4mm Fixed Lens	2.8mm Fixed Lens	5.3 - 159mm Motorized Lens
Night Vision	Smart IR LEDs with up to 40m range	Smart IR LEDs with up to 40m range	Smart IR LEDs with up to 30m range	Up to 150m
Dynamic Range	WDR (120dB) and HLC/BLC	True WDR	True WDR	True WDR > 120dB
Housing	Metal + Plastic	Metal + Plastic	Metal	Metal
Ingress Protection	IP66	IP66	IP66	IP66 & TVS4000V
Streaming Protocol	Triple RTSP Streams	Triple RTSP Streams	Triple RTSP Streams	Triple RTSP Streams
Applications	Best for modest outdoor areas or large indoor areas: small parking lots, fields, parking garages, work yards, back yards, outdoor entrances, warehouses.	Best for outdoor applications where low light color performance is required. Can also produce a color image in no light scenarios by using the warm light LEDs.	Best for building perimeters or large open areas like parking lots, fields, road ways, and warehouses.	Best for large areas like parking lots, fields, road ways, and warehouses.

Eagle Eye Encoder

		EC01
Camera Input	16 Channel BNC	
Input Resolutions	8 Mega Pixels, 5 Mega Pixels, 4 Mega Pixels, 1080 Pixels, 720 Pixels	
Formats	AHD, TVI, CVI, CVBS	
HDMI Output	3840×2160, 1920×1080, 1280×1024, 1024×768	
Dimensions	380 x 159.8 x 51 mm	
Weight	1.6 kg	




Eagle Eye Camera Accessories

SD Cards

	EN-SDMD-001	EN-SDMD-002
		
Description	Eagle Eye Industrial High Endurance Video microSD Card 32G with built-in sync between SD Card & Eagle Eye Cloud. Continues recording without internet.	Eagle Eye Industrial High Endurance Video microSD Card 64G with built-in sync between SD Card & Eagle Eye Cloud. Continues recording without internet.
Compatibility	Eagle Eye Cameras with SD Slot	Eagle Eye Cameras with SD Slot
Warranty	2 Years	2 Years
Recording	Video and audio	Video and audio

Junction Boxes




	JUNCTION BOX BX004	JUNCTION BOX BX005	JUNCTION BOX BX006
			
Compatibility	Please see "Accessory Selection"	Please see "Accessory Selection"	Please see "Accessory Selection"
Material	Aluminum alloy	Aluminum alloy	Aluminum alloy
Color	White	White	White
Operating Humidity	0% - 90% RH	0% - 90% RH	0% - 90% RH
Load Bearing	4 kg (8.82 lb)	2 kg (4.4 lb)	4 kg (8.82 lb)
Dimensions	Φ142 × 51 mm (Φ5.6 × 2.0")	Φ123 × 52 mm (Φ4.84 × 2.05")	Φ121 × 46 mm (Φ4.76 × 1.81")
Weight	0.56 kg (1.23 lb)	0.4 kg (0.88 lb)	0.4 kg (0.88 lb)

	JUNCTION BOX BX007	JUNCTION BOX BX008	JUNCTION BOX BX009	JUNCTION BOX BX011
				
Compatibility	Please see "Accessory Selection"	Please see "Accessory Selection"	Please see "Accessory Selection"	Please see "Accessory Selection"
Material	Aluminum alloy	Aluminum alloy + plastic	Aluminum alloy + plastic	Aluminum alloy
Color	White	White	White	White
Operating Humidity	0% - 90% RH	0% - 90% RH	0% - 90% RH	0% - 90% RH
Load Bearing	4 kg (8.82 lb)	3 kg (6.61 lb)	3 kg (6.61 lb)	3 kg (6.61 lb)
Dimensions	Φ121 × 46 mm (Φ4.76 × 1.81")	Φ110 × 37.3 mm (Φ4.33 × 1.47")	Φ107 × 46 mm (Φ4.21 × 1.81")	Φ123 × 52 mm (Φ4.84 × 2.05")
Weight	0.4 kg (0.88 lb)	0.21 kg (0.46 lb)	0.34 kg (0.75 lb)	0.4 kg (0.88 lb)

Wall Arms

	WALL ARM WA006	WALL ARM WA007
		
Compatibility	Please see "Accessory Selection"	Please see "Accessory Selection"
Material	Aluminum alloy	Aluminum alloy
Color	White	White
Operating Humidity	0% - 90% RH	0% - 90% RH
Load Bearing	3 kg (6.61 lb)	3 kg (6.61 lb)
Dimensions	141 × 116.2 × 116.2 mm (5.55 × 4.57 × 4.57")	201.8 × 120.2 × 167.4 mm (7.94 × 4.73 × 6.59")
Weight	0.25 kg (0.55 lb)	0.85 kg (1.87 lb)

Pendants, Pole Mounts, and Corner Mounts

	PENDANT PE004	POLE MOUNT 002	CORNER MOUNT 002
			
Compatibility	Please see "Accessory Selection"	Please see "Accessory Selection"	Please see "Accessory Selection"
Material	Aluminum alloy	Aluminum alloy + stainless steel	Aluminum alloy
Color	White	White	White
Operating Humidity	0% - 90% RH	0% - 90% RH	0% - 90% RH
Load Bearing	3 kg (6.61 lb)	4 kg (8.82 lb)	4 kg (8.82 lb)
Dimensions	Φ140 × 264 mm (Φ5.51 × 10.4")	130.2 × 46 × 170 mm (5.13 × 1.81 × 6.69") Embrace Hoop Diameter: 130 ~ 152 mm (5.12 ~ 5.98")	176.5 × 103.3 × 170 mm (6.95 × 4.07 × 6.69")
Weight	0.56 kg (1.23 lb)	0.41 kg (0.9 lb)	0.5 kg (1.1 lb)

Camera Caps

	CAMERA CAP 001	CAMERA CAP 002	CAMERA CAP 003
			
Compatibility	Please see "Accessory Selection"	Please see "Accessory Selection"	Please see "Accessory Selection"
Material	Aluminum alloy	Aluminum alloy	Aluminum alloy
Color	White	White	White
Operating Humidity	0% - 90% RH	0% - 90% RH	0% - 90% RH
Load Bearing	3 kg (6.61 lb)	3 kg (6.61 lb)	3 kg (6.61 lb)
Dimensions	Φ109.8 × 65 mm (Φ4.32 × 2.56")	Φ122.8 × 68 mm (Φ4.83 × 2.68")	Φ145 × 73 mm (Φ5.71 × 2.87")
Weight	0.13 kg (0.29 lb)	0.17 kg (0.37 lb)	0.21 kg (0.46 lb)

	CAMERA CAP 004	CAMERA CAP 005	CAMERA CAP 006
			
Compatibility	Please see "Accessory Selection"	Please see "Accessory Selection"	Please see "Accessory Selection"
Material	Aluminum alloy	Aluminum alloy	Aluminum alloy
Color	White	White	White
Operating Humidity	0% - 90% RH	0% - 90% RH	0% - 90% RH
Load Bearing	3 kg (6.61 lb)	3 kg (6.61 lb)	3 kg (6.61 lb)
Dimensions	Φ118 × 68 mm (Φ4.65 × 2.68")	Φ122.8 × 70 mm (Φ4.83 × 2.76")	99.5 × 99.5 x 75.8 mm (3.92 × 3.92 x 2.98")
Weight	0.17 kg (0.37 lb)	0.25 kg (0.55 lb)	0.19 kg (0.42 lb)

Accessory Selection

