# CREED TA WHITE

### Ultra white tile adhesive

White, high polymer modified, cement-based wall and floor tile adhesive. Suitable for fixing marble, tiles and natural stones in interior and exterior situations, including swimming pools

#### **SPECIFICATION**

Pot Life : 2 Hrs
Setting Time : 24 Hrs
Compressive Strength : 14N/mm²
Curing Time : 10 min

#### **KEY FEATURES**

Whitish color enhance true marble effect Excellent adhesion Optimum settling time

#### Area of Use:-

- This adhesive is suitable for fixing wall and floor tiles, mosaics, vitrified and fully vitrified tiles, marble, terrazzo, and natural stone.
- It is suitable for fixing at 3 6mm bed thickness (can be extended up to 12 mm in area of limited extent).
- The set adhesive is water-resistant and is suitable for use in showers and totally immersed situations such as swimming pools.

#### **APPLICATION**



Mosiac glass tile



Marble



Floor tile



Terrazo & natural stone

#### HOW TO APPLY :-

- To prepare CREED TA WHITE adhesive, mix it with water in the ratio of 4:1 by volume using a slow speed drill with a paddle attachment. Blend until a homogeneous, lump-free mixture is obtained.
- After mixing, spread not more than I sq.m. at a time and apply the adhesive to the wall or floor surface.
- To fix the tiles, comb the adhesive to the required depth (between 3 6 mm) using a suitable trowel.
- Press the tiles firmly into position with a slight twisting action, checking periodically that good contact is maintained with the back of each tile.
- · Leave no voids behind tiles when solid-bed fixing.
- Tiles should be fixed within 20 minutes of adhesive being applied, depending on the porosity of the surface and atmospheric conditions.
- Tiles can be adjusted up to 10 15 minutes after fixing.
- Touch the adhesive ribs periodically, and if a skin has formed, remove the adhesive and apply a new layer.
- · Leave adequate joints between individual wall and floor tiles unless self-spacing tiles are used.
- · Clean off surplus adhesive from the tile face and between joints.
- Please note that this adhesive is not suitable for use in damp conditions and temperatures less than 5°C.



# Packing:-

20 Kg & 50 Kg



#### Area to cover:-

TO cover an area of 3 to 4 m2 with a recommended thickness of 4 to 5 mm it will need 20 kg of CREED TA WHITE

## Precautions :-

CREED TA WHITE is a non-toxic adhesive. However, if it comes in contact with your skin, wash it
well with water. If it comes in contact with your eyes, wash it well with water and seek medical
advice

#### Shelf Life:-:

 CREED TA WHITE has a shelf life of 12 months when stored in unpened containers in dry conditions at a temperature between 5°C and 45°C.