

GPOXY-05

Epoxy tile grout

GPOXY-05 is a high-performance epoxy grout that offers color uniformity, durability, and stain resistance with ease of use. It is used for filling tile joints of width 3 mm to 10 mm in both interior and exterior areas. GPOXY -05 is designed for use on ceramic tile, glass tile, and stone applications, both residential and commercial. It can be used both interior and exterior on floors and walls. This grout is ideal for re-grouting applications.

KEY FEATURES

Non-sag formula for walls and floors.

No- Shading

Chemical Resistant for Internal & External Tiling

APPLICATION



Swimming pool



Wall tile



External facades



Vitrified tiles

Area of Use:-

- GPOXY-05 is ideal for filling tile joints with a thickness of 3 - 10 mm. It works well for both wall and floor tiles, mosaics, vitrified and fully vitrified tiles, marble, terrazzo, and natural stone.
- The set tile grout is water-resistant, making it suitable for use in showers and even in completely immersed situations like swimming pools.
- You can use GPOXY-05 in residential, commercial, external facades, and wet areas.

HOW TO APPLY :-

- GPOXY-05 is a three-part system with a ratio of 70:30 for Part A and Part B.
- Mix Part A and Part B using a slow-speed drill with a paddle attachment.
- Add Part C to the mixture and thoroughly blend it to achieve a homogenous consistency.
- Clean off any surplus adhesive from the joints and ensure the joints are free of dirt for grout application. Remove excess water from the joints.
- Pack the joints fully and without voids using a rubber grouting float.
- To remove excess grout from tile faces, use the edge of the rubber float and make diagonal strokes (at a 45° angle to the direction of the joints).
- Once the joints have set, use a moist sponge to remove any remaining excess grout from the tiles and joints. Use minimal water for cleanup.



Packing:-

1 & 5 Kg

Net Content:-

Resin	:	0.200 gm
Hardener	:	0.100 gm
Filler Powder	:	0.700 gm
Total Net Content	:	1.000 kg



Area to cover:-

30 Rft./ kg for 3-10 mm thickness

Precautions:-

- GPOXY-05 is non-toxic. However, splashes on the skin should be washed well with water and in contact with eye occurs, wash well with water and seek medical advice.

Shelf Life:-:

- GPOXY-05 has a shelf life of 6 months when stored in unopened containers under dry conditions at temperatures between 5°C to 45°C. However, storage at higher temperatures or in high humidity environments may reduce its shelf life.