

# MCRETE-FIX

## High performanc motar for AAC blocks

MCRETE FIX is a pre-mixed adhesive mortar that is polymer-modified, easy to apply, and of high quality. It comprises cement, graded sand, and special additives. Specifically designed to provide strength and adhesion to walls constructed by AAC blocks, fly ash bricks, concrete blocks, etc. MCRETE FIX replaces conventional jointing mortar of 12-18 mm thickness with a highly versatile 3-6 mm thickness.

### SPECIFICATION

Appearance : Grey Coloured Powder  
Basic Binder : Ordinary Portland Cement  
Aggregate : Graded Sand  
Additives : Polymer Additives  
Pot Life : 2 Hrs  
Setting Time : 24 Hrs

### KEY FEATURES

Excellent bonding strength  
Minimise leakage  
Strong adhesion  
Improves labour productivity

### APPLICATION



Flyash bricks



Concrete blocks



AAC blocks

## HOW TO APPLY :-

- Wet the surface and remove the excess water before applying the adhesive.
- Take approximately 8 to 9 liters of water for a bag of MCRETE-FIX.
- Add the 40 kg bag of MCRETE-FIX to the water.
- Leave the mix to slake for 5-10 minutes and remix before use.
- Apply the mix material with a notch trowel on the block surface and place the block.
- Repeat the same procedure for the rest of the area.



### Packing:-

25 kg & 40Kg



### Area to cover:-

90 -100 sq.ft. / 40 kg bag @ 3mm thickness

## Precautions:-

- However, splashes on the skin should be washed well with water and in contact with eye occurs, wash well with water and seek medical advice.

## Shelf Life:-:

- 6 months from manufacture in original unopened bags if stored in dry conditions.