

# Hand Operated Grease Pump

18% GST for Pneumatic Operated



## Key Features:

- > Anti Air lock System
- > Mobile Pumps
- > Powder Coated
- > Available in sizes from 3kgs to 20kgs

## Hand Operated Grease Pump Technical Specifications

Capacity	3kgs
Block Pressure	140kg/cm <sup>2</sup>
Output	3 Grams per stroke
Hose length	2 Mtr HYD SAE100 R1 Hose with end fittings
Pressure Plate	Installed with pump
Net Weight	6.2kgs

MANUFACTURED IN : COIMBATORE

# Hand Operated Grease Pump

18% GST for Pneumatic Operated



## Key Features:

- > Anti Air lock System
- > Mobile Pumps
- > Powder Coated
- > Available in sizes from 3kgs to 20kgs

## Hand Operated Grease Pump Technical Specifications

Capacity	5kgs
Block Pressure	140kg/cm <sup>2</sup>
Output	3 Grams per stroke
Hose length	2 Mtr HYD SAE100 R1 Hose with end fittings
Pressure Plate	Installed with pump
Net Weight	7.5kgs

MANUFACTURED IN : COIMBATORE

# Hand Operated Grease Pump

18% GST for Pneumatic Operated



## Key Features:

- > Anti Air lock System
- > Mobile Pumps
- > Powder Coated
- > Available in sizes from 3kgs to 20kgs

## Hand Operated Grease Pump Technical Specifications

Capacity	10kgs
Block Pressure	140kg/cm <sup>2</sup>
Output	3 Grams per stroke
Hose length	2 Mtr HYD SAE100 R1 Hose with end fittings
Pressure Plate	Installed with pump
Net Weight	9.5kgs

MANUFACTURED IN : COIMBATORE



# Hand Operated Grease Pump

18% GST for Pneumatic Operated



## Key Features:

- > Anti Air lock System
- > Mobile Pumps
- > Powder Coated
- > Available in sizes from 3kgs to 20kgs

## Hand Operated Grease Pump Technical Specifications

Capacity	20kgs
Block Pressure	140kg/cm <sup>2</sup>
Output	3 Grams per stroke
Hose length	2 Mtr HYD SAE100 R1 Hose with end fittings
Pressure Plate	Installed with pump
Net Weight	13.5kgs

MANUFACTURED IN : COIMBATORE

# Pneumatic Operated Grease Pump

18% GST for Pneumatic Operated



## Key Features:

- > Anti Air lock System
- > Mobile Pumps
- > Powder Coated
- > Available in sizes from 5kgs to 200kgs

## Pneumatic Operated Grease Pump Technical Specifications

	6kgs
Max Working Pressure	Minimum 4kg/cm <sup>2</sup> Max. 10.5kg/cm <sup>2</sup>
Pressure ratio	50:1
Hose length	2.2 Mtr HYD SAE100 R2 Hose with end fittings
Pressure Plate	Provided with Rubber seal
Net Weight	14kg

MANUFACTURED IN : COIMBATORE

# Pneumatic Operated Grease Pump

18% GST for Pneumatic Operated



## Key Features:

- > Anti Air lock System
- > Mobile Pumps
- > Powder Coated
- > Available in sizes from 5kgs to 200kgs

## Pneumatic Operated Grease Pump Technical Specifications

Capacity	12kgs
Max Working Pressure	Minimum 4kg/cm <sup>2</sup> Max. 10.5kg/cm <sup>2</sup>
Pressure ratio	50:1
Hose length	2.2 Mtr HYD SAE100 R2 Hose with end fittings
Pressure Plate	Provided with Rubber seal
Net Weight	15kg

MANUFACTURED IN : COIMBATORE



# Pneumatic Operated Grease Pump

18% GST for Pneumatic Operated



## Key Features:

- > Anti Air lock System
- > Mobile Pumps
- > Powder Coated
- > Available in sizes from 5kgs to 200kgs

## Pneumatic Operated Grease Pump Technical Specifications

Capacity	25kgs
Max Working Pressure	Minimum 4kg/cm <sup>2</sup> Max. 10.5kg/cm <sup>2</sup>
Pressure ratio	50:1
Hose length	2.2 Mtr HYD SAE100 R2 Hose with end fittings
Pressure Plate	Provided with Rubber seal
Net Weight	22kg

MANUFACTURED IN : COIMBATORE

# Pneumatic Operated Grease Pump

18% GST for Pneumatic Operated



## Key Features:

- > Anti Air lock System
- > Mobile Pumps
- > Powder Coated
- > Available in sizes from 5kgs to 200kgs

## Pneumatic Operated Grease Pump Technical Specifications

Capacity	50kgs
Max Working Pressure	Minimum 4kg/cm <sup>2</sup> Max. 10.5kg/cm <sup>2</sup>
Pressure ratio	50:1
Hose length	2.2 Mtr HYD SAE100 R2 Hose with end fittings
Pressure Plate	Provided with Rubber seal
Net Weight	27kg

MANUFACTURED IN : COIMBATORE