

GREY DUCT HOSE



Grey Duct Hose –

The Grey Duct Hose is a flexible and durable ventilation duct designed for efficient air transfer and exhaust applications. Made from high-quality coated material with spiral reinforcement, it ensures excellent strength, flexibility, and long service life.







Its lightweight and highly flexible design allows easy installation in tight spaces, while maintaining smooth airflow performance. Ideal for use in HVAC systems, industrial ventilation, and dust extraction applications.



Grey Duct Hose

Wall	Soft PVC
Spiral	Square Rigid PVC Helix
Temp Range	-20°C to +70°C Short time to 80°C
Features	<ul style="list-style-type: none"> • PVC Hoses Reinforced with Anti-Shock Rigid PVC Spiral • Inside Surface Perfectly Smooth, Outside Corrugated • High Resistance Against Abrasion and Bending • Could Be Manufactured Anti-Static Upon Request • Could Be Manufactured in PU Upon Request • High Tensile Strength and Tear Resistant • Could Be Resistant to Chemicals and Mineral Oils Upon Request • Comply to RoHS
Application	As Suction and Discharge Hose Ideal for Abrasive Powders, Chips, Gravel, Sand, Cements, Shavings, and Smoke, Vapours

TECHNICAL DATA

 ID	 WT	 BR	 WP	 VACUUM	 L
<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>bar</i>	<i>bar</i>	<i>m</i>
25	0.8	35	1.6	0.50	20
32	0.8	50	1.5	0.45	20
38	0.8	55	1.3	0.40	20
51	0.8	110	1.2	0.35	20
63	0.8	163	1.2	0.30	20
76	0.8	190	1.1	0.30	20
89	0.8	220	1.0	0.25	20
102	0.8	240	1.0	0.25	20
127	0.8	400	0.8	0.20	20
152	0.8	450	0.6	0.15	20
178	0.8	500	0.5	0.15	20
203	0.8	550	0.4	0.10	20
25	0.8	35	1.6	0.50	20
32	0.8	50	1.5	0.45	20
38	0.8	55	1.3	0.40	20
51	0.8	110	1.2	0.35	20
63	0.8	163	1.2	0.30	20