









## TECHNICAL DATA

 ID		 OD		 WP		 BP		 VACUUM		 BR		 W		 L	
<i>inch</i>	<i>mm</i>	<i>mm</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>mm</i>	<i>g/m</i>	<i>m</i>					
1"	25.4	36	10	145	30	435	-0.92	110	707	40-46-61					
1 1/4"	32	43	10	145	30	435	-0.92	140	914	40-46-61					
1 1/2"	38	49	10	145	30	435	-0.92	170	1155	40-46-61					
1 3/4"	44.5	56	10	145	30	435	-0.92	210	1363	40-46-61					
2"	50.8	63	10	145	30	435	-0.92	250	1644	40-46-61					
2 1/2"	63.5	76	10	145	30	435	-0.92	310	2129	40-46-61					
3"	76.2	89	10	145	30	435	-0.92	380	2768	40-46-61					
3 1/2"	90	105	10	145	30	435	-0.92	450	3605	40-46-61					
4"	101.6	117	10	145	30	435	-0.92	510	4035	40-46-61					
5"	127	145	10	145	30	435	-0.80	650	6210	40-46-61					
6"	152.4	170	10	145	30	435	-0.80	790	7750	40-46-61					

 -25°C / + 70°C  
-13°F / +158°F

MARKING / BESCHRIFTUNG / MARCATURA: **TRANSFER TAPE OR EMBOSSED**

### OIL S/D HOSE W.P. 10 Bar (145 PSI)

NORMS  
NORMEN  
NORME  
NORMES

ISO 1307

COLOUR  
FARBEN  
COLORI  
COULEUR

