




 ID		 OD	 WP		 BP		 W	 L
<i>inch</i>	<i>mm</i>	<i>mm</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>	<i>g/m</i>	<i>m</i>
3/4	19	30	10	145	30	435	634	40-46-61
1	25.4	37	10	145	30	435	820	40-46-61
1 1/4	32	44	10	145	30	435	1080	40-46-61
1 1/2	38	51	10	145	30	435	1365	40-46-61
1 3/4	44.5	57.5	10	145	30	435	1565	40-46-61
2	50.8	65	10	145	30	435	1910	40-46-61
2 1/2	63.5	77.5	10	145	30	435	2330	40-46-61
3	76.2	92	10	145	30	435	3030	40-46-61
4	101.6	117.5	10	145	30	435	3955	40-46-61

Sanification : Max. 120°C for 15 min. with steam, max. 50°C for 15 min. with caustic soda (5%).
 Sterilisierung : Bei max. 120°C für 15 min. mit Dampf, bei max. 50°C für 15 min. mit Natronlauge (5%).
 Sanificazione : Massimo 120°C per 15 minuti con vapore, massimo 50°C per 15 minuti con soda caustica (5%).
 Sanification : 120°C max. pendant 15 min. avec vapeur à 50°C max. pendant 15 min. avec soude caustique (5%).



-40°C / +70°C
-40°F / +158°F

MARKING / BESCHRIFTUNG / MARCATURA / MARQUAGE: **TRANSFER TAPE OR EMBOSSED**

SPRING /D10

POTABLE WATER DELIVERY HOSE - W.P. 10 BAR (145PSI)

NORMS
 NORMEN
 NORME
 NORMES

ISO 1307
 MEETS FDA REQUIREMENT

COLOUR
 FARBEN
 COLORI
 COULEUR

