

POTABLE WATER DELIVERY HOSE



TUBE : White non-toxic, food quality, taste and odour free, special synthetic rubber.
REINFORCEMENT : High tensile synthetic textile.
COVER : Weather, ozone and abrasion resistant, special synthetic rubber.
APPLICATION : For discharge of potable water.



SEELE : Geschmacks- und geruchsneutral, lebensmittelecht, spezieller synthetischer Gummi, weiss, schadstofffrei.
EINLAGE : Hochzugfeste synthetische Textileinlage.
DECKE : Ozon- und witterungsbeständiger, abriebfester, spezieller synthetischer Gummi.
ANWENDUNG : Zum Durchleiten von Trinkwasser.



SOTTOSTRATO : Gomma speciale sintetica bianca atossica, di qualità alimentare insapore ed inodore.
RINFORZO : Inserzioni tessili ad alta tenacità.
COPERTURA : Gomma speciale sintetica, resistente all'abrasione, all'ozono ed agli agenti atmosferici.
IMPIEGO : Per mandata di acqua potabile.









TUBE : Caoutchouc synthétique spécial blanc, non toxique, qualité alimentaire, anti odeur et ne transmettant pas de goût.
RENFORCEMENT : Insertion textile haute ténacité.
REVÊTEMENT : Caoutchouc synthétique spécial, résistant à l'abrasion, à l'ozone et aux agents atmosphériques.
APPLICATION : Pour refoulement d'eau potable.




POTABLE WATER DELIVERY HOSE

TUBE:	Smooth, white, non-toxic EPDM rubber suitable for potable water.
REINFORCEMENT:	High tensile synthetic textile reinforcement with steel wire helix for strength and suction resistance.
COVER:	Blue synthetic rubber, abrasion, weather, and ozone resistant.
APPLICATION:	Specifically designed for the delivery of potable drinking water.

 ID		 OD	 WP		 BP		 W	 L
<i>inch</i>	<i>mm</i>	<i>mm</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>	<i>g/m</i>	<i>m</i>
3/4 1	19	30	10	145	30	435	634	40-46-61
1 1/4	25.4	37	10	145	30	435	820	40-46-61
1 1/2	32	44	10	145	30	435	1080	40-46-61
1 3/4	38	51	10	145	30	435	1365	40-46-61
2	44.5	57.5	10	145	30	435	1565	40-46-61
2 1/2	50.8	65	10	145	30	435	1910	40-46-61
3	63.5	77.5	10	145	30	435	2330	40-46-61
4	76.2	92	10	145	30	435	3030	40-46-61
	101.6	117.5	10	145	30	435	3955	40-46-61


Sanification : Max. 120°C for 15 min. with steam, max. 50°C for 15 min. with caustic soda (5%).
 Sterilisierung : Bei max. 120°C für 15 min. mit Dampf, bei max. 50°C für 15 min. mit Natronlauge (5%).
 Sanificazione : Massimo 120°C per 15 minuti con vapore, massimo 50°C per 15 minuti con soda caustica (5%).
 Sanification : 120°C max. pendant 15 min. avec vapeur à 50°C max. pendant 15 min. avec soude caustique (5%).



-40°C / +70°C
-40°F / +158°F

MARKING / BESCHRIFTUNG / MARCATURA / MARQUAGE: TRANSFER TAPE OR EMBOSSED

SPRING /D10 POTABLE WATER DELIVERY HOSE - W.P. 10 BAR (145PSI)

NORMS NORMEN NORME NORMES	ISO 1307 MEETS FDA REQUIREMENT	COLOUR FARBEN COLORI COULEUR	
------------------------------------	-----------------------------------	---------------------------------------	---