

FOOD GRADE HOSE S & D



TUBE : White colour non-toxic, taste and odour free, natural rubber.
REINFORCEMENT : High tensile synthetic textile and steel wire helix.
COVER : Weather, ozone and abrasion resistant, special synthetic rubber.
APPLICATION : For suction and discharge of foodstuffs, such as water, fruit juices, etc. Not recommended for oily or fatty foods.



SEELE : Geschmacks- und geruchsneutral, spezieller Naturgummi, weiss, schadstofffrei.
EINLAGE : Hochzugfeste synthetische Textileinlage mit einer Stahldrahtspirale.
DECKE : Ozon- und witterungsbeständiger, abriebfester, spezieller synthetischer Gummi.
ANWENDUNG : Saug- / Druckschlauch für Getränke wie Wasser, Fruchtsäfte, usw. Ungeeignet für öl- und fetthaltige Produkte.



SOTTOSTRATO : Gomma naturale bianca atossica di qualità alimentare, insapore ed inodore.
RINFORZO : Inserzioni tessili ad alta tenacità con spirale di acciaio.
COPERTURA : Gomma speciale sintetica resistente all'abrasione, all'ozono ed agli agenti atmosferici.
IMPIEGO : Per aspirazione e mandata di prodotti alimentari come acqua, succhi di frutta, ecc. Non consigliabile per prodotti contenenti grassi.









TUBE : Caoutchouc naturel couleur blanc, non toxique, anti odeur et ne transmettant pas de goût.
REINFORCEMENT : Insertion textile haute ténacité et spirale en acier noyée.
REVÊTEMENT : Caoutchouc synthétique spécial, résistant à l'abrasion, à l'ozone et aux agents atmosphériques.
APPLICATION : Pour aspiration et refoulement de produits alimentaires non gras, eaux, jus de fruits, etc.



BLUE FOOD GRADE HOSE S&D

TUBE:	White, non-toxic natural rubber that is taste and odour free.
REINFORCEMENT:	High tensile synthetic textile with steel wire helix for strength and suction resistance.
COVER:	Special synthetic rubber resistant to weather, ozone, and abrasion.
APPLICATION:	Designed for suction and discharge of foodstuffs, such as water and fruit juices. (Not recommended for oily or fatty foods)

HOSE TEMPERATURE: -30°C to +120°C

 ID		 OD	 WP		 BP		 W	 L
<i>inch</i>	<i>mm</i>	<i>mm</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>	<i>g/m</i>	<i>m</i>
3/4"	19	30	10	145	30	435	545	40-46-61
1" 1	25.4	37	10	145	30	435	705	40-46-61
1/4" 1	32	44	10	145	30	435	915	40-46-61
1/2" 1	38	51	10	145	30	435	1135	40-46-61
3/4"	44.5	57.5	10	145	30	435	1300	40-46-61
2"	50.8	65	10	145	30	435	1635	40-46-61
2 1/2"	63.5	77.5	10	145	30	435	1890	40-46-61
3"	76.2	92	10	145	30	435	2580	40-46-61
4"	101.6	117.5	10	145	30	435	3500	40-46-61

Sanification : Max. 130 °C for 15 min. with steam, max. 60 °C for 15 min. with caustic soda (5%).

Sterilisierung : Bei max. 130 °C für 15 min. mit Dampf, bei max. 60 °C für 15 min. mit Natronlauge (5%).

Sanificazione : Massimo 130 °C per 15 minuti con vapore, massimo 60 °C per 15 minuti con soda caustica (5%).

Sanification : 130 °C max. pendant 15 min. avec vapeur à 60 °C max. pendant 15 min. avec soude caustique (5%).



-30°C to +120°C

MARKING / BESCHRIFTUNG / MARCATURA / MARQUAGE: TRANSFER TAPE OR EMBOSSED

RAKI D/10 PE

FOOD STUFF DELIVERY HOSE - UHMW-PE - W.P. 10BAR (145PSI)

NORMS
NORMEN
NORME
NORMES

ISO 1307
MEETS FDA REQUIREMENT

COLOUR
FARBEN
COLORI
COULEUR

