

TUBE : Black NBR rubber, suitable for water and general-purpose suction applications.
REINFORCEMENT : High tensile synthetic textile, steel wire helix for suction resistance and structural stability.
COVER : Weather, ozone and abrasion resistant special synthetic rubber.
APPLICATION : For suction and discharge of water, slurry and non-aggressive fluids in industrial and agricultural applications.



SEELE : Schwarzer NBR-Gummi, geeignet für Wasser- und allgemeine Saugförderanwendungen.
EINLAGE : Hochzugfeste synthetische Textileinlage, Stahldrahtspirale für Saugfestigkeit und Formstabilität.
DECKE : Witterungs-, ozon- und abriebfester, speziell synthetischer Gummi.
ANWENDUNG : Saug- und Druckschlauch für Wasser, Schlämme und nicht aggressive Flüssigkeiten in Industrie und Landwirtschaft.











SOTTOSTRATO : Gomma NBR nera, idonea per acqua e applicazioni di aspirazione generali.
RINFORZO : Inserzioni tessili ad alta tenacità con spirale d'acciaio per resistenza al vuoto e stabilità strutturale.
COPERTURA : Gomma sintetica speciale resistente agli agenti atmosferici, all'ozono e all'abrasione.
IMPIEGO : Per aspirazione e mandata di acqua, fanghi e fluidi non aggressivi in applicazioni industriali e agricole.



TUBE : Caoutchouc NBR noir, adapté pour l'eau et les applications d'aspiration générales.
REINFORCEMENT : Insertion textile haute ténacité avec spirale en fil d'acier pour résistance à la dépression et stabilité.
REVÊTEMENT : Caoutchouc synthétique spécial, résistant aux intempéries, à l'ozone et à l'abrasion.
APPLICATION : Pour aspiration et refoulement d'eau, boues et fluides non agressifs dans les applications industrielles et agricoles.

WATER SUCTION HOSE – 16 BAR

INNER TUBE:	Black NBR rubber, suitable for water and general-purpose suction applications.
REINFORCEMENT:	High tensile synthetic textile combined with steel wire helix for excellent suction resistance and structural stability.
COVER:	Weather, ozone and abrasion resistant special synthetic rubber, ensuring long service life in harsh conditions.
APPLICATION:	For suction and discharge of water, slurry and non-aggressive fluids in industrial and agricultural applications.
PERFORMANCE:	Excellent flexibility, very high vacuum resistance, and reliable performance under continuous operation.
HOSE TEMPERATURE:	-25°C / +70°C -13°F / +158°F

 ID		 OD		 WP		 BP		 VACUUM		 BR		 W		 L	
<i>inch</i>	<i>mm</i>	<i>mm</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>psi</i>	<i>bar</i>	<i>mm</i>	<i>g/m</i>	<i>m</i>			
3/4"	19	29	16	232	48	696	-0.92	75	572	40-46-61					
1"	25.4	35	16	232	48	696	-0.92	100	715	40-46-61					
1/4"	32	42	16	232	48	696	-0.92	130	915	40-46-61					
1 1/2"	38	50	16	232	48	696	-0.92	160	1341	40-46-61					
1 3/4"	44.5	57.5	16	232	48	696	-0.92	195	1736	40-46-61					
2"	50.8	64	16	232	48	696	-0.92	240	1920	40-46-61					
2 1/2"	63.5	76.5	16	232	48	696	-0.92	300	2470	40-46-61					
2 3/4"	70	84	16	232	48	696	-0.92	340	2785	40-46-61					
3"	76.2	90	16	232	48	696	-0.92	380	3050	40-46-61					
4"	101.6	118	16	232	48	696	-0.92	525	4855	40-46-61					
5"	127	144	16	232	48	696	-0.80	700	6340	40-46-61					
6"	152.4	173	16	232	48	696	-0.80	850	9390	40-46-61					
8"	203.2	228	16	232	48	696	-0.80	1250	14880	20-30					
10"	254	284	16	232	48	696	-0.80	1650	20755	10					
12"	304.8	339	16	232	48	696	-0.80	2100	28480	10					



-25.°C/+70°C

-13.°F/+158°F

MARKING / BESCHRIFTUNG / MARCATURA / MARQUAGE: **TRANSFER TAPE OR EMBOSSED**

WATER S/D HOSE W.P. 16 Bar (232 PSI)

NORMS
NORMEN
NORME
NORMES

ISO 1307

COLOUR
FARBEN
COLORI
COULEUR

