



Model	BN-AB30WS126-K1	BN-AB60WS126-K1	BN-AB90WS126-K1	BN-AB120WS126-K1
Power	30W	60W	90W	120W
LED Type	SMD3030	SMD3030	SMD3030	SMD3030
Material	ABS	ABS	ABS	ABS
IP Rating	IP66	IP66	IP66	IP66
Size	15.4 * 7.7 * 2.2"	19.3 * 8.7 * 2.2"	24.4 * 9.5 * 2.2"	28.4 * 9.5 * 2.2"
Color Temperature	3000K	3000K	3000K	3000K
Solar Panel	6V 8W	6V 10W	8V 10W	6V 10W
Charging Time	12-16 Hours	12-16 Hours	12-16 Hours	12-16 Hours
Working Time	Up to 36 Hours	Up to 36 Hours	Up to 36 Hours	Up to 36 Hours
Charging Type	Solar	Solar	Solar	Solar
Luminous Efficiency	130 lm/W	130 lm/W	130 lm/W	130 lm/W
Country of Origin	Korea	Korea	Korea	Korea

KEY ADVANTAGES

- Insect-Reducing Lighting
- Up to 94% Energy Saving
- Solar Powered (No Wiring)
- Long Runtime (Auto On/Off)
- IP66 Waterproof
- Wide Coverage Brightness

APPLICATIONS

- Streets & Parks
- Parking & Commercial
- Residential & Pathways
- Industrial & Construction
- Security Lighting
- Remote Areas

