

CAPACITORES DE MARCHA A 250 VCA Y 450 VCA

MEDIDAS EN MILÍMETROS

Capacidad	400 V-450 VAC	400 V-450 VAC	250 V- 300 VAC	250 V- 300 VAC
	D (mm)	H (mm)	D (mm)	H (mm)
1uF	30	57	30	57
1.5uF	30	57	30	57
2uF	30	57	30	57
2.5uF	30	57	30	57
3.0uF	30	57	30	57
3.5uF	30	70	30	57
4uF	30	70	30	57
4.5uF	30	70	30	57
5uF	30	70	30	57
6uF	30	70	30	57
7uF	30	70	30	57
7.5uF	30	70	30	57
8uF	35	60	35	60
9uF	35	60	35	60
10uF	35	70	35	60
12uF	35	70	35	60
12.5uF	35	70	35	70
14uF	35	70	35	70
15uF	35	70	35	70
16uF	40	70	35	70
18uF	40	70	35	70
20uF	40	70	35	70
22uF	40	70	35	70
24uF	40	70	35	70
25uF	40	80	35	70
30uF	45	92	40	70
35uF	45	92	40	70
40uF	45	92	40	70
45uF	45	92	40	70
50uF	50	92	45	92
55uF	50	100	45	92
60uF	50	116	45	92
65uF	50	116	45	92
70uF	50	116	45	92
80uF	60	120	50	100
90uF	60	120	50	100
100uF	60	120	50	116

