



FF120 RANGE

Filter Fan

Features	UoM	FF120230VAC	FF120115VAC	FF12024VDC	FF12048VDC
Air Flow Rate With Mat	m³/h	24/30	24/30	40	40
Power Supply	V - Hz	230 1~50-60	115 1~50-60	24VDC	48VDC
Dimensions HxWxD	mm	120*120*64	120*120*64	120*120*64	120*120*64
Cut-Out Dimensions	mm	92*92	92*92	92*92	92*92
Power Consumption	W	13 10	13 10	4.8	5.28
Max Current	A	0.078/0.062	0.078/0.062	0.2	0.11
Electrical Connection	-	Faston	Faston	Lead-Terminal	Lead-Terminal
IP Rating EN60529	-	IP54	IP54	IP54	IP54
Noise Level	dB(A)	27 30	27 30	30	30
Fan + Filter airflow rate	m³/h	17-21	17-21	28	28
Filter (Eurovent)	-	EU4	EU4	EU4	EU4
Filter Materia Din	-	G4 RoHS ABS	G4 RoHS ABS	G4 RoHS ABS	G4 RoHS ABS
Weight	Kg	0.395	0.395	0.245	0.245
Conformity	-	CE	CE	CE	CE
Operating Temperature	°C	-25 to +65°C	-25 to +65°C	-25 to +65°C	-25 to +65°C
Colour	RAL	7035	7035	7035	7035