



FF152 RANGE

Filter Fan

Features	UoM	FF152230VAC	FF152115VAC	FF15224VDC	FF15248VDC	FF15224VAC
Air Flow Rate With Mat	m ³ /h	56-61	56-61	60	60	60
Power Supply	V - Hz	230 1~50-60	115 1~50-60	24VDC	48VDC	24VAC
Dimensions HxWxD	mm	148x148x67	148x148x67	148x148x67	148x148x67	148x148x67
Cut-Out Dimensions	mm	125*125	125*125	125*125	125*125	125*125
Power Consumption	W	21-18	21-18	9.6	9.6	15-16
Max Current	A	0.13-0.11	0.22-0.18	0.4	0.2	0.63
Electrical Connection	-	Faston	Faston	Lead-Terminal	Lead-Terminal	Lead-Terminal
IP Rating EN60529	-	IP54	IP54	IP54	IP54	IP54
Noise Level	dB(A)	43-48	43-48	48	48	43-48
Fan + Filter airflow rate	m ³ /h	41-44	41-44	43	43	41-44
Filter (Eurovent)	-	EU4	EU4	EU4	EU4	EU4
Filter Materia Din	-	G4 RoHS ABS	G4 RoHS ABS	G4 RoHS ABS	G4 RoHS ABS	G4 RoHS ABS
Weight	Kg	0.6	0.6	0.45	0.45	0.45
Conformity	-	CE	CE	CE	CE	CE
Operating Temperature	°C	-25 to +65°C	-25 to +65°C	-25 to +65°C	-25 to +65°C	-25 to +65°C
Colour	RAL	7035	7035	7035	7035	7035

• FILTER - F152