



FF204H RANGE

Filter Fan

Features	UoM	FF204H230VAC	FF204H115VAC	FF204H415VAC	FF204H24VDC	FF204H48VDC
Air Flow Rate With Mat	m³/h	180-200	180-200	180-200	200	200
Power Supply	V - Hz	230 1~50-60	115 1~50-60	415 3~50-60	24VDC	48VDC
Dimensions HxWxD	mm	204*204*80	204*204*80	204*204*80	204*204*80	204*204*80
Cut-Out Dimensions	mm	177*177	177*177	177*177	177*177	177*177
Power Consumption	W	26-28	26-28	26-28	9.6	12
Max Current	A	0.12-0.11	0.12-0.11	0.13 -0.11	0.4	0.5
Electrical Connection	-	Faston	Faston	Faston	Lead Terminal	Lead Terminal
IP Rating EN60529	-	IP54	IP54	IP54	IP54	IP54
Noise Level	dB(A)	43-48	43-48	43-48	48	48
Fan + Filter airflow rate	m³/h	130-150	130-150	130-150	150	150
Filter (Eurovent)	-	EU4	EU4	EU4	EU4	EU4
Filter Materia Din	-	G4 RoHS ABS	G4 RoHS ABS	G4 RoHS ABS	G4 RoHS ABS	G4 RoHS ABS
Weight	Kg	1.08	1.08	1.08	1.08	1.08
Conformity	-	CE	CE	CE	CE	CE
Operating Temperature	°C	-25 to +65°C	-25 to +65°C	-25 to +65°C	-25 to +65°C	-25 to +65°C
Colour	RAL	7035	7035	7035	7035	7035

• FILTER - F204