



FF255 RANGE

Filter Fan

Features	UoM	FF255230VAC	FF255115VAC	FF255415VAC	FF25524VDC	FF25548VDC
Air Flow Rate With Mat	m ³ /h	230 - 260	230 - 260	230 - 262	250	250
Power Supply	V - Hz	230 1~50-60	115 1~50-60	400 3~50-60	24VDC	48VDC
Dimensions HxWxD	mm	255*255*214	255*255*214	255*255*214	255*255*214	255*255*214
Cut-Out Dimensions	mm	223*223	223*223	223*223	223*223	223*223
Power Consumption	W	48-40	48-40	26-28	24	12
Max Current	A	0.43-0.4	0.43-0.4	0.13-0.11	1	0.5
Electrical Connection	-	Faston	Faston	Faston	Lead Terminal	Lead Terminal
IP Rating EN60529	-	IP54	IP54	IP54	IP54	IP54
Noise Level	dB(A)	52 - 62	52 - 62	52-62	62	62
Fan + Filter airflow rate	m ³ /h	195 - 220	195 - 220	195 - 220	200	200
Filter (Eurovent)	-	EU4	EU4	EU4	EU4	EU4
Filter Materia Din	-	G4 RoHS ABS	G4 RoHS ABS	G4 RoHS ABS	G4 RoHS ABS	G4 RoHS ABS
Weight	Kg	1.32	1.32	1.32	1.32	1.32
Conformity	-	CE	CE	CE	CE	CE
Operating Temperature	°C	-25 to +65°C	-25 to +65°C	-25 to +65°C	-25 to +65°C	-25 to +65°C
Colour	RAL	7035	7035	7035	7035	7035