

### General Specifications

- Display 7\*17mm digits LCD display, with white LED backlight
- Capacities 220g
- Pan size  $\Phi 90\text{mm}$
- Keyboard 6 keys (Membrane keyboard)
- Housing ABS plastic
- Max. Divisions 2,200,000d
- Operating Temp.  $+10^{\circ}\text{C} \sim +30^{\circ}\text{C}$
- Power Input :AC 100~240V, 50~60Hz; Output:DC 12V 2000mA
- Packing Master carton packing, dimension  $0.065\text{m}^3$



- Standard stainless steel pan
- Electromagnetic force loadcell
- Die-cast aluminum bottom cover
- Internal and external calibration selectable
- Applications: 1. Basic weighing 2. Counting 3. Percentage weighing  
4. Weighing units conversion
- Standard RS-232 interface can connect to computer and printer

Model Name	Capacity	Readability	Division	Pan Size	Approx. weight
DHB+-220	220g	0.0001g	2,200,000d	Φ90mm	3.7kg
DHB+-I-220	220g	0.0001g	2,200,000d	Φ90mm	3.7kg

### Options



### Print Formats

#### Receipt Format

```
G:          93.8162g
G:          93.8162g
U.W:       4.9376g/pcs
PCS:        19.pcs

G:          93.8162g
PCT:       134.02%
```

#### Label Format

```
2019/03/25  09:00
G:          93.8162g
```

```
2019/03/25  09:05
G:          93.8162g
U.W:       4.9376g/pcs
PCS:        19.pcs
```

```
2019/03/25  09:10
G:          93.8162g
PCT:       134.02%
```

### Dimensions(mm)

