

General Specifications

- | | |
|-------------------|--|
| • Display | 25mm LCD display with white LED backlight |
| • Capacities | 30kg~600kg |
| • Keyboard | 5 keys (Mechanical switch) |
| • Housing | ABS plastic |
| • Max. Divisions | 3,000d/6,000d |
| • ADC | Sigma delta |
| • ADC update | ≤1/10 second |
| • Operating Temp. | 0°C~+40°C |
| • Power | AC adapter (12V/500mA), Internal rechargeable battery (lead acid 6V/1.2Ah) |



- Easy to use front panel configuration
- SGS 500% safety approval
- Applications: 1. Display hold 2. Weighing unit conversion 3. Tare
- S hook (30kg), G hook (>30kg)
- Battery provides up to 40 hours of continuous use (without backlight)
- Optional hand held remote control device (except on the 30kg unit)
- Optional rear display



DR Crane Scales

Model Number	Capacity	Readability	Division	Approx. weight	Approval
DR-30K	30kg	10g	3,000d	1.8kg	CE, SGS
DR-60K	60kg	10g	6,000d	2kg	CE, SGS
DR-150K	150kg	20g	7,500d	2kg	CE, SGS
DR-300K	300kg	50g	6,000d	2kg	CE, SGS
DR-600K	600kg	100g	6,000d	2kg	CE, SGS

Options



Dimensions(mm)

