

ROW Weighing Scale

General Specifications

- Display 22mm digit LCD display, with white LED backlight
- Capacities 3kg, 6kg, 15kg
- Pan size Ø232mm
- Keyboard 6 keys (Mechanical switch)
- Housing ABS plastic indicator
- Max. Divisions 30,000d; 6,000e; 2x3,000e
- ADC Sigma delta
- ADC update ≤1/10 second
- Operating Temp. 0°C~+40°C
- Power AC adapter (12V/500mA), Ni-MH battery (1.2V/2000mAh x 6)
- Gross weight 3.8kg



- Stainless steel pan
- An economical general purpose instrument
- Applications: 1. Net/gross shift 2. Weighing unit conversion 3. Check weighing
- Battery provides up to 40 hours of continuous use (without backlight)
- Standard RS-232 to connect to computer



ROW Weighing Scale

Model Name	Capacity	Readability	Division	Approx. weight	Approval
ROW-3K	3kg	0.1g	30,000d	3.8kg	CE
ROW-6K	6kg	0.2g	30,000d	3.8kg	CE
ROW-15K	15kg	0.5g	30,000d	3.8kg	CE
ROW-3K-M	3kg	0.5g	6,000e	3.8kg	CE,OIML
ROW-6K-M	6kg	1g	6,000e	3.8kg	CE,OIML
ROW-15K-M	15kg	2g	6,000e	3.8kg	CE,OIML
ROW-3K-MR	3kg	0.5g/1g	2x3,000e	3.8kg	CE,OIML
ROW-6K-MR	6kg	1g/2g	2x3,000e	3.8kg	CE,OIML
ROW-15K-MR	15kg	2g/5g	2x3,000e	3.8kg	CE,OIML

Options



Dimensions(mm)

