

VW-LC Weighing Indicator

CE



Features

- Flexible positioning, e.g. free-standing
- Full function: accumulation, checkweighing, Gross/Net shift, simple counting, Printing.
- Weighing with tolerance range (check-weighing): a visual and audible signal helps with portioning, dispensing or grading
- Animal function: When the weighing conditions are unstable, a stable weight is calculated determining an average value
- RS-232 interface can connect to PC or TPup printer.
- Connection parts to install on pole for platform scale

Technical Data

- Display:** 48mm digit LCD display with white backlight
- Power:** AC adapter (100~240VAC/5V/1A), rechargeable battery (lithium battery 3.7V/4Ah), operation time 50 hours
- Operation temperature:** -10°C~40°C

Accessories

- Mounted to the wall
- RS-232 cable for PC
- RS-232 cable for printer
- TPuP Printer

Standard



| Model | VW-LC |
|------------------------------|--------------------|
| Housing | ABS plastic |
| Dimensions | 252x152x133 mm |
| Net weight | 1.6kg |
| nmax. | 15000 |
| Load cell input resistance | 87-1400 ohms |
| Load cell excitation voltage | 3VDC |
| Load cell connector | Air connector 5pin |


* Specification to change without notice



Bracket



Printer



Rechargeable lithium battery



AC adapter