

DOWNLIGHT SURFACE IP20



PLANUM 4829
8W/12W
P.1



OPTIX 5061
5W
P.2



OPTIX 5062
15W
P.3



OPTIX 5063
20W
P.4




OPTIX 5064
30W
P.5



KORPER 5052
20W
P.6



KORPER 5053
40W
P.7



KORPER 5054
60W
P.8



KORPER 5055
12W
P.9



KORPER 5056
20W
P.10



FOCUS 5051
7W/10W
P.11



FLACHE 5050
10W/18W/25W/42W/50W/70W/85W
P.12-13



ORBIS 4840
12W/18W
P.14




GELENK 5057
12W
P.15




GELENK 5058
12W
P.16



PLATTE 5065
7W
P.17



PLATTE 5066
7*2W
P.18



PLATTE 5067
7*3W
P.19



PLATTE 5068
7*4W
P.20



PLATTE 5069
7*6W
P.21



PLATTE 5070
7*2W
P.22



PLATTE 5071
7*3W
P.23



PLATTE 5072
7*5W
P.24



PLATTE 5073
7W
P.25



PLATTE 5074
7*2W
P.26



PLATTE 5075
7*3W
P.27



SENSIO 4441
12W
P.28




SENSIO 4442
12W
P.29

4829

Downlight Recessed. Ambience/UGR

PLANUMseries

ArchitecturalINDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|----------|---------------|---------------|---------|--------------|
| COB LED | 8W | ∅78x62mm | 930lm | 640lm | ● 2700K | 482912.B.P.C |
| COB LED | 8W | ∅78x62mm | 992lm | 683lm | ● 3000K | 482913.B.P.C |
| COB LED | 8W | ∅78x62mm | 1054lm | 726lm | ○ 4000K | 482914.B.P.C |
| COB LED | 8W | ∅78x62mm | 1095lm | 754lm | ○ 5000K | 482915.B.P.C |
| COB LED | 12W | ∅96x69mm | 930lm | 640lm | ● 2700K | 482912.B.P.C |
| COB LED | 12W | ∅96x69mm | 992lm | 683lm | ● 3000K | 482913.B.P.C |
| COB LED | 12W | ∅96x69mm | 1054lm | 726lm | ○ 4000K | 482914.B.P.C |
| COB LED | 12W | ∅96x69mm | 1095lm | 754lm | ○ 5000K | 482915.B.P.C |

Beam Angle: B(1-24° 2-36° 3-50°)

Power Supply: P(1-0n/Off)

Colour Finish: C(WW-White/White BB - Black/Black)




White / White Black / Black

5061

Downlight Recessed. Ambience/UGR

OPTIXseries

ArchitecturalINDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|------------|---------------|---------------|---------|--------------|
| COB LED | 5W | 50x50x83mm | 656lm | 482lm | ● 2700K | 506112.B.P.C |
| COB LED | 5W | 50x50x83mm | 700lm | 514lm | ● 3000K | 506113.B.P.C |
| COB LED | 5W | 50x50x83mm | 744lm | 546lm | ○ 4000K | 506114.B.P.C |
| COB LED | 5W | 50x50x83mm | 773lm | 568lm | ○ 5000K | 506115.B.P.C |

Beam Angle: B(1-50° 2-80°)

Power Supply: P(1-0n/Off)

Colour Finish: C(WW-White/White BB-Black/Black)



White / White Black / Black

5062

Downlight Recessed. Ambience/UGR

OPTIXseries

Architectural INDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|------------|---------------|---------------|---------|--------------|
| COB LED | 15W | 86x86x88mm | 1968lm | 1405lm | ● 2700K | 506212.B.P.C |
| COB LED | 15W | 86x86x88mm | 2100lm | 1499lm | ● 3000K | 506213.B.P.C |
| COB LED | 15W | 86x86x88mm | 2232lm | 1594lm | ○ 4000K | 506214.B.P.C |
| COB LED | 15W | 86x86x88mm | 2318lm | 1655lm | ○ 5000K | 506215.B.P.C |

Beam Angle: B(1-50° 2-80°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW-White/White BB - Black/Black)



5063

Downlight Recessed. Ambience/UGR

OPTIXseries

Architectural INDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|-------------|---------------|---------------|---------|--------------|
| COB LED | 20W | 203x51x88mm | 2624lm | 1806lm | ● 2700K | 506312.B.P.C |
| COB LED | 20W | 203x51x88mm | 2800lm | 1928lm | ● 3000K | 506313.B.P.C |
| COB LED | 20W | 203x51x88mm | 2976lm | 2049lm | ○ 4000K | 506314.B.P.C |
| COB LED | 20W | 203x51x88mm | 3091lm | 2128lm | ○ 5000K | 506315.B.P.C |

Beam Angle: B(1-50° 2-80°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW-White/White BB-Black/Black)



5064

Downlight Recessed. Ambience/UGR

OPTIXseries

Architectural INDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|---------------------|
| COB LED | 30W | 125x125x88mm | 3935lm | 3011lm | ● 2700K | 506412.B.P.C |
| COB LED | 30W | 125x125x88mm | 4200lm | 3213lm | ● 3000K | 506413.B.P.C |
| COB LED | 30W | 125x125x88mm | 4465lm | 3415lm | ○ 4000K | 506414.B.P.C |
| COB LED | 30W | 125x125x88mm | 4637lm | 3547lm | ○ 5000K | 506415.B.P.C |

Beam Angle: B(1-50° 2-80°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW-White/White BB-Black/Black)




5052

Downlight Recessed. Ambience/UGR

KORPERseries

Architectural INDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|---------------------|
| SMD LED | 20W | 200x200x39mm | 2436lm | 1579lm | ● 2700K | 505212.B.P.C |
| SMD LED | 20W | 200x200x39mm | 2600lm | 1685lm | ● 3000K | 505213.B.P.C |
| SMD LED | 20W | 200x200x39mm | 2764lm | 1791lm | ○ 4000K | 505214.B.P.C |
| SMD LED | 20W | 200x200x39mm | 2870lm | 1860lm | ○ 5000K | 505215.B.P.C |

Beam Angle: B(1-15° 2-24° 3-36°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW - White / White WB - White / Black WMS - White / Matt Silver BB - Black / Black BW - Black / White BMS - Black / Matt Silver)




5053

Downlight Recessed. Ambience/UGR

KORPERseries

ArchitecturalINDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|--------------|
| SMD LED | 40W | 368x158x39mm | 4872lm | 3333lm | ● 2700K | 505312.B.P.C |
| SMD LED | 40W | 368x158x39mm | 5200lm | 3557lm | ● 3000K | 505313.B.P.C |
| SMD LED | 40W | 368x158x39mm | 5528lm | 3781lm | ● 4000K | 505314.B.P.C |
| SMD LED | 40W | 368x158x39mm | 5741lm | 3927lm | ● 5000K | 505315.B.P.C |

Beam Angle: B(1-15° 2-24° 3-36°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW - White / White WB - White / Black WMS - White / Matt Silver BB - Black / Black BW - Black / White BMS - Black / Matt Silver)




5054

Downlight Recessed. Ambience/UGR

KORPERseries

ArchitecturalINDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|--------------|
| SMD LED | 60W | 368x248x39mm | 7309lm | 5262lm | ● 2700K | 505412.B.P.C |
| SMD LED | 60W | 368x248x39mm | 7800lm | 5616lm | ● 3000K | 505413.B.P.C |
| SMD LED | 60W | 368x248x39mm | 8291lm | 5970lm | ● 4000K | 505414.B.P.C |
| SMD LED | 60W | 368x248x39mm | 8611lm | 6200lm | ● 5000K | 505415.B.P.C |

Beam Angle: B(1-15° 2-24° 3-36°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW - White / White WB - White / Black WMS - White / Matt SilverBB - Black / Black BW - Black / White BMS - Black / Matt Silver)




5055

Downlight Recessed. Ambience/UGR

KORPERseries

ArchitecturalINDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|-----------|---------------|---------------|---------|--------------|
| COB LED | 12W | ø89x100mm | 1462lm | 1052lm | ● 2700K | 505512.B.P.C |
| COB LED | 12W | ø89x100mm | 1560lm | 1123lm | ● 3000K | 505513.B.P.C |
| COB LED | 12W | ø89x100mm | 1658lm | 1194lm | ● 4000K | 505514.B.P.C |
| COB LED | 12W | ø89x100mm | 1722lm | 1240lm | ● 5000K | 505515.B.P.C |

Beam Angle: B(1-15° 2-24° 3-36°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW - White / White WB - White / Black WMS - White / Matt Silver BW - Black / White BMS - Black / Matt Silver Silver BB - Black / Black)




5056

Downlight Recessed. Ambience/UGR

KORPERseries

ArchitecturalINDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|------------|---------------|---------------|---------|--------------|
| COB LED | 20W | ø109x100mm | 2436lm | 1579lm | ● 2700K | 505612.B.P.C |
| COB LED | 20W | ø109x100mm | 2600lm | 1685lm | ● 3000K | 505613.B.P.C |
| COB LED | 20W | ø109x100mm | 2764lm | 1761lm | ● 4000K | 505614.B.P.C |
| COB LED | 20W | ø109x100mm | 2870lm | 1860lm | ● 5000K | 505615.B.P.C |

Beam Angle: B(1-15° 2-24° 3-36°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW - White / White WB - White / Black WMS - White / Matt Silver BW - Black / White BMS - Black / Matt Silver Silver BB - Black / Black)



5051

Downlight Recessed. Ambience/UGR

FOKUSseries

Architectural INDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|----------|---------------|---------------|---------|--------------|
| COB LED | 7W | ∅60x60mm | 813lm | 502lm | ● 2700K | 505112.B.P.C |
| COB LED | 7W | ∅60x60mm | 868lm | 536lm | ● 3000K | 505113.B.P.C |
| COB LED | 7W | ∅60x60mm | 923lm | 569lm | ● 4000K | 505114.B.P.C |
| COB LED | 7W | ∅60x60mm | 958lm | 591lm | ● 5000K | 505115.B.P.C |
| COB LED | 10W | ∅85x75mm | 1162lm | 784lm | ● 2700K | 505122.B.P.C |
| COB LED | 10W | ∅85x75mm | 1240lm | 837lm | ● 3000K | 505123.B.P.C |
| COB LED | 10W | ∅85x75mm | 1318lm | 890lm | ● 4000K | 505124.B.P.C |
| COB LED | 10W | ∅85x75mm | 1369lm | 924lm | ● 5000K | 505125.B.P.C |

Beam Angle: B(1-5°-2-8°-3-10°-4-25°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW-White/White BB-Black/Black)



5050

Downlight Recessed. Ambience/UGR

FLACHEseries

Architectural INDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|--------------|
| SMD LED | 10W | ∅85x74mm | 1265lm | 911lm | ● 2700K | 505012.B.P.C |
| SMD LED | 10W | ∅85x74mm | 1350lm | 972lm | ● 3000K | 505013.B.P.C |
| SMD LED | 10W | ∅85x74mm | 1435lm | 1033lm | ● 4000K | 505014.B.P.C |
| SMD LED | 10W | ∅85x74mm | 1490lm | 1073lm | ● 5000K | 505015.B.P.C |
| SMD LED | 18W | ∅115x95mm | 2277lm | 1639lm | ● 2700K | 505022.B.P.C |
| SMD LED | 18W | ∅115x95mm | 2430lm | 1750lm | ● 3000K | 505023.B.P.C |
| SMD LED | 18W | ∅115x95mm | 2583lm | 1860lm | ● 4000K | 505024.B.P.C |
| SMD LED | 18W | ∅115x95mm | 2683lm | 1932lm | ● 5000K | 505025.B.P.C |
| SMD LED | 25W | ∅135x110.5mm | 3162lm | 2186lm | ● 2700K | 505032.B.P.C |
| SMD LED | 25W | ∅135x110.5mm | 3375lm | 2333lm | ● 3000K | 505033.B.P.C |
| SMD LED | 25W | ∅135x110.5mm | 3588lm | 2480lm | ● 4000K | 505034.B.P.C |
| SMD LED | 25W | ∅135x110.5mm | 3726lm | 2575lm | ● 5000K | 505035.B.P.C |
| SMD LED | 42W | ∅165x136mm | 5313lm | 3643lm | ● 2700K | 505042.B.P.C |
| SMD LED | 42W | ∅165x136mm | 5670lm | 3888lm | ● 3000K | 505043.B.P.C |
| SMD LED | 42W | ∅165x136mm | 6027lm | 4133lm | ● 4000K | 505044.B.P.C |
| SMD LED | 42W | ∅165x136mm | 6260lm | 4292lm | ● 5000K | 505045.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW-White/White BB-Black/Black)




5050

Downlight Recessed. Ambience/UGR

FLACHE series

Architectural INDOOR



OSRAM 50,000hrs LED LM80 Fixed Ra >90 UGR <19 IP20 5 Years Warranty AC220-240V 50/60Hz CE Die-cast Aluminum Heatsink 120°

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|--------------|
| SMD LED | 50W | ∅190x156.6mm | 6325lm | 4736lm | ● 2700K | 505052.B.P.C |
| SMD LED | 50W | ∅190x156.6mm | 6750lm | 5054lm | ● 3000K | 505053.B.P.C |
| SMD LED | 50W | ∅190x156.6mm | 7175lm | 5373lm | ○ 4000K | 505054.B.P.C |
| SMD LED | 50W | ∅190x156.6mm | 7452lm | 5580lm | ○ 5000K | 505055.B.P.C |
| SMD LED | 70W | ∅215x176mm | 8855lm | 6148lm | ● 2700K | 505062.B.P.C |
| SMD LED | 70W | ∅215x176mm | 9450lm | 6561lm | ● 3000K | 505063.B.P.C |
| SMD LED | 70W | ∅215x176mm | 10045lm | 6974lm | ○ 4000K | 505064.B.P.C |
| SMD LED | 70W | ∅215x176mm | 10433lm | 7243lm | ○ 5000K | 505065.B.P.C |
| SMD LED | 85W | ∅240x201mm | 10752lm | 7172lm | ● 2700K | 505072.B.P.C |
| SMD LED | 85W | ∅240x201mm | 11475lm | 7655lm | ● 3000K | 505073.B.P.C |
| SMD LED | 85W | ∅240x201mm | 12198lm | 8137lm | ○ 4000K | 505074.B.P.C |
| SMD LED | 85W | ∅240x201mm | 12668lm | 8451lm | ○ 5000K | 505075.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW-White/White)BB-Black/Black



White / White Black / Black

4840

Downlight Surface. Ambience/UGR

ORBIS series

Architectural INDOOR



OSRAM 50,000hrs LED LM80 Fixed Ra >90 UGR <19 IP20 5 Years Warranty AC220-240V 50/60Hz CE Die-cast Aluminum Heatsink 15° 24° 36° 55°

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|-----------|---------------|---------------|-------|--------------|
| COB LED | 12W | ∅65x108mm | ● 1394lm | ● 1019lm | 2700K | 484012.B.P.C |
| COB LED | 12W | ∅65x108mm | ● 1488lm | ● 1087lm | 3000K | 484013.B.P.C |
| COB LED | 12W | ∅65x108mm | ○ 1582lm | ○ 1156lm | 4000K | 484014.B.P.C |
| COB LED | 12W | ∅65x108mm | ○ 1643lm | ○ 1201lm | 5000K | 484015.B.P.C |
| COB LED | 18W | ∅90x130mm | ● 2091lm | ● 1638lm | 2700K | 484022.B.P.C |
| COB LED | 18W | ∅90x130mm | ● 2232lm | ● 1748lm | 3000K | 484023.B.P.C |
| COB LED | 18W | ∅90x130mm | ○ 2373lm | ○ 1858lm | 4000K | 484024.B.P.C |
| COB LED | 18W | ∅90x130mm | ○ 2464lm | ○ 1929lm | 5000K | 484025.B.P.C |

Beam Angle: B(1-15° 2-24° 3-36° 4-55°)

Power Supply: P(1-On/Off 2-Phase Dim 3-DALI Dim 4-0-10V Dim)

Colour Finish: C(WW-White/White)BB-Black/Black GG-Gold/Gold GB-Gold/Black WB-White/Black BW-Black/White SS-Silver/Silver SB-Silver/Black




White / White Black / Black Gold / Gold Gold / Black White / Black Black / Black Silver / Silver Silver / Black

5057

Downlight Recessed. Ambience/UGR

GELENKseries

Architectural INDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|-------------|---------------|---------------|---------|--------------|
| COB LED | 12W | 79x79x110mm | 1394lm | 1092lm | ● 2700K | 505712.B.P.C |
| COB LED | 12W | 79x79x110mm | 1488lm | 1165lm | ● 3000K | 505713.B.P.C |
| COB LED | 12W | 79x79x110mm | 1582lm | 1239lm | ● 4000K | 505714.B.P.C |
| COB LED | 12W | 79x79x110mm | 1643lm | 1286lm | ● 5000K | 505715.B.P.C |

Beam Angle: B(1-10° 2-23° 3-36°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW White/ White WB White/ Black BB - Black/ Black)




5058

Downlight Recessed. Ambience/UGR

GELENKseries

Architectural INDOOR



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|-------------|---------------|---------------|---------|--------------|
| COB LED | 12W | 79x79x110mm | 1394lm | 1092lm | ● 2700K | 505812.B.P.C |
| COB LED | 12W | 79x79x110mm | 1488lm | 1165lm | ● 3000K | 505813.B.P.C |
| COB LED | 12W | 79x79x110mm | 1582lm | 1239lm | ● 4000K | 505814.B.P.C |
| COB LED | 12W | 79x79x110mm | 1643lm | 1286lm | ● 5000K | 505815.B.P.C |

Beam Angle: B(1-10° 2-23° 3-36°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW White/ White WB White/ Black BB - Black/ Black)




5065

Downlight Recessed. Ambience/UGR

PLATTEseries



ArchitecturalINDOOR



5066

Downlight Recessed. Ambience/UGR

PLATTEseries



| | | | | | | | | | | | |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|
| OSRAM 50,000hrs | SMD | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Gypsum | 120° |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|--------------|
| SMD LED | 7W | 110x110x70mm | 813lm | 535lm | ● 2700K | 506512.B.P.C |
| SMD LED | 7W | 110x110x70mm | 868lm | 571lm | ● 3000K | 506513.B.P.C |
| SMD LED | 7W | 110x110x70mm | 923lm | 607lm | ● 4000K | 506514.B.P.C |
| SMD LED | 7W | 110x110x70mm | 958lm | 631lm | ● 5000K | 506515.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(W-White)



White

| | | | | | | | | | | | |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|
| OSRAM 50,000hrs | SMD | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Gypsum | 120° |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|--------------|
| SMD LED | 7x2W | 210x110x70mm | 1627lm | 1004lm | ● 2700K | 506612.B.P.C |
| SMD LED | 7x2W | 210x110x70mm | 1736lm | 1071lm | ● 3000K | 506613.B.P.C |
| SMD LED | 7x2W | 210x110x70mm | 1845lm | 1139lm | ● 4000K | 506614.B.P.C |
| SMD LED | 7x2W | 210x110x70mm | 1917lm | 1183lm | ● 5000K | 506615.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(W-White)





White

5067

Downlight Recessed. Ambience/UGR

PLATTEseries

ArchitecturalINDOOR



| | | | | | | | | | | | |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|
| OSRAM 50,000hrs | SMD | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Gypsum | 120° |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|--------------|
| SMD LED | 7x3W | 310x110x70mm | 2324lm | 1506lm | ● 2700K | 506712.B.P.C |
| SMD LED | 7x3W | 310x110x70mm | 2480lm | 1607lm | ● 3000K | 506713.B.P.C |
| SMD LED | 7x3W | 310x110x70mm | 2636lm | 1708lm | ○ 4000K | 506714.B.P.C |
| SMD LED | 7x3W | 310x110x70mm | 2738lm | 1774lm | ○ 5000K | 506715.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(W-White)




5068

Downlight Recessed. Ambience/UGR

PLATTEseries

ArchitecturalINDOOR



| | | | | | | | | | | | |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|
| OSRAM 50,000hrs | SMD | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Gypsum | 120° |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|--------------|
| SMD LED | 7x4W | 210x210x70mm | 3043lm | 2035lm | ● 2700K | 506812.B.P.C |
| SMD LED | 7x4W | 210x210x70mm | 3248lm | 2172lm | ● 3000K | 506813.B.P.C |
| SMD LED | 7x4W | 210x210x70mm | 3453lm | 2308lm | ○ 4000K | 506814.B.P.C |
| SMD LED | 7x4W | 210x210x70mm | 3586lm | 2397lm | ○ 5000K | 506815.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(W-White)




5069

Downlight Recessed. Ambience/UGR

PLATTEseries

Architectural INDOOR




5070

Downlight Recessed. Ambience/UGR

PLATTEseries

Architectural INDOOR



| | | | | | | | | | | | |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|
| OSRAM 50,000hrs | SMD | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Gypsum | 120° |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|--------------|
| SMD LED | 7x6W | 310x210x70mm | 4648lm | 3012lm | ● 2700K | 506912.B.P.C |
| SMD LED | 7x6W | 310x210x70mm | 4960lm | 3214lm | ● 3000K | 506913.B.P.C |
| SMD LED | 7x6W | 310x210x70mm | 5272lm | 3417lm | ● 4000K | 506914.B.P.C |
| SMD LED | 7x6W | 310x210x70mm | 5476lm | 3548lm | ● 5000K | 506915.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(W-White)



| | | | | | | | | | | | |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|
| OSRAM 50,000hrs | SMD | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Gypsum | 120° |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|---------------|---------------|---------------|---------|--------------|
| SMD LED | 7x2W | 215x165x110mm | 1627lm | 1004lm | ● 2700K | 507012.B.P.C |
| SMD LED | 7x2W | 215x165x110mm | 1736lm | 1071lm | ● 3000K | 507013.B.P.C |
| SMD LED | 7x2W | 215x165x110mm | 1845lm | 1139lm | ● 4000K | 507014.B.P.C |
| SMD LED | 7x2W | 215x165x110mm | 1917lm | 1183lm | ● 5000K | 507015.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(W-White)



5071

Downlight Recessed. Ambience/UGR

PLATTEseries

Architectural INDOOR



| | | | | | | | | | | | |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|
| OSRAM 50,000hrs | SMD | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Gypsum | 120° |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|---------------|---------------|---------------|---------|--------------|
| SMD LED | 7x3W | 265x215x110mm | 2324lm | 1506lm | ● 2700K | 507112.B.P.C |
| SMD LED | 7x3W | 265x215x110mm | 2480lm | 1607lm | ● 3000K | 507113.B.P.C |
| SMD LED | 7x3W | 265x215x110mm | 2636lm | 1708lm | ○ 4000K | 507114.B.P.C |
| SMD LED | 7x3W | 265x215x110mm | 2738lm | 1774lm | ○ 5000K | 507115.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(W-White)



5072

Downlight Recessed. Ambience/UGR

PLATTEseries

Architectural INDOOR



| | | | | | | | | | | | |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|
| OSRAM 50,000hrs | SMD | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Gypsum | 120° |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|---------------|---------------|---------------|---------|--------------|
| SMD LED | 7x5W | 370x270x110mm | 4067lm | 2677lm | ● 2700K | 507212.B.P.C |
| SMD LED | 7x5W | 370x270x110mm | 4340lm | 2857lm | ● 3000K | 507213.B.P.C |
| SMD LED | 7x5W | 370x270x110mm | 4613lm | 3037lm | ○ 4000K | 507214.B.P.C |
| SMD LED | 7x5W | 370x270x110mm | 4791lm | 3154lm | ○ 5000K | 507215.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(W-White)



5073

Downlight Recessed. Ambience/UGR

PLATTEseries

Architectural INDOOR



| | | | | | | | | | | | |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|
| OSRAM 50,000hrs | SMD | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Gypsum | 120° |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|-----------|---------------|---------------|---------|--------------|
| SMD LED | 7W | ∅110x70mm | 813lm | 535lm | ● 2700K | 507312.B.P.C |
| SMD LED | 7W | ∅110x70mm | 868lm | 571lm | ● 3000K | 507313.B.P.C |
| SMD LED | 7W | ∅110x70mm | 923lm | 607lm | ● 4000K | 507314.B.P.C |
| SMD LED | 7W | ∅110x70mm | 958lm | 631lm | ● 5000K | 507315.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(W-White)



White

5074

Downlight Recessed. Ambience/UGR

PLATTEseries

Architectural INDOOR



| | | | | | | | | | | | |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|
| OSRAM 50,000hrs | SMD | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Gypsum | 120° |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|---------------|---------------|---------------|---------|--------------|
| SMD LED | 7x2W | 215x110x110mm | 1627lm | 1004lm | ● 2700K | 507212.B.P.C |
| SMD LED | 7x2W | 215x110x110mm | 1736lm | 1071lm | ● 3000K | 507213.B.P.C |
| SMD LED | 7x2W | 215x110x110mm | 1845lm | 1139lm | ● 4000K | 507214.B.P.C |
| SMD LED | 7x2W | 215x110x110mm | 1917lm | 1183lm | ● 5000K | 507215.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(W-White)



White

5075

Downlight Recessed. Ambience/UGR

PLATTEseries

ArchitecturalINDOOR



| | | | | | | | | | | | |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|
| OSRAM 50,000hrs | SMD | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Gypsum | 120° |
|--------------------|-----|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|--------|------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|---------------|---------------|---------------|---------|--------------|
| SMD LED | 7x3W | 260x170x110mm | 2324lm | 1506lm | ● 2700K | 507312.B.P.C |
| SMD LED | 7x3W | 260x170x110mm | 2480lm | 1607lm | ● 3000K | 507313.B.P.C |
| SMD LED | 7x3W | 260x170x110mm | 2636lm | 1708lm | ● 4000K | 507314.B.P.C |
| SMD LED | 7x3W | 260x170x110mm | 2738m | 1774lm | ● 5000K | 507315.B.P.C |

Beam Angle: B(1-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(W-White)




White

4441

Downlight Recessed. Ambience/UGR

SENSIOseries

ArchitecturalINDOOR



| | | | | | | | | | | |
|--------------------|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|-------------------------------|-----------------|
| OSRAM 50,000hrs | LED LM80 | Fixed | Ra >90 | UGR <19 | IP20 | 5 Years Warranty | AC220-240V 50/60Hz | CE | Die-cast Aluminum Heatsink | 15° 24° 36° 50° |
|--------------------|-------------|-------|-----------|------------|------|------------------------|-----------------------|----|-------------------------------|-----------------|

| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|----------|---------------|---------------|---------|--------------|
| COB LED | 12W | ∅80x90mm | 1394lm | 1092lm | ● 2700K | 444112.B.P.C |
| COB LED | 12W | ∅80x90mm | 1488lm | 1165lm | ● 3000K | 444113.B.P.C |
| COB LED | 12W | ∅80x90mm | 1582lm | 1239lm | ● 4000K | 444114.B.P.C |
| COB LED | 12W | ∅80x90mm | 1643lm | 1286lm | ● 5000K | 444115.B.P.C |

Beam Angle: B(1-15° 2-24° 3-36° 4-50°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW-White/White BW - Black / White)




White/White Black/White

4442

Architectural INDOOR

Downlight Recessed. Ambience/UGR

SENSIO series



| Light Source | Power | Size | Source Lumens | System Lumens | CCT | Code |
|--------------|-------|--------------|---------------|---------------|---------|--------------|
| COB LED | 12W | 117x117x50mm | 1394lm | 1092lm | ● 2700K | 472012.B.P.C |
| COB LED | 12W | 117x117x50mm | 1488lm | 1165lm | ● 3000K | 472013.B.P.C |
| COB LED | 12W | 117x117x50mm | 1582lm | 1239lm | ○ 4000K | 472014.B.P.C |
| COB LED | 12W | 117x117x50mm | 1643lm | 1286lm | ○ 5000K | 472015.B.P.C |

Beam Angle: B(1-15° 2-24° 3-36° 4-50°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW-White/White BW - Black / White)



White/White Black/White