

HIGH BAY



HIGH BAY 7010
100W/150W/200W/240W
P.3



HIGH BAY 7011
60W/100W/150W/200W/240W
P.4-5



HIGH BAY 7012
60W/80W/100W/120W
150W/200W
P.7-8



HIGH BAY 7013
50W/100W/150W/200W/240W
P.9



LED HIGH BAY LIGHT

A large graphic on the right page shows a glowing white oval light fixture at the top, with several curved, concentric lines radiating downwards, suggesting light beams or a lens effect. Below this, a detailed wireframe rendering of a high bay light fixture is shown, highlighting its internal structure and mounting components.

POCHE

7010


Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65



Architectural OUTDOOR



OSRAM 50,000hrs SMD LED LM80 Fixed Ra >80 UGR <19 IP65 5 years Warranty AC120-277V 50/60Hz CE Die-cast Aluminum Heatsink 60° 90° 120°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	100W	ø262x175mm	12650lm	9740lm	● 2700K	701012.B.P.C
SMD LED	100W	ø262x175mm	13500lm	10868lm	● 3000K	701013.B.P.C
SMD LED	100W	ø262x175mm	14351lm	11552lm	○ 4000K	701014.B.P.C
SMD LED	100W	ø262x175mm	14904lm	12206lm	○ 5000K	701015.B.P.C
SMD LED	150W	ø301x175mm	18974lm	14610lm	● 2700K	701022.B.P.C
SMD LED	150W	ø301x175mm	20250lm	16301lm	● 3000K	701023.B.P.C
SMD LED	150W	ø301x175mm	21526lm	17328lm	○ 4000K	701024.B.P.C
SMD LED	150W	ø301x175mm	22356lm	18310lm	○ 5000K	701025.B.P.C
SMD LED	200W	ø350x175mm	25299lm	19480lm	● 2700K	701032.B.P.C
SMD LED	200W	ø350x175mm	27000lm	21735lm	● 3000K	701033.B.P.C
SMD LED	200W	ø350x175mm	28701lm	23104lm	○ 4000K	701034.B.P.C
SMD LED	200W	ø350x175mm	29808lm	24413lm	○ 5000K	701035.B.P.C
SMD LED	240W	ø350x175mm	30359lm	23376lm	● 2700K	701042.B.P.C
SMD LED	240W	ø350x175mm	32400lm	26082lm	● 3000K	701043.B.P.C
SMD LED	240W	ø350x175mm	34441lm	27725lm	○ 4000K	701044.B.P.C
SMD LED	240W	ø350x175mm	35770lm	29295lm	○ 5000K	701045.B.P.C

Beam Angle: B(1-60° 2-90° 3-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(1-Black 2-White 3-Grey)

Accessories:



Reflector:



Für allgemeine Anfragen, technischen Support oder Informationen zur Treiberkompatibilität – www.pochelicht.de.
For general enquiries, technical support, or driver compatibility details – www.pochelicht.de.

7011


Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65



Architectural OUTDOOR



OSRAM 50,000hrs SMD LED LM80 Fixed Ra >80 UGR <19 IP65 5 years Warranty AC120-277V 50/60Hz CE Die-cast Aluminum Heatsink 60° 90° 120°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	60W	ø200x149mm	7084lm	5454lm	● 2700K	701112.B.P.C
SMD LED	60W	ø200x149mm	7560lm	6086lm	● 3000K	701113.B.P.C
SMD LED	60W	ø200x149mm	8036lm	6469lm	○ 4000K	701114.B.P.C
SMD LED	60W	ø200x149mm	8346lm	6836lm	○ 5000K	701115.B.P.C
SMD LED	100W	ø240x152mm	11806lm	9091lm	● 2700K	701122.B.P.C
SMD LED	100W	ø240x152mm	12600lm	10143lm	● 3000K	701123.B.P.C
SMD LED	100W	ø240x152mm	13394lm	10782lm	○ 4000K	701124.B.P.C
SMD LED	100W	ø240x152mm	13910lm	11393lm	○ 5000K	701125.B.P.C
SMD LED	150W	ø280x155mm	17709lm	13636lm	● 2700K	701132.B.P.C
SMD LED	150W	ø280x155mm	18900lm	15215lm	● 3000K	701133.B.P.C
SMD LED	150W	ø280x155mm	20091lm	16173lm	○ 4000K	701134.B.P.C
SMD LED	150W	ø280x155mm	20866lm	17089lm	○ 5000K	701135.B.P.C

Beam Angle: B(1-60° 2-90° 3-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(1-Black 2-White 3-Grey)



Für allgemeine Anfragen, technischen Support oder Informationen zur Treiberkompatibilität – www.pochelicht.de.
For general enquiries, technical support, or driver compatibility details – www.pochelicht.de.

7011

Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65



UFO High Bay Lights

OSRAM 50,000hrs
SMD
LED LM80
Fixed
Ra >80
UGR <19
IP65
5 years Warranty
AC120-277V 50/60Hz
CE
Die-cast Aluminum Heatsink
60°
90°
120°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	200W	ø320x156mm	23612lm	18182lm	● 2700K	701142.B.P.C
SMD LED	200W	ø320x156mm	25200lm	20286lm	● 3000K	701143.B.P.C
SMD LED	200W	ø320x156mm	26788lm	21564lm	○ 4000K	701144.B.P.C
SMD LED	200W	ø320x156mm	27821lm	22785lm	○ 5000K	701145.B.P.C
SMD LED	240W	ø390x175mm	30359lm	23376lm	● 2700K	701152.B.P.C
SMD LED	240W	ø390x175mm	32400lm	26082lm	● 3000K	701153.B.P.C
SMD LED	240W	ø390x175mm	34441lm	27725lm	○ 4000K	701154.B.P.C
SMD LED	240W	ø390x175mm	35770lm	29295lm	○ 5000K	701155.B.P.C

Beam Angle: B(1-60° 2-90° 3-120°)

Power Supply: P(1-0n/Off 2-0-10V Dim 3-DALI Dim)

Colour Finish: C(1-Black 2-White 3-Grey)

Accessories:



Lamp Fitting:



Power and CCT Adjustable



Microwave Sensor Optional



Screw-in breather nut



ZHAGA Induction Base



Bracket + Lampshade



UFO high bay lights are widely used in warehouses, manufacturing plants, stadiums, logistics centre, high speed rail stations, aircraft.

Product Certification: Products passed CE, ROHS, CCC, ETL and other certificates.

7012


Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65



Architectural OUTDOOR



OSRAM 50,000hrs SMD LED LM80 Fixed Ra >80 UGR <19 IP65 5 years Warranty AC100-277V 50/60Hz CE Die-cast Aluminum Heatsink 60° 90° 120°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	60W	Ø300x125mm	6072lm	4675lm	● 2700K	701212.B.P.C
SMD LED	60W	Ø300x125mm	6480lm	5216lm	● 3000K	701213.B.P.C
SMD LED	60W	Ø300x125mm	6888lm	5545lm	○ 4000K	701214.B.P.C
SMD LED	60W	Ø300x125mm	7154lm	5859lm	○ 5000K	701215.B.P.C
SMD LED	80W	Ø300x125mm	8096lm	6234lm	● 2700K	701222.B.P.C
SMD LED	80W	Ø300x125mm	8640lm	6955lm	● 3000K	701223.B.P.C
SMD LED	80W	Ø300x125mm	9184lm	7393lm	○ 4000K	701224.B.P.C
SMD LED	80W	Ø300x125mm	9539lm	7812lm	○ 5000K	701225.B.P.C
SMD LED	100W	Ø300x125mm	10120lm	7792lm	● 2700K	701232.B.P.C
SMD LED	100W	Ø300x125mm	10800lm	8694lm	● 3000K	701233.B.P.C
SMD LED	100W	Ø300x125mm	11480lm	9242lm	○ 4000K	701234.B.P.C
SMD LED	100W	Ø300x125mm	11923lm	9765lm	○ 5000K	701235.B.P.C

Beam Angle: B(1-60° 2-90° 3-120°)

Power Supply: P(1-On/Off 2-0-10V Dim 3-DALI Dim)

Colour Finish: C(1-Black 2-White 3-Grey 4-Orange)



7012


Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65



Architectural OUTDOOR



OSRAM 50,000hrs SMD LED LM80 Fixed Ra >80 UGR <19 IP65 5 years Warranty AC120-277V 50/60Hz CE Die-cast Aluminum Heatsink 60° 90° 120°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	120W	Ø300x125mm	12144lm	9351lm	● 2700K	701242.B.P.C
SMD LED	120W	Ø300x125mm	12960lm	10433lm	● 3000K	701243.B.P.C
SMD LED	120W	Ø300x125mm	13776lm	11090lm	○ 4000K	701244.B.P.C
SMD LED	120W	Ø300x125mm	14308lm	11718lm	○ 5000K	701245.B.P.C
SMD LED	150W	Ø345x136mm	15179lm	11688lm	● 2700K	701252.B.P.C
SMD LED	150W	Ø345x136mm	16200lm	13041lm	● 3000K	701253.B.P.C
SMD LED	150W	Ø345x136mm	17221lm	13863lm	○ 4000K	701254.B.P.C
SMD LED	150W	Ø345x136mm	17885lm	14648lm	○ 5000K	701255.B.P.C
SMD LED	200W	Ø345x136mm	20239lm	15584lm	● 2700K	701262.B.P.C
SMD LED	200W	Ø345x136mm	21600lm	17388lm	● 3000K	701263.B.P.C
SMD LED	200W	Ø345x136mm	22961lm	18483lm	○ 4000K	701264.B.P.C
SMD LED	200W	Ø345x136mm	23846lm	19530lm	○ 5000K	701265.B.P.C

Beam Angle: B(1-60° 2-90° 3-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(1-Black 2-White 3-Grey 4-Orange)



7013

Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65



Architectural OUTDOOR



Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	50W	353x137x107mm	5903lm	4545lm	● 2700K	701312.B.P.C
SMD LED	50W	353x137x107mm	6300lm	5072lm	● 3000K	701313.B.P.C
SMD LED	50W	353x137x107mm	6697lm	5391lm	○ 4000K	701314.B.P.C
SMD LED	50W	353x137x107mm	6955lm	5696lm	○ 5000K	701315.B.P.C
SMD LED	100W	620x137x107mm	11806lm	9091lm	● 2700K	701322.B.P.C
SMD LED	100W	620x137x107mm	12600lm	10143lm	● 3000K	701323.B.P.C
SMD LED	100W	620x137x107mm	13394lm	10782lm	○ 4000K	701324.B.P.C
SMD LED	100W	620x137x107mm	13910lm	11393lm	○ 5000K	701325.B.P.C
SMD LED	150W	887x137x107mm	17709lm	13636lm	● 2700K	701332.B.P.C
SMD LED	150W	887x137x107mm	18900lm	15215lm	● 3000K	701333.B.P.C
SMD LED	150W	887x137x107mm	20091lm	16173lm	○ 4000K	701334.B.P.C
SMD LED	150W	887x137x107mm	20866lm	17089lm	○ 5000K	701335.B.P.C
SMD LED	200W	1154x137x107mm	23612lm	18182lm	● 2700K	701342.B.P.C
SMD LED	200W	1154x137x107mm	25200lm	20286lm	● 3000K	701343.B.P.C
SMD LED	200W	1154x137x107mm	26788lm	21564lm	○ 4000K	701344.B.P.C
SMD LED	200W	1154x137x107mm	27821lm	22785lm	○ 5000K	701345.B.P.C
SMD LED	240W	1421x137x107mm	28335lm	21818lm	● 2700K	701352.B.P.C
SMD LED	240W	1421x137x107mm	30240lm	24343lm	● 3000K	701353.B.P.C
SMD LED	240W	1421x137x107mm	32145lm	25877lm	○ 4000K	701354.B.P.C
SMD LED	240W	1421x137x107mm	33385lm	27342lm	○ 5000K	701355.B.P.C

Beam Angle: B(1-30° 2-60° 3-90° 4-30x70° 5-60x90° 6-80x155°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(1-Black 2-White 3-Grey)



Für allgemeine Anfragen, technischen Support oder Informationen zur Treiberkompatibilität – www.pochelicht.de.
For general enquiries, technical support, or driver compatibility details – www.pochelicht.de.