



DOWNLIGHT SURFACE IP65



DECKE 5060
12W/18W/25W/35W/40W
P.1-2



DECKE 5059
12W/18W/25W/35W/40W/52W
P.3-4

5059

Downlight Recessed. Ambience/UGR

DECKEseries

IP65



ArchitecturalINDOOR



Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
COB LED	12W	ø80x90mm	1394lm	1092lm	● 2700K	505912.B.P.C
COB LED	12W	ø80x90mm	1488lm	1165lm	● 3000K	505913.B.P.C
COB LED	12W	ø80x90mm	1582lm	1239lm	● 4000K	505914.B.P.C
COB LED	12W	ø80x90mm	1643lm	1286lm	● 5000K	505915.B.P.C
COB LED	18W	ø100x100mm	1956lm	1362lm	● 2700K	505922.B.P.C
COB LED	18W	ø100x100mm	2088lm	1453lm	● 3000K	505923.B.P.C
COB LED	18W	ø100x100mm	2220lm	1545lm	● 4000K	505924.B.P.C
COB LED	18W	ø100x100mm	2305lm	1604lm	● 5000K	505925.B.P.C
COB LED	25W	ø130x130mm	2717lm	2043lm	● 2700K	505932.B.P.C
COB LED	25W	ø130x130mm	2900lm	2180lm	● 3000K	505933.B.P.C
COB LED	25W	ø130x130mm	3083lm	2317lm	● 4000K	505934.B.P.C
COB LED	25W	ø130x130mm	3202lm	2407lm	● 5000K	505935.B.P.C
COB LED	35W	ø150x140mm	3739lm	2844lm	● 2700K	505942.B.P.C
COB LED	35W	ø150x140mm	3990lm	3035lm	● 3000K	505943.B.P.C
COB LED	35W	ø150x140mm	4241lm	3226lm	● 4000K	505944.B.P.C
COB LED	35W	ø150x140mm	4405lm	3351lm	● 5000K	505945.B.P.C

Beam Angle: B(1-24° 2-36°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW - White / White WSB - White / Shiny Black WS - White / Silver WMS - White / Mat Silver WRG - White / Rose Golden BB - Black / Black BSB - Black / Shiny Black BS - Black / Silver BMS - Black / Mat Silver BRG - Black / Rose Golden)



5059

Downlight Recessed. Ambience/UGR

DECKEseries

IP65



ArchitecturalINDOOR



Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
COB LED	40W	ø170x160mm	4273lm	3178lm	● 2700K	505952.B.P.C
COB LED	40W	ø170x160mm	4560lm	3392lm	● 3000K	505953.B.P.C
COB LED	40W	ø170x160mm	4847lm	3606lm	● 4000K	505954.B.P.C
COB LED	40W	ø170x160mm	5034lm	3745lm	● 5000K	505955.B.P.C
SMD LED	52W	ø200x190mm	6334lm	4960lm	● 2700K	505962.B.P.C
SMD LED	52W	ø200x190mm	6760lm	5293lm	● 3000K	505963.B.P.C
SMD LED	52W	ø200x190mm	7186lm	5627lm	● 4000K	505964.B.P.C
SMD LED	52W	ø200x190mm	7463lm	5844lm	● 5000K	505965.B.P.C

Beam Angle: B(1-24° 2-36°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW - White / White WSB - White / Shiny Black WS - White / Silver WMS - White / Mat Silver WRG - White / Rose Golden BB - Black / Black BSB - Black / Shiny Black BS - Black / Silver BMS - Black / Mat Silver BRG - Black / Rose Golden)



5060

Downlight Recessed. Ambience/UGR

DECKEseries

IP65



ArchitecturalINDOOR



50,000hrs |
 LED LM80 |
 Fixed |
 Ra >90 |
 UGR <19 |
 IP65 |
 5 years Warranty |
 AC220-240V 50/60Hz |
 CE |
 Die-cast Aluminum Heatsink |
 24° 36°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
COB LED	12W	80x80x83mm	1394lm	1092lm	● 2700K	506012.B.P.C
COB LED	12W	80x80x83mm	1488lm	1165lm	● 3000K	506013.B.P.C
COB LED	12W	80x80x83mm	1582lm	1239lm	○ 4000K	506014.B.P.C
COB LED	12W	80x80x83mm	1643lm	1286lm	○ 5000K	506015.B.P.C
COB LED	18W	100x100x96mm	1956lm	1362lm	● 2700K	506022.B.P.C
COB LED	18W	100x100x96mm	2088lm	1453lm	● 3000K	506023.B.P.C
COB LED	18W	100x100x96mm	2220lm	1545lm	○ 4000K	506024.B.P.C
COB LED	18W	100x100x96mm	2305lm	1604lm	○ 5000K	506025.B.P.C
COB LED	25W	130x130x121mm	2717lm	2043lm	● 2700K	506032.B.P.C
COB LED	25W	130x130x121mm	2900lm	2180lm	● 3000K	506033.B.P.C
COB LED	25W	130x130x121mm	3083lm	2317lm	○ 4000K	506034.B.P.C
COB LED	25W	130x130x121mm	3202lm	2407lm	○ 5000K	506035.B.P.C
COB LED	35W	150x150x136mm	3739lm	2844lm	● 2700K	506042.B.P.C
COB LED	35W	150x150x136mm	3990lm	3035lm	● 3000K	506043.B.P.C
COB LED	35W	150x150x136mm	4241lm	3226lm	○ 4000K	506044.B.P.C
COB LED	35W	150x150x136mm	4405lm	3351lm	○ 5000K	506045.B.P.C

Beam Angle: B(1-24° 2-36°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW-White / White WB - White / Black WS- White / Silver WRG- White / Rose Golden WMS- White / Mat Silver BB - Black / Black BRG - Black / Rose Golden BS - Black / Silver BMS - Black / Mat Silver BSB - Black / Shiny Black)



5060



Downlight Recessed. Ambience/UGR

DECKEseries

IP65



ArchitecturalINDOOR



50,000hrs |
 LED LM80 |
 Fixed |
 Ra >90 |
 UGR <19 |
 IP65 |
 5 years Warranty |
 AC220-240V 50/60Hz |
 CE |
 Die-cast Aluminum Heatsink |
 24° 36°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
COB LED	40W	170x170x160mm	4273lm	3178lm	● 2700K	506052.B.P.C
COB LED	40W	170x170x160mm	4560lm	3392lm	● 3000K	506053.B.P.C
COB LED	40W	170x170x160mm	4847lm	3606lm	○ 4000K	506054.B.P.C
COB LED	40W	170x170x160mm	5034lm	3745lm	○ 5000K	506055.B.P.C

Beam Angle: B(1-24° 2-36°)

Power Supply: P(1-On/Off)

Colour Finish: C(WW-White / White WB - White / Black WS- White / Silver WRG- White / Rose Golden WMS- White / Mat Silver BB - Black / Black BRG - Black / Rose Golden BS - Black / Silver BMS - Black / Mat Silver BSB - Black / Shiny Black)

