



HIGH BAY



HIGH BAY 7010
100W/150W/200W/240W
P.3



HIGH BAY 7011
60W/100W/150W/200W/240W
P.4-5



HIGH BAY 7012
60W/80W/100W/120W
150W/200W
P.7-8



HIGH BAY 7013
50W/100W/150W/200W/240W
P.9


7010

Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65

Architectural OUTDOOR



OSRAM 50,000hrs SMD LED LM80 Fixed Ra >80 UGR <19 IP65 5 years Warranty AC120-277V 50/60Hz CE Die-cast Aluminum Heatsink 60° 90° 120°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	100W	ø262x175mm	12650lm	9740lm	● 2700K	701012.B.P.C
SMD LED	100W	ø262x175mm	13500lm	10868lm	● 3000K	701013.B.P.C
SMD LED	100W	ø262x175mm	14351lm	11552lm	○ 4000K	701014.B.P.C
SMD LED	100W	ø262x175mm	14904lm	12206lm	○ 5000K	701015.B.P.C
SMD LED	150W	ø301x175mm	18974lm	14610lm	● 2700K	701022.B.P.C
SMD LED	150W	ø301x175mm	20250lm	16301lm	● 3000K	701023.B.P.C
SMD LED	150W	ø301x175mm	21526lm	17328lm	○ 4000K	701024.B.P.C
SMD LED	150W	ø301x175mm	22356lm	18310lm	○ 5000K	701025.B.P.C
SMD LED	200W	ø350x175mm	25299lm	19480lm	● 2700K	701032.B.P.C
SMD LED	200W	ø350x175mm	27000lm	21735lm	● 3000K	701033.B.P.C
SMD LED	200W	ø350x175mm	28701lm	23104lm	○ 4000K	701034.B.P.C
SMD LED	200W	ø350x175mm	29808lm	24413lm	○ 5000K	701035.B.P.C
SMD LED	240W	ø350x175mm	30359lm	23376lm	● 2700K	701042.B.P.C
SMD LED	240W	ø350x175mm	32400lm	26082lm	● 3000K	701043.B.P.C
SMD LED	240W	ø350x175mm	34441lm	27725lm	○ 4000K	701044.B.P.C
SMD LED	240W	ø350x175mm	35770lm	29295lm	○ 5000K	701045.B.P.C

Beam Angle: B(1-60° 2-90° 3-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(1-Black 2-White 3-Grey)

Accessories:



Reflector:



Für allgemeine Anfragen, technischen Support oder Informationen zur Treiberkompatibilität – www.pochelicht.de.
For general enquiries, technical support, or driver compatibility details – www.pochelicht.de.


7011

Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65

Architectural OUTDOOR



OSRAM 50,000hrs SMD LED LM80 Fixed Ra >80 UGR <19 IP65 5 years Warranty AC120-277V 50/60Hz CE Die-cast Aluminum Heatsink 60° 90° 120°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	60W	ø200x149mm	7084lm	5454lm	● 2700K	701112.B.P.C
SMD LED	60W	ø200x149mm	7560lm	6086lm	● 3000K	701113.B.P.C
SMD LED	60W	ø200x149mm	8036lm	6469lm	○ 4000K	701114.B.P.C
SMD LED	60W	ø200x149mm	8346lm	6836lm	○ 5000K	701115.B.P.C
SMD LED	100W	ø240x152mm	11806lm	9091lm	● 2700K	701122.B.P.C
SMD LED	100W	ø240x152mm	12600lm	10143lm	● 3000K	701123.B.P.C
SMD LED	100W	ø240x152mm	13394lm	10782lm	○ 4000K	701124.B.P.C
SMD LED	100W	ø240x152mm	13910lm	11393lm	○ 5000K	701125.B.P.C
SMD LED	150W	ø280x155mm	17709lm	13636lm	● 2700K	701132.B.P.C
SMD LED	150W	ø280x155mm	18900lm	15215lm	● 3000K	701133.B.P.C
SMD LED	150W	ø280x155mm	20091lm	16173lm	○ 4000K	701134.B.P.C
SMD LED	150W	ø280x155mm	20866lm	17089lm	○ 5000K	701135.B.P.C

Beam Angle: B(1-60° 2-90° 3-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(1-Black 2-White 3-Grey)



Für allgemeine Anfragen, technischen Support oder Informationen zur Treiberkompatibilität – www.pochelicht.de.
For general enquiries, technical support, or driver compatibility details – www.pochelicht.de.

7011

Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65



UFO High Bay Lights


Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	200W	ø320x156mm	23612lm	18182lm	● 2700K	701142.B.P.C
SMD LED	200W	ø320x156mm	25200lm	20286lm	● 3000K	701143.B.P.C
SMD LED	200W	ø320x156mm	26788lm	21564lm	○ 4000K	701144.B.P.C
SMD LED	200W	ø320x156mm	27821lm	22785lm	○ 5000K	701145.B.P.C
SMD LED	240W	ø390x175mm	30359lm	23376lm	● 2700K	701152.B.P.C
SMD LED	240W	ø390x175mm	32400lm	26082lm	● 3000K	701153.B.P.C
SMD LED	240W	ø390x175mm	34441lm	27725lm	○ 4000K	701154.B.P.C
SMD LED	240W	ø390x175mm	35770lm	29295lm	○ 5000K	701155.B.P.C

Beam Angle: B(1-60° 2-90° 3-120°)


Power Supply: P(1-0n/Off 2-0-10V Dim 3-DALI Dim)

Colour Finish: C(1-Black 2-White 3-Grey)

Accessories:



Lamp Fitting:



Power and CCT Adjustable



Microwave Sensor Optional



Screw-in breather nut



ZHAGA Induction Base



Bracket + Lampshade



UFO high bay lights are widely used in warehouses, manufacturing plants, stadiums, logistics centre, high speed rail stations, aircraft.

Product Certification: Products passed CE, ROHS, CCC, ETL and other certificates.

7012


Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65



Architectural OUTDOOR



OSRAM 50,000hrs SMD LED LM80 Fixed Ra >80 UGR <19 IP65 5 years Warranty AC100-277V 50/60Hz CE Die-cast Aluminum Heatsink 60° 90° 120°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	60W	300x125mm	6072lm	4675lm	2700K	701212.B.P.C
SMD LED	60W	300x125mm	6480lm	5216lm	3000K	701213.B.P.C
SMD LED	60W	300x125mm	6888lm	5545lm	4000K	701214.B.P.C
SMD LED	60W	300x125mm	7154lm	5859lm	5000K	701215.B.P.C
SMD LED	80W	300x125mm	8096lm	6234lm	2700K	701222.B.P.C
SMD LED	80W	300x125mm	8640lm	6955lm	3000K	701223.B.P.C
SMD LED	80W	300x125mm	9184lm	7393lm	4000K	701224.B.P.C
SMD LED	80W	300x125mm	9539lm	7812lm	5000K	701225.B.P.C
SMD LED	100W	300x125mm	10120lm	7792lm	2700K	701232.B.P.C
SMD LED	100W	300x125mm	10800lm	8694lm	3000K	701233.B.P.C
SMD LED	100W	300x125mm	11480lm	9242lm	4000K	701234.B.P.C
SMD LED	100W	300x125mm	11923lm	9765lm	5000K	701235.B.P.C

Beam Angle: B(1-60° 2-90° 3-120°)

Power Supply: P(1-On/Off 2-0-10V Dim 3-DALI Dim)

Colour Finish: C(1-Black 2-White 3-Grey 4-Orange)



7012


Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65



Architectural OUTDOOR



OSRAM 50,000hrs SMD LED LM80 Fixed Ra >80 UGR <19 IP65 5 years Warranty AC120-277V 50/60Hz CE Die-cast Aluminum Heatsink 60° 90° 120°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	120W	300x125mm	12144lm	9351lm	2700K	701242.B.P.C
SMD LED	120W	300x125mm	12960lm	10433lm	3000K	701243.B.P.C
SMD LED	120W	300x125mm	13776lm	11090lm	4000K	701244.B.P.C
SMD LED	120W	300x125mm	14308lm	11718lm	5000K	701245.B.P.C
SMD LED	150W	345x136mm	15179lm	11688lm	2700K	701252.B.P.C
SMD LED	150W	345x136mm	16200lm	13041lm	3000K	701253.B.P.C
SMD LED	150W	345x136mm	17221lm	13863lm	4000K	701254.B.P.C
SMD LED	150W	345x136mm	17885lm	14648lm	5000K	701255.B.P.C
SMD LED	200W	345x136mm	20239lm	15584lm	2700K	701262.B.P.C
SMD LED	200W	345x136mm	21600lm	17388lm	3000K	701263.B.P.C
SMD LED	200W	345x136mm	22961lm	18483lm	4000K	701264.B.P.C
SMD LED	200W	345x136mm	23846lm	19530lm	5000K	701265.B.P.C

Beam Angle: B(1-60° 2-90° 3-120°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(1-Black 2-White 3-Grey 4-Orange)



7013

Downlight Recessed. Ambience/UGR

HIGH BAY series

IP65



Architectural OUTDOOR



Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	50W	353x137x107mm	5903lm	4545lm	● 2700K	701312.B.P.C
SMD LED	50W	353x137x107mm	6300lm	5072lm	● 3000K	701313.B.P.C
SMD LED	50W	353x137x107mm	6697lm	5391lm	○ 4000K	701314.B.P.C
SMD LED	50W	353x137x107mm	6955lm	5696lm	○ 5000K	701315.B.P.C
SMD LED	100W	620x137x107mm	11806lm	9091lm	● 2700K	701322.B.P.C
SMD LED	100W	620x137x107mm	12600lm	10143lm	● 3000K	701323.B.P.C
SMD LED	100W	620x137x107mm	13394lm	10782lm	○ 4000K	701324.B.P.C
SMD LED	100W	620x137x107mm	13910lm	11393lm	○ 5000K	701325.B.P.C
SMD LED	150W	887x137x107mm	17709lm	13636lm	● 2700K	701332.B.P.C
SMD LED	150W	887x137x107mm	18900lm	15215lm	● 3000K	701333.B.P.C
SMD LED	150W	887x137x107mm	20091lm	16173lm	○ 4000K	701334.B.P.C
SMD LED	150W	887x137x107mm	20866lm	17089lm	○ 5000K	701335.B.P.C
SMD LED	200W	1154x137x107mm	23612lm	18182lm	● 2700K	701342.B.P.C
SMD LED	200W	1154x137x107mm	25200lm	20286lm	● 3000K	701343.B.P.C
SMD LED	200W	1154x137x107mm	26788lm	21564lm	○ 4000K	701344.B.P.C
SMD LED	200W	1154x137x107mm	27821lm	22785lm	○ 5000K	701345.B.P.C
SMD LED	240W	1421x137x107mm	28335lm	21818lm	● 2700K	701352.B.P.C
SMD LED	240W	1421x137x107mm	30240lm	24343lm	● 3000K	701353.B.P.C
SMD LED	240W	1421x137x107mm	32145lm	25877lm	○ 4000K	701354.B.P.C
SMD LED	240W	1421x137x107mm	33385lm	27342lm	○ 5000K	701355.B.P.C

Beam Angle: B(1-30° 2-60° 3-90° 4-30x70° 5-60x90° 6-80x155°)

Power Supply: P(1-On/Off 2-DALI Dim 3-0-10V Dim)

Colour Finish: C(1-Black 2-White 3-Grey)



Für allgemeine Anfragen, technischen Support oder Informationen zur Treiberkompatibilität – www.pochelicht.de.
For general enquiries, technical support, or driver compatibility details – www.pochelicht.de.