



4100

Downlight Recessed. Ambience/UGR

SMART LIGHT series



Architectural INDOOR



OSRAM 50,000hrs	LED LM80	Fixed	Ra >90	UGR <19	IP20	5 years Warranty	AC220-240V 50/60Hz	CE	Die-cast Aluminum Heatsink	15° 24° 36° 50°
--------------------	-------------	-------	-----------	------------	------	---------------------	-----------------------	----	-------------------------------	-----------------

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
COB LED	12W	ø82x55mm	● 1394lm	● 1092lm	2700K	410010.B.P.C
			○ 1643lm	○ 1286lm	6500K	

Beam Angle: B(1-15° 2-24° 3-36° 4-50°)

Power Supply: P(1-Zigbee Smart)


Colour Finish: C(WW-White/White BB-Black/Black WB- White / Black)




4120

Downlight Recessed. Ambience/UGR

SMART LIGHT series



Architectural INDOOR



OSRAM 50,000hrs	LED LM80	Fixed	Ra >90	UGR <19	IP20	5 years Warranty	AC220-240V 50/60Hz	CE	Die-cast Aluminum Heatsink	120°
--------------------	-------------	-------	-----------	------------	------	---------------------	-----------------------	----	-------------------------------	------

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
SMD LED	12W	ø82x55mm	● 1349lm	● 971lm	2700K	412010.B.P.C
			○ 1590lm	○ 1145lm	6500K	

Beam Angle: B(1-120°)

Power Supply: P(1-Zigbee Smart)

Colour Finish: C(WW-White/White WB-White/Black)




4125

Downlight Recessed. Ambience/UGR

SMART LIGHT series

Architectural INDOOR



OSRAM 50,000hrs | LED LM80 | Fixed | Ra > 90 | UGR < 19 | IP65 | 5 years Warranty | AC220-240V 50/60Hz | CE | Die-cast Aluminum Heatsink | 15° 24° 36° 50°

Light Source	Power	Size	Source Lumens	System Lumens	CCT	Code
COB LED	18W	∅62x73mm	● 2091lm	● 1638lm	2700K	412510.B.P.C
			○ 2464lm	○ 1884lm	6500K	

Beam Angle: B(1-15° 2-24° 3-36° 4-50°)

Power Supply: P(1-Zigbee Smart)

Colour Finish: C(WW-White/White WB-White/Black BB-Black/Black)



4130



Strip Light LED. Ambience/Dotless

SMART LIGHT series



1 LED PER CUT

Architectural INDOOR



OSRAM 50,000hrs | SMD | Fixed | Ra > 90 | Blue Light | 5 years Warranty | 24V DC | CE | Designed & Patent D-Layer PCB | 120° BEAM ANGLE

Light Source	Power	Lumens Efficiency	System Lumens	CCT	Code
SMD LED	12W/M	● 131lm/W	● 1574lm	2700K	413012.L.P.I
		○ 155lm/W	○ 1855lm	6500K	

Length: L(1-5m/roll 2-10m/roll)

Power Supply: P(1-Zigbee Smart)

IP Rating: I(1-IP20 2-IP44 3-IP65 4-IP67 5-IP68)

Protection Rating:



Tunable Color Temperature