

Product Categories

Industrial Dehumidifier



Concealed installed for
grow room, Swimming Pool,
Hotel, Cellar, Garage, Office
Villa...



CMD-90L/138L Ceiling Mounted Dehumidifier

- Framed machine body construction
- Micro-computer control, LCD digital display
- Humidity control accuracy to $\pm 1\%$, set freely
- Double sound insulation, silence running design
- Timed on/off setting



Model no.	CMD-9	CMD-138L
Cooling Capacity	9,000 BTU	9,000 BTU
Water Removal Capacity @30°C, RH80%, 24hrs	90 Liters	138 Liters
Supply Voltage	208~240V	208~240V
Rated Power	1.0 Kw	1.2 Kw
Rated Amps	3.8 A	3.8A
Air Volume @ 0.0" ,CFM	590	765
Static Pressure	50~80 Pa	50~80 Pa
Working Temperature	5°C~38°C	41°F~100°F
Humidity Range (RH)	40%~95%	40%~95%
Net Dimensions	35.4" x 25.2" x 18.5"	35.4" x 25.2" x 18.5"
Packed Dimesions	40.6" x 27.6" x 25"	40.6" x 27.6" x 25"
Net Weight	108 Lbs	118 Lbs
Gross Weight	132 Lbs	143 Lbs
Air Inlet Flange Size	11.8" x 15.8"	11.8" x 15.8"
Air Outlet Flange Size	8.9" x 7.5"	8.9" x 7.5"
Noise	≤60dB	≤60dB
Applying Area	700~1200 Sqft	1300~1500 Sqft