

Portable dehumidifier for
Home, Office, Basement,
Warehouse, Commercial,
Storage...



PD-38L/58L Portable Dehumidifier

- Micro-computer control LCD display
- Controlled by low voltage, more safe
- Automatic shut down when tank is full
- Humidity set freely, easy to use
- Moving by universal wheels, portable



Model no.	PD-38L	PD-58L
Cooling Capacity	7,200 BTU	7,200 BTU
Water Removal Capacity @30°C, RH80%, 24hrs	80 pints	123 pints
Supply Voltage	208~240V or 110~120V	208~240V or 110~120V
Refrigerator	R410a	R410a
Rated Power	0.55 Kw	0.65 Kw
Rated Amps	2.5 A	3.0 A
Air Volume @0.0"	295 CFM	295 CFM
Working Temperature	41°F~100°F	41°F~100°F
Static Pressure	20~40 Pa	20~40 Pa
Humidity Range (RH)	45%~95%	45%~95%
Net Dimensions	17.7" x15.8" x 30.0"	17.7" x15.8" x 30.0"
Packed Dimesions	21.7" x20.0" x 37.8"	21.7" x20.0" x 37.8"
Net Weight	72 Lbs	82 Lbs
Gross Weight	95 Lbs	105 Lbs
Rubber wheel size	6"	6"
Universal wheel size	2.5"	2.5"
Noise	≤45dB	≤45dB
Applying Area	200~300 Sqft	300~400 Sqft