


MECHANICAL



SDS I Duct silencer, rigid



- Steel sheet, galvanized
- Sound insulation material 2 in
- Length A = 39,4 in

Type	Noise reduction dB							Ø B in	Ø C in	Weight lbs
	Octave bands [Hz]									
	125	250	500	1k	2k	4k	8k			
SDS 100	8	10	20	17	18	19	15	7,9	3,9	10,8
SDS 125	6	12	25	26	30	30	18	8,9	4,9	11,7
SDS 150	5	10	24	24	28	25	22	9,8	5,9	13,0
SDS 160	5	11	23	28	34	26	21	10,2	6,3	12,8
SDS 200	2	9	19	25	27	18	20	11,8	7,9	15,7
SDS 250	1	8	19	25	25	16	15	13,8	9,8	10,4
SDS 280	6	10	18	22	18	14	14	15,0	11,0	22,7
SDS 315	0	5	10	22	16	13	14	16,3	12,4	21,4
SDS 355	4	7	14	24	14	11	12	17,9	14,0	25,6
SDS 400	2	3	10	18	10	8	7	19,7	15,7	26,7
SDS 450	-	-	-	-	-	-	-	21,7	17,7	-
SDS 500	4	5	10	8	10	11	11	23,6	19,7	44,3