

8 inch is available in different tailored packages/Spec. to perfectly meet your company's needs.

KEY FEATURES

Android 13 GMS

Qualcomm® Snapdrag SM4350, 2*Kryo 460 Gold(A76) 2.0GHz + 6*Kryo 460 Silver(A55) 1.8GHz

Wifi6-Ready, 802.11ac, a/b/g/n, Frequency 2.4GHz/5GHz

6GB +128GB

5G NR: N1/N3/N28/N41/N78/N79



♦ Operation System

OS	Android 13 GMS
CPU	Qualcomm® Snapdrag SM4350, 2*Kryo 460 Gold(A76) 2.0GHz + 6*Kryo 460 Silver(A55) 1.8GHz
Memory	6GB +128GB
Language support	Multi-Language

♦ Display

Size	8" IPS HD 800*1280 700 Nits
Screen Technology	IPS Display Panel Coming® Gorilla® Glass 3
Touch Pannel	Capacitive, 10-Point touchscreen, Glove/Wet Finger Supported

♦ Dimensions and Weight

Dimensions	8" 235 x 145 x 14mm (9.25 x 5.7 x 0.55 inch)
Weight	600g(21.16oz)

♦ Camera

Rear	13M Autofocus with Flash Light
Front	5M
Flash Lights	Support

♦ Keypad

8 Functions keys	Power/Home/Manu/Back/Volume +/- F1, F2
------------------	--

♦ Audio

Audio PA	Integrated Loudspeaker
Audio Jack	Type C

♦ Indicator

♦ Sensor and Data Collectoin



RFID HF (By Optional)
NFC Built-in: Frequency 13.56Mhz 0-3m
UHF RFID modula (By Opitonal Accessories)
1D/2D Scanner modula (By Opitonal Accessories)
Vehicle Charging(By Opitonal Accessories)
High Precision GPS (By Opitonal Accessories)
Bio-Fingerprint
Gravity
Gyroscope
E-compass
Light Sensor

♦ Battery

Battery	Swappable Lithium-ion Polymerm, Removable and Replaceable
LI-ion battery	9000mAh
Voltage	3.8V

♦ Battery Approvals

UN38.3 MSDS IEC 62133

♦ Regulatory Approvals

FCC, CE, ISED, RCM, UKCA, KC, PTCRB, GCF
IP68 IEC60529
MIL-STD-810G

♦ Software

Compatible with common third-party software,

♦ I/O Interface

SD	1 x Micro SD Support Max:128G
SIM	Nano SIM x 2 & Dual Standby
USB	USB Type-c support OTG, USB 2.0
Pogo Pin	14* Back Pins Pogo Pin UART/USB/CAN/DCIN/GPIO/USB2.0
Bluetooth®	Bluetooth® 5.1
GPS	Built-in ublox M8/ ext. GPS antenna connector
WLAN	GPS/GLONASS/Beidou/Galileo
Wifi	WIFI/BT
WWAN	Wifi6-Ready, 802.11ac, a/b/g/n, Frequency 2.4GHz/5GHz
	2G/3G/4G/5G LTE
	GSM:850/900/1800/1900
	EVDO: BC0
	WCDMA: B1/B2/B5/B8
	TD-SCDMA:B34/B39
	TDD-LTE: B38/B39/B40/B41
	FDD-LTE:B1/B2/B3/B4/B5/B7/B8/B17/B20/B28
	5G NR: N1/N3/N28/N41/N78/N79

♦ Environmental

Operating temperature	-20°C~60°C(-4°F~140 °F)
Storage temperature	-30°C~70°C(-22°F~158 °F)
Relative Humidity	95% No Condensation
Drop Specifications	1.5M (4.9 ft) Drop
Ingress Protection	MIL-STD-810G

♦ Inside the box



TAB30 device
9000mAh Battery
Type C charging cable
USB power adapter with EU, UK, US and AU

♦ Accessories

Handstrap
Shoulder Strap
Bag
Protected Case
Stand
Stylus
Micro SD Card
Metal Cradle
Vehicle Mounting
Battery Charger
Vehicle Charging by Cigarette Lighter
Antenna