




Front Hollow Pipe ▲

PH Series Preset Torque Wrench

- Accuracy: $\pm 4\%$ in clockwise direction from 20% to 100% of capacity.
- Easy to adjust to desired torque (in the tool room, appropriate torque tester is required).
- Operator cannot change set torque by accident or by mistake.
- Head holder for standard 9x12, 14x18, 24x32, 27x36mm square shank heads.

Torque Adjusting Tool



Optional Fittings:



Metric

Item No.	Shank Size mm	Torque Range		OD of Tube mm	Length mm	Weight Kg
		N.m	LB.FT			
PH925TI	9X12	5-25	45-225*	φ 22.2	182	0.35
PH950TI	9X12	10-50	8.0-40	φ 22.2	244	0.45
PH985TI	9X12	17-85	12-60	φ 22.2	313	0.56
PH9120TI	9X12	24-120	18-90	φ 22.2	353	0.67
PH14200TI	14X18	40-200	30-150	φ 23	430	1.09
PH14300TI	14X18	60-300	45-225	φ 23	690	1.84
PH14500TI	14X18	100-500	80-400	φ 25.4	970	2.56
PH24650TI	24X32	130-650	100-500	φ 32	1030	4.9
PH24800TI	24X32	160-800	120-600	φ 32	1030	4.9
PH241000TI	24X32	200-1000	150-750	φ 32	1030	4.9
PH271500TI	27X36	300-1500	220-1100	φ 40.5	1250	8