

48-ports 6A 2U modular Patch Panel – Rack mountable**Features**

- RJ45 Keystone Panel fully loaded
- Cat6A, UTP
- 2U, 48-port CAT.6A cable holder
- Cable tie-free plastic buckles

Technical Data

Product Type	RJ45 keystone patch panel
ANSI/TIA	Category 6A UTP
Cable Type	Unshielded
Color	Black
Modules, quantity	48-by front-loading frames
Panel Style	Straight
Rack Type	EIA 19 in
Total Ports, quantity	48 CAT6A Keystones (toll-free)
Wiring	T568A T568B
Dimensions	Height: 88.90 mm 3.50" Width: 482.6 mm 19 " Depth with cable management 170 mm 6.7"
Compatible Diameter Over Dielectric	maximum 1.168 mm 0.046"
Compatible Diameter Over Dielectric	Minimum 0.762 mm 0.03"
Current Rating at Temperature	1.5 A @ 20 °C 1.5 A @ 68 °F
Dielectric Withstand Voltage, RMS	conductive surface 1,500 Vac @ 60 Hz
Dielectric Withstand Voltage, RMS	contact-to-contact 1,000 Vac @ 60 Hz
Insulation Resistance minimum	500 MOhm
, Material Type	High-impact, flame-retardant, thermoplastic Powder-coated steel
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative Humidity	Up to 95%, non-condensing
Flammability Rating	UL 94 V-0
Safety Standard	UL cUL