

Full Shielded Field Termination CAT6A plug



Features:

- Full Shielded Field Termination plug is designed to terminate with Cat6A FTP or Cat7A S/FTP cables with larger diameter (22AWG to 26AWG), fit with the cable outer diameter from 6.0~8.5mm.
- The Field Termination RJ45 Plug offers easy, toolless termination and complies fully with ISO/IEC A and ANSI/TIA568C.2, Category 6 A standards.
- Providing excellent network cabling solutions for data centers and suitable for the Poe Plus (IEEE 802.3at) application for fast termination and connection to network cameras, wireless access points, LED signage, LED lights, and POE-enabled devices.
- Special design for easy, quick, and reliable installation with crew-fit boot. IP20 anti-dust plug cover is provided as well.

Technical Data

Design	Full-shielded Cat 6A FTP with zinc alloy housing
Termination standards	T568A & T568B wiring
Termination technique	Toolless for ease of termination easy, quick, and reliable installation
Construction	Die-cast zinc alloy construction
performance	CAT6A / 10G
Compatibility	Complied with the C6A patch cord component level
AWG supported	Cable wire gauge: 22AWG to 26AWG
Cable outer Ø	Cable outer diameter: 6.0 to 8.5mm (Cat6A FTP or Cat7A S/FTP cables)
Applications	Suitable for PoE plus (IEEE 802.3at) applications, Data Centers fast termination and connection to network cameras, wireless access points, LED signage, LED lights, and POE-enabled devices.
Standards	ISO/IEC A and ANSI/TIA568C.2, Category 6 A standards.
Color latch	7-different colors (blue, orange, yellow, white, green, black and red)

