

## WOODCHIPS SPECIFICATION SHEET

Parameter	Specification	Remarks
<b>PRODUCT IDENTITY</b>		
Product Name	Thailand Eucalyptus spp Woodchips (Debarked)	
Species	Eucalyptus spp	Thailand Origin
Applicable Incoterm	FOB — INCOTERM 2020	
Loading Port	Future Port, Thailand	
<b>CHIP SIZE SPECIFICATION</b>		
Oversize (> 40 mm length)	Maximum 5%	
Acceptable Range (4.8 mm – 40 mm)	Minimum 91%	
Preferred Range (9.5 mm – 22.2 mm)	Minimum 55%	
Undersize (< 4.8 mm length)	Maximum 3%	
Chip Thickness	Less than 5 mm	Reference only
<b>QUALITY &amp; CONTAMINATION</b>		
Bark & Rot Content	Maximum 1.0%	
Charcoal	Nil	
Contamination	Free from plastic, rubber, bitumen, metal, stone, and sand	Suitable for pulp & paper production
<b>WEIGHT MEASUREMENT</b>		
Weight Unit	BDMT (Bone Dry Metric Tonne)	1,000 kg per tonne
Green Weight Unit	GMT (Green Metric Tonne)	Green / undried chips
BDMT Formula	$BDMT = A \times (1 - B/100)$	A = tonnes per COA
Survey / Inspection	Independent licensed surveyor (SGS or equivalent)	Mutually agreed
<b>VESSEL &amp; STOWAGE</b>		
<b>Stowage Factor</b>	165 CBF / BDMT	Cubic Feet per Bone Dry Metric Tonne (Standard vessel load reference)