

- 1. Remove all liquids
- 2. Remove all food
- 3. Remove all bedding, towels, pillows and paper goods
- 4. Spread out mouse control and dryer sheets
- 5. Prop fridge and freezer doors open, add baking soda
- 6. Open cabinet doors
- 7. Crack open bathroom vent
- 8. Damp Rid
- 9. Unplug microwave, fan, tv and sound bar
- 10. Remove water filter, water pressure regulator and Keurig
- 11. Remove batteries from smoke detector, RV Lock (turn off switch on inside handle), remotes, batteries on tools
- 12. Water heater
 - a. Use 1-1/16" socket to remove plug
 - b. Lift lever and drain
 - c. Close lever and replace plug
 - d. Put bypass valve to winter position (inside trailer)

13. Water system

- a. Drain and flush grey and black water tanks
- b. Drain the fresh water tank and water lines (low point drains) open faucets (sink, toilet, shower, outdoor shower)
- c. Reinstall low point caps and close faucets
- d. Attach compressed air to water supply inlet
- e. Blow out water lines by opening each faucet (hot then cold) sink, shower, toilet, outside shower, low point drains (momentarily put water heater bypass valve in summer modes and then return to winter position)
- f. Drain grey tank again
- g. Add 1 gallon RV antifreeze in bucket, close fresh water tank valve, insert pickup hose in bucket. Turn on water pump. Open faucet, toilet, shower, outdoor shower and low points until pink flows
- 14. Plug in power
- 15. Place material between tires and ground (I used a thick rubber sheet)
- 16. Cover tires with wheel covers
- 17. Lower jacks

(This list is used for a Sunset Park RV Sun-Lite 16BH but can be used for any trailer)