




Straight Coupling [Straight - Union]

Series : L / S [Low / High pressure] — W01/ W02




Series	Tube OD [MM]	W.P	Dimensions						Weight Kg ca.	Ordering Codes
	D1	Bar	D2	L	L1	L2	S1	S2	Per 100g	Code number
Low pressure [L — Series]	6.0	500.0	4.0	25.5	42.6	10.0	12.0	14.0	1.83	W0601
	8.0	500.0	6.0	26.5	46.1	11.0	14.0	17.0	1.44	W0801
	10.0	500.0	7.0	28.0	48.6	13.0	17.0	19.0	1.90	W1001
	12.0	400.0	9.0	29.5	50.6	14.0	19.0	22.0	2.60	W1201
	15.0	400.0	12.0	32.5	54.0	16.0	24.0	27.0	2.67	W1501
	18.0	400.0	14.0	34.6	57.5	16.0	27.0	32.0	4.80	W1801
	22.0	250.0	18.0	36.0	58.0	20.0	32.0	36.0	6.65	W2201
	28.0	250.0	23.0	42.0	66.5	21.0	41.0	41.0	8.94	W2801
	35.0	250.0	30.0	46.5	71.0	20.0	46.0	50.0	13.90	W3501
	42.0	250.0	36.0	28.5	72.0	21.0	55.0	60.0	29.26	W4201
High pressure [S — Series]	6.0	800.0	4.0	28.5	47.2	16.0	14.0	17.0	2.52	W0602
	8.0	800.0	5.0	29.0	49.0	18.0	17.0	19.0	3.67	W0802
	10.0	800.0	7.0	32.0	54.5	17.0	19.0	22.0	4.23	W1002
	12.0	600.0	8.0	33.0	58.5	19.0	22.0	24.0	5.88	W1202
	14.0	600.0	10.0	38.0	57.0	22.0	24.0	27.0	7.52	W1402
	16.0	600.0	12.0	39.5	64.0	21.0	27.0	30.0	9.20	W1602
	20.0	600.0	16.0	46.5	78.0	23.0	32.0	36.0	14.27	W2002
	25.0	400.0	19.0	51.0	84.5	26.0	41.0	46.0	24.99	W2502
	30.0	400.0	22.0	54.0	89.0	27.0	46.0	50.0	33.08	W3002
	38.0	400.0	32.0	64.5	101.5	29.0	55.0	60.0	53.80	W3802


Connecting Parts -




Double Edge
Cutting Ring



Metric Nuts -
24° Fittings



24° Flared Cone
Set with sealing.



Support Sleeve
for W-B2 [24°]