4K Video Soundbar





MPIX WC-T01

All in one 4K Video Bar having multiple functionality - Speaker Tracking, Auto Framing.

Designed for Huddle and Small Meeting Rooms.

Features: -

- Integrated design of video cam, microphones and speakers, easy setup of remote video conference;
- Smart and precise positioning of speaker and auto framing, giving best view of speaker and all attendees;
- 4K UHD video for superb experience
- HFOV up to 110°, full cover of meeting room
- Built-in high-sense mic array, pickup range up to 5 meters, supporting AGC, AEC, ANC
- Supporting 2 external cascade microphones to extend pickup range up to 12 meters;
- Speaker with Passive diaphragm design with enhanced bass experience
- USB 3.0 interface, supporting MJPEG/H.264/H.265 data
- Built-in Bluetooth for easy connection of external devices
- Compatible with main cloud platforms such as Zoom and Microsoft Teams etc.
- Equipped with bracket for TV installation

Speaker Tracking

Auto Framing

All in one Video Soundbar



Technical Specifications: -

Dimensions		
	All in one Video Soundbar	
	Camera	
	Image Sensor	1/2.8" 4K CMOS, 8.46MP
	Iris	F2.2
	Focal Length	f=2.1mm
	Digital Zoom	4x
	FOV	Horizontal: 110°, Vertical: 74°
	EPTZ	Support
	Min Focus Distance	50cm
	Video Output Format	4KP30
	Exposure	Auto, Manual, Shutter Priority
(L x W x H) 603mm x 74mm x93mm	White Balance	Auto, Manual
	DNR	2D/3D
	Image Flip	Flip/Mirror
	Audio	
	Built-in Mic	4 MIC array
	Pick-up Distance	5 meters
	Audio Process	AEC/ANC/AGC
		1xUSB3.0, Type B. Support UVC 1.0
	USB	MJPEG/H.264/H.265
		MJPEG: 4KP30/P25,
		1080P30/P25, 720P30/P25,
		360P30/P25
		H.264: 4KP20, 1080P30/P25,
		720P30/P25,
		360P30/P25
		H.265: 4KP20, 1080P30/P25,
		720P30/P25,
OPAQUA is a Trademark		360P30/P25
Registered Brand	EPTZ	EPTZ Support
	Other	
Make in India Product	Network Interface	RJ45, 10M/100M
	Remote Control	
		Support
Contact us at	Mic Extension	Support
	General	
	Power	DC12V; <8W
+91 8448791610	Dimension (L×W×H)	603mm×74mm×93mm
	Operating Temperature	0°C ~ +40°C
	Storage Temperature	-20°C ~ +60°C
	Weight	≤2kg

www.opaqua.in

BIS Certified