

FABTECH HYDRO EXTRACTOR



**CAPACITY
AVAILABLE FROM
12 KG TO 50 KG**

Direct Drive. Self Balancing

Direct drive with heavy-duty motor and rubber cushion ensures self-balancing, no belts, no speed loss, and quiet operation.

Durable Lock Mechanism

Durable lock mechanism ensures safe and reliable locking at high RPM.

Automatic DC Injection Brake

Automatic DC brake with digital timing ensures safe, maintenance-free operation—no pedals or levers needed.

HEAVY DUTY DESIGN

Inner cylinder removable without dismantling the outer drum, electrically interlocked top lid for safety, three-position drain connection, and a galvanized, hot-painted heavy base frame for strength and long rust-free life.

Parameter/Models	HDS 12	HDS 20	HDS 30	HDS 50
Capacity (Dry Weight)	12 KG	20 KG	30 KG	50 KG
Basket Dia x Depth	450 x 300 mm	550 x 300 mm	700 x 300 mm	1000 x 300 mm
Motor Power	0.37 KW	2.20 KW	3.75 KW	7.50 KW
Net Weight	210 KG	210 KG	395 KG	820 KG
Dimensions (WxDxH)	760 x 920 x 1000 mm	880 x 1030 x 1100 mm	1020 x 1170 x 1700 mm	1370 x 1580 x 1210 mm