

PROFESSIONAL BLUE POWER TOOLS FOR TRADE AND INDUSTRY 2024









BeConnected is a simple way for users to stay connected through product registration

Avail the best-in-class Bosch products with all the exciting benefits such as Paperless Warranty, Warranty Extension, Reward Points*, Cash Back*, Product Information and Seamless After Sales Service













BENEFITS

Anti-Counterfeit

Certified Bosch-made products only

Warranty Certificate

Quality products with certified assurances

Promotions / Coupons

Win exciting rewards and prizes

Communication / Bosch Power Tools

Stay up to date with the latest from Bosch Power Tools

Product Info (Video)

Valuable demos and tutorials on the product

Where to Buy/Service

Locate the nearest Bosch dealer to you

Fleet Management

Manage your entire portfolio of products

Ratings & Reviews

Share your valuable experience with us and your peers

JOIN BECONNECTED TO GET FREE WARRANTY EXTENSION!

- Extended Warranty
- **Genuine Tool Check**
- 🙎 Service Center Locator
- Product Information
- **Promotional Offer**







NOW ALL BOSCH PROFESSIONAL TOOLS COME WITH 1 YEAR WARRANTY





For more details, visit www.bosch-pt.co.in or the BeConnected app



Bosch GO 2.0 Professional



Technical Specifications

Part no. 06019H21L1 Battery voltage Torque, max. (hard/soft) No-load speed Electronic brake Yes Smart stop Yes Tool holder

3.6V 5/2.5 Nm 360 rpm

1/4" Inter HEX

Bosch GO 2.0 Kit Professional



Technical Specifications

Part no. 06019H2181 3.6V Battery voltage Torque, max. (hard/soft) 5/2.5 Nm No-load speed 360 rpm Electronic brake Yes Smart stop Yes ¼" Inter HEX Tool holder Weight excl. battery 0.31 kg

COMING New! Bosch GO 3.0 SOON Professional





BOSCH (FOSISTEEL MRP: ₹5,600

Technical Specifications

Part no. Battery voltage Torque (min/hard/soft) No-load speed Electronic brake Smart stop Charging port Weight excl. battery

06019H2181 2.0 Ah 0.1/.5/5 Nm 360 rpm Yes Yes USB-C 0.31 kg

New Launch! GRO 12V-35 (Solo) Professional



Technical Specifications

Part no. 06019C50K1 Battery voltage 12V No-load speed 5,000 / 35,000 rpm Weight 600 g 44 x 36 x 11.5 cm

Dimensions L x W x H









MRP: ₹8,700

New! Pro Pruner Professional



Technical Specifications

Part no. Rated voltage Battery capacity* Max. cutting diameter No. of cuts per charge** Weight with 12V/2.0Ah battery Weight w/o battery BOSCH

06019K10F1 12V 2.0 Ah 25 mm 4500 1 kg

MRP: ₹ 25.900

0.8 kg

GSR 120-Li (Single Battery)

Professional



Technical Specifications

06019G80F1 Part no. Battery voltage 12V No-load speed 0-400 / 0-1,500 rpm Torque, max. (hard/soft) 30/14 Nm Max. screw diameter 7 mm Chuck size 10 mm Drilling in wood/metal 20/10 mm Weight incl. battery 0.97 kg DSCH FEEDER MRP: ₹7,900

GSR 12V-30 (Solo) Professional

GSR 120-Li Kit Professional



Technical Specifications

06019G80F0 Battery voltage No-load speed(1ST/2ND) Torque (hard/soft) Max. screw diameter Max. drilling (wood/steel) 20/10 mm Chuck size

12V 0-400/0-1,500 rpm 30/14 Nm 7 mm 10 mm







Battery voltage 12V No-load speed 0-420/0-1,600 rpm Torque, max. (hard/soft) 30/18 Nm Max. screw diameter 8 mm

Max. drilling (wood/steel) 20/10 mm

GSR 12V-35 HX (Solo) Professional



Technical Specifications

Part no. Battery voltage No-load speed (1st/2nd) Torque (soft/hard) Max. screw diameter Max. drilling (wood/steel) Chuck capacity, min./max. 0.8/10 mm Weight excl. battery

HEAVY BUTY MRP: ₹12,500

06019J9180 12V 0-460/0-1,750 rpm 20/35/- Nm

8 mm 32/10 mm 0.57 kg

GSR 12V-15 FC Professional



Technical Specifications

06019F60F0 Battery voltage 12V No-load speed (1st/2nd) 0 - 400/0 - 1,300 rpm Torque (hard/soft) 30/15 Nm Max. screw diameter 7 mm Max. drilling (wood/steel) 19/10 mm Chuck size 10 mm

DUTY BeConnected

MRP: ₹28,300

GSR 180-Li Professional





Technical Specifications

Part no. Battery voltage No-load speed (1st/2nd) Torque (hard/soft) Max. screw diameter Max. drilling (wood/steel) Chuck size

06019F81F0 18V 0-450/0-1,700 rpm 54 /21 Nm 10 mm 35/10 mm 13 mm

SCH

| SCH | SEC | SHECKHOOL | MRP: ₹19,500

New! GSR 185-Li Kit Professional



Technical Specifications

Part no. 06019K30F0 Battery voltage 18V 162 mm Head length No-load speed 0-500 / 1,900 rpm Max. torque (hard / soft) 50/21 Nm Chuck Size 13 mm Max. drilling (wood/metal) 35 /10 mm Weight (w/2.0Ah) 1.3 kg MRP: ₹17.700 H (Ty) BeCo

GSR 18V-50 (Solo) Professional



Technical Specifications

06019H5082 18V Battery voltage No-load speed(1ST/2ND) 0-460/0-1,800 rpm Torque (soft/hard/max.) 28/50/50 Nm Chuck Size 13 mm Max. drilling

(alum/wood/steel) 13 / 35 / 13 mm Weight excl. battery 1 kg HEAVY A THE THE BECOMMENTED MRP: ₹15,000

GSR 18V-50 Kit Professional



Technical Specifications

Part no. 06019H50F0 Battery voltage 18V No-load speed 0-460/0-1,800 rpm Torque, max. (hard/soft) 50/28 Nm Max. drilling (wood/steel) 35 /13 mm Max. screw diameter 10 mm







HEAVY BeConnected MRP: ₹28,300

GSB 120-Li Kit Professional



Part no. Battery voltage No-load speed(1ST/2ND) 0-400/0-1,500 rpm Torque (hard/soft) Impact rate Max. drilling (wood/steel/masonry) Weight with battery

06019G81F2 30/14 Nm 0 - 18750 bpm 20 / 10 / 8 mm

1.1 kg BeConnected MRP: ₹13,700

GSB 180-Li Professional





Technical Specifications

Part no. 06019F83F0 Battery voltage 18V No-load speed (1st/2nd) 0-450/0-1,700 rpm Torque (hard/soft) 54 /21 Nm Max. screw diameter 10 mm Max. drilling 35 / 10 / 8 mm

wood/steel/masonry) Chuck size

13 mm SCH ## (T) BeConnected MRP: ₹20,600

New! GSB 185-Li Kit Professional



Technical Specifications

Part no. Battery voltage No-load speed (1st/2nd) Weight (w/2.0Ah) Max. screw diameter Max. drilling (wood/metal/masonry) Chuck material

06019K31F2 18V 0-500/0-1,900 rpm 1.3kg 10 mm

35 / 10 / 10 mm

Metal MRP: ₹19,800

New! GSB 18V-150 C (Solo)



Technical Specifications

Part no Battery voltage 18V Torque (soft/hard/max.) No-load speed (1st/2nd) Max. impact rate Chuck capacity, min./max. Weight excl. battery Chuck material

06019J51L0 84/100/150 Nm 0-550/0-2,200 rpm 30,000 bpm 1.5 /13 mm 2.2 kg Metal MRP: ₹30,900

GDR 120-Li Kit Professional



Technical Specifications Part no. Battery voltage No-load speed (1st/2nd) Torque (hard) Max screw diameter Rated impact rate Bit holder

06019F00F0 12V 0-1,300/0-2,600 rpm 100 Nm 8 mm 0-1,900/0-3,200 bpm ¼" hexagon socket

GDR 12V-EC Professional

DUTY BeConnected



Technical Specifications

Part no. Battery voltage No-load speed Torque (hard) Max screw diameter Rated impact rate Bit holder

12V 2,600 rpm 110 Nm M4-M12 0 - 3,100 bpm 1/4" internal hexagon

06019E00F6







06019G42F0

0 - 3,400 rpm

18V

200 Nm

M6 - M16

New! GDR 180-Li Professional



Technical Specifications

Part no. Battery voltage No-load speed Impact rate Max. torque Tool holder Screw diameter Weight excl. battery BOSCH AND SHOCK MRP: ₹30,500

06019G51F0 18V

0 - 2.800 rpm 0 - 3,600 bpm 160 Nm ¼" Hex Uni

M6-M14 1.1 kg

GDX 18V-200 C Professional



Technical Specifications

Part no. Battery voltage Torque max. No-load speed Screw Diameter Bit holder

Weight excl. battery

¼" internal hexagon & ½" external square 1.1 kg

HEAVY BECHNESSEE MRP: ₹41,200

GDS 18V-200 Professional



Technical Specifications

Battery voltage Square drive No-load speed Impact rate Max. torque Screw diameter Weight excl. battery

Part no.

06019J23F0 18V 1/2 inch 0 - 3,400 rpm 0 - 4,200 bpm 200 Nm M6 - M16 1.1 kg HEAVY BECHNESSEE MRP: ₹35,900

GDS 250-Li Professional



Technical Specifications 06019G61F0

Part no. Battery voltage Max. torque No-load speed Impact rate Tool holder Screw size Weight excl. battery

M10 - M18 1.2 kg SCH ## ## (100 BeCommond MRP: ₹36,100

18V

250 Nm

0 - 2,400 rpm 0 - 3,300 bpm

1/2 Square

GDS 18V-400 (Solo) Professional



Technical Specifications

Battery voltage Max. declared torque Square drive No-load speed Screw Diameter Head length Weight (w/o battery)

M10 - M20 HEAVY 🕮 🕥 Becomected 📰 MRP: ₹19,600

172 mm 1.25 kg

0 - 2,500 rpm

06019K00K1

18V

400 Nm

1/2 inch

GDS 18V-400 Professional



Technical Specifications

06019K00F0 Battery voltage 18V Max. declared torque 400 Nm 1/2 inch Square drive No-load speed 0 - 2,500 rpm Screw Diameter M10 - M20 Head length 172 mm Weight (w GBA 18V 5.0Ah) 1.85 kg HEAVY BUTY BECOMMENT MRP: ₹49,500

COMING New! GDS 18V-1050 H (Solo)Professional



Technical Specifications

Part no. 06019J85F0 Battery voltage 18V 1,050 Nm Max. tightening torque Max. breakaway torque 1,700 Nm Square drive 3/4 inch No-load speed 0-800/1,200/1,750 rpm Bolt diameter M10 - M24 Weight (w/o battery) 2.9 kg DUTY BeConnected

GDS 18V-1050 H Professional



Technical Specifications

Part no. 06019J85F0 Battery voltage 18V Max. tightening torque 1,050 Nm Max. breakaway torque 1,700 Nm Square drive 3/4 inch No-load speed 0-800/1,200/1,750 rpm Bolt diameter M10 - M24 Weight (w/o battery) 2.9 kg DUTY BECONNECTED MRP: ₹66,800

COMING New! GDS 18V-1600 HC SOON (Solo) Professional



Technical Specifications

Part no. 06019M1080 Battery voltage 18V Max Declared Torque 1600 Nm Square drive 3/4 inch Speed Setting 3 No Load Speed

0-800 / 1300 / 1750 rpm 0-1550 / 2200 / 2350 bhp Impact rate M16 - M33 Screw Diameter

Connectivity feature



Yes

New! GBH 185-Li Professional



Technical Specifications

Part no. 06119240F0 Battery voltage 18V Impact energy 1.9 J 0 - 1,050 rpm No-load speed Impact rate 0 - 4,67504 - 22 mm Max. drilling in concrete 13 mm Max. drilling in steel Max. drilling in wood 20 mm HEAVY A MRP: ₹44,400

New! GDE 12 Professional



Technical Specifications

Part no. 1600A02BW0 Maximum drilling depth 100 mm 165 mm Max. drill bit length Drilling diameter 4-12 mm Weight 1.1 kg



MRP: ₹8,000

GBH 18V-34 CF (Solo) Professional



Technical Specifications

DUTY BeConnected

0611914082 Part no Battery voltage 18V 5.8 J Max. impact energy Rated speed 0 - 500 rpm 0 - 2,900 bpm Impact rate at rated speed Max. drilling in metal 13 mm Max. drilling in wood 40 mm Max. drilling in concrete 34 mm

MRP: ₹84,300

GWS 18V-10(100 mm) Kit Professional



Technical Specifications

Battery voltage Grinding spindle thread No-load speed Weight w/o battery Disc. diameter

06019J40F0 18V M 10

9,000 rpm 2.0 kg 100 mm



Battery voltage No-load speed Spindle size Disc diameter Grip size front / back Weight w/o battery Weight w/ 4.0 battery 06019H90F0 18V (15t/2") 11,000 rpm M 10 100 mm 185 / 156 1.4 kg





2.0 kg

GWS 180-Li(100 mm) Kit Professional

GWS 180-Li (Solo) (100mm) Professional

HEAVY BECOMMENT MRP: ₹47,700



Technical Specifications

Part no. Battery voltage No-load speed Spindle size Disc diameter Grip size front / back Weight w/o battery Weight w/ 4.0 battery (T) BeCsen

06019H90K0 18V 11,000 rpm M 10 100 mm 185 / 156 1.4 kg

2.0 kg MRP: ₹16,700 Professional



Part no. 06019H91K0 Battery voltage 18V No-load speed 11,000 rpm Grinding/cutting disc 125 mm Grinding spindle thread M 14 Weight excluding battery 2.0 kg







MRP: ₹18,700

GWS 18V-10 (125 mm) (Solo) Professional



Part no. 06019J4002 Battery voltage 18V 9,000 rpm 125 mm M 14 2.1 kg



Improved pruning efficiency, with the pull of a trigger!

- (4) Sharp and durable blades which always cut cleanly
- Easy and safe to use with double safety switch
- (5) 4500 cuts from just 1 hour of fast charging
- (Portable and lightweight for continuous use



GBL 18V-120 (Solo) Professional



Technical Specifications

06019F51L0 Battery voltage 18V Max. air speed 75 m/s Max. airflow 120 m3/h No-load speed 17,000 rpm Weight excluding battery 1.1 kg









MRP: ₹9,900

GKS 185-Li (Solo) Professional



Technical Specifications

Part no. Voltage Blade size / bore size No-load speed Cutting depth, 90°/45° Weight w/o battery Bevel capacity max.

06016C12L1 18V 165/20 mm 5,000 rpm 57/41 mm

2.8 kg 50°





MRP: ₹19,800

New! GHO 185-LI (Solo) Professional



Technical Specifications

Part no. Battery voltage No-load speed Planning depth Planning width Rebating depth Double chipping

HEAVY DUTY

06015B5080 18V 14,000 rpm 2.6 mm

82 mm 9 mm Yes

MRP: ₹16.900

New! GRG 18v-16 C (Solo) Professional

Technical Specifications Part no. Battery voltage Motor Pulling force Stroke length Rivet diameter Weight excl. battery

16,000 N 25 mm 3.0 - 6.4 mm 1.6 kg

Brushless

06019K5080

18V





MRP: ₹78,800

GSA 18V-Li Compact (Solo) Professional



Technical Specifications

Part no. Battery voltage Cutting depth in wood Stroke lengths Cutting depth in metal Stroke rate (1st gear / 2nd gear)

HEAVY DUTY

MRP: ₹28,500

GSA 18V-32 (Solo) Professional





100 mm

06016A5080

18V

200 mm

21 mm

0 - 3,050 spm

Technical Specifications 06016A8108

Cutting depth in wood Stroke lengths Cutting depth in metal

175 mm Stroke rate (1st gear / 2nd gear) 0 - 2.500 spm Weight excl. battery 3.5 kg







MRP: ₹65,500

230 mm

32 mm

New! GSA 185-Li (Solo) Professional



Technical Specifications

Part no Voltage No-load stroke rate Stroke length Dimensions (LxWxH) Weight w/o battery Cutting depth (wood)

BOSCH

Pyefessional

06016C00L0 18V 0 - 2.900 min⁻¹ 28 mm

450 x 96 x 170 3.2 kg 230 mm

MRP: ₹21,500

GEX 185-Li (Solo) Professional



Technical Specifications

06013A5080 18V Battery voltage 6.000 - 10.000 No-load speed Sanding sheet diameter 125 mm 135 mm Height Sanding stroke 2.5 mm Vibration 2.2 m/s²





MRP: ₹10,500

GTB 185-Li (Solo) Professional



Technical Specifications

Part no. Rated voltage No-load speed Soft torque Weight (w/o batt) Weight (w/2.0Ah batt) Dimension (L/W/H)

06019K70L1 18V 0 - 4,500 5.2 Nm 0.95 kg 1.3 kg 261/56/222





GAS 18V-1 (Solo) Professional

MRP: ₹14,300

GST 185-Li (Solo) Professional



Technical Specifications

Part no. 06015B30L3 Battery voltage 18V Stroke length 26 mm Cutting depth 125 mm Bladeholder SUS LED Yes Weight (w/4.0 Ah battery) 2.6 kg

Chuck Size 13 mm MRP: ₹15,700

BATTERY / CHARGERS





Technical Specifications

Part no 1600A00F6X Battery voltage 12V 2 0 Ah Battery capacity Weight 175 g

Suitable for

• 10.8 V

12.0 V

MRP: ₹3.900

Technical Specifications 06019C62L0

Part no Battery voltage Weight excl. battery Container volume Filter surface area Max. airflow rate Max. vacuum pressure

18V 1.3 kg 0.71 55 cm² 10 l/s 60 mbar





GBA 18V 2.0 Ah Professional

BATTERY / CHARGERS



Technical Specifications

Part no. 1600A001CG Battery voltage 18V Battery capacity 2.0 Ah Weight 300 g

Suitable for

All 18 V

MRP: ₹6,300

GBA 18V 4.0 Ah Professional



Technical Specifications

Part no. 1600A00163 18V Battery voltage Battery capacity 4.0 Ah 600 g Weight

Suitable for All 18 V



MRP: ₹9,600

GBA 18V 5.0 Ah Professional



Technical Specifications

Part no. 1600A001Z9 Battery voltage 18V Battery capacity 5.0 Ah 620 g Weight

Suitable for

• All 18 V

MRP: ₹10,200

Technical Specifications

Part no. 1600A0193L 18V Battery voltage 4.0 Ah Battery capacity Weight 515 g

Suitable for

• All 18 V



MRP: ₹12,000

BATTERY / CHARGERS

New! ProCORE 18V 8.0 Ah Professional



Technical Specifications


Part no. 1600A0193N Battery voltage 18V 8.0 Ah Battery capacity Weight 955 g

Suitable for

• All 18 V



MRP: ₹22,300





Technical Specifications

Part no. 1600A021L7 Charge current 2A 24 min Charging time min. Input voltage 230 V Model Li-lon quick charger Weight, approx. 0.4 kg



MRP: ₹3,275

GAL 12V-40 Professional



Technical Specifications

Part no. 1600A022V0 Charge current 4A Charging time min. 24 min Input voltage 230 V Model. Li-lon quick charger 0.4 kg Weight, approx.

MRP: ₹3,600



GAL 18V-40 Professional



Technical Specifications

Battery charging voltage 14.4-18V 4A Charge current Charging time min. 36 min Li-lon quick charger Model 550 g Weight, approx.



MRP: ₹4,600

1600A022V1

GAL 12V-40 + 2x12V 2.0Ah Professional





GAL 18V-40 + 2x GBA 18V 2.0Ah Professional



Technical Specifications

1600A022V3 Battery 1 capacity Battery voltage 2.0 Ah 12V 0.185 kg Battery 1 weight Cell type Li-lon Battery charging voltage 12 V 4 A Charge current Charger weight 0.45 kg

MRP: ₹10,100

Technical Specifications

Part no. 1600A022V4 2.0 Ah Battery 1 capacity Battery voltage 18V 0.35 kg Battery 1 weight Cell type Li-lon Battery charging voltage 14.4-18V Charge current 4 A Charger weight 0.55 kg

MRP: ₹16,900

GAL 18V-40 + 2x GBA 18V 4.0Ah Professional







Technical Specifications

1600A022V2 4.0 Ah Battery 1 capacity Battery voltage 18V Battery 1 weight 0.6 kg Cell type Li-lon Battery charging voltage 14.4-18 V Charge current 4A 0.55 kg Charger weight MRP: ₹23,300 Available in THREE CLASSES PERFORMANCE COMPACT 100% COMPATIBLE

DEMOLITION HAMMERS

New! GSH 500 Hex Professional



Technical Specifications

Part no. 06113386F1 1,100 W Input power Impact rate at rated speed 2,900 bpm Impact energy 7.8 J Tool holder 17 Hex mm Side handle Straight handle Weight 5.5 kg





Technical Specifications

06113370F0 Rated power input 1,100 W Impact energy 7.5J Rated speed 2,850 bpm 5.6 kg Weight without cable

*with vario lock feature for chisel adjustment

DUTY BeConnected

MRP: ₹49.500

MRP: ₹28,300

GSH 500 Max Professional



Technical Specifications

Part no. 06113387F0 Input power 1.100 W Impactrate atrated speed 2,900 bpm 7.8 J Impact energy SDS MAX Tool holder Side handle Straight handle Weight 5.7 kg

Professional BeCommocited

MRP: ₹36,000

New! GSH 11 E Promo Professional



Technical Specifications

Part no. 06113168F2 Power input 1,500 W 900 - 1,890 bpm Impact rate Impact energy 16.8 J 10.1 kg Weight

HEAVY DUTY BeConnected

MRP: ₹63.100

GSH 11 VC Professional



Technical Specifications

Part no. 06113360F0 Power input 1,700 W Impact energy 23 J Impact rate at

rated speed 900 - 1,700 bpm Weight without cable 11.4 kg

DUTY BeCsenected

MRP: ₹ 1,10,300

New Launch! GSH 14 C Professional



Technical Specifications

Power input 1,750 W Impact rated at 1.900 bpm rated speed Impact energy (EPTA) 28 J

Width x length x height 140 x 750 x 280 Weight 14.6 kg



MRP: ₹1,04,400

06113440F0

GSH 16-30 Professional



Technical Specifications

06113351F0 1,750 W Power input Impact rate 1,300 bpm Impact energy 41 J 16.5 kg Weight

GSH 27 VC Professional

Part no.

Technical Specifications

061130A0F0 2.000 W Rated power input Impact energy 62 J Impact rate at rated speed 1,000 bpm Weight 29.5 Kg



MRP: ₹1,54,600



ROTARY HAMMERS

New! GBH 220 Professional



Technical Specifications

Part no. 06112A60F0 Rated input power 720 W Impact energy 2 J Impact rate at rated speed 0 - 4,800 bpm 4-22 mm Drilling diameter Max. drilling diameter 13/30/22 mm Tool holder SDS Plus

Bosch
Professional

BeCommected

MRP: ₹11,100

GBH 2-24 DRE Professional



Technical Specifications

Part no. 06112721F1 Power input 790 W Impact energy 2.7 J Drilling capacity 24 mm 1,300 rpm No-load speed Impact rate 4,200 bpm Weight 2.8 kg

HEAVY BECSEROCIAN

MRP: ₹17,200

GBH 2-26 RE Professional



Technical Specifications

Drilling dia. in concrete Drilling dia. in steel Drilling dia. in wood Core bits masonry Power input No-load speed Single impact energy

DUTY BeConnected

0611251755 4-26 mm 13 mm

30 mm 68 mm 800 W 0 - 900 rpm 0-3J

MRP: ₹21,200

GBH 2-26 DRE + Drill Chuck



Technical Specifications

Part no. Drilling dia. in concrete Drilling dia. in steel Drilling dia. in wood Core bits masonry Power input No-load speed

Single impact energy HEAVY BECSSTREETER

06112537F0 4-26 mm 13 mm

30 mm 68 mm 800 W 0 - 900 rpm 2.7J

MRP: ₹22.900

GBH 2-28 DV Professional



Technical Specifications

Drilling dia. in concrete Drilling dia. in steel Drilling dia. in wood Core diameter masonry Rated power input No-load speed Impact energy

DUTY (T) BeConnected

06112671F0 4-28 mm 13 mm 30 mm

68 mm 850 W 0 - 1,300 rpm 0-3.2 J

MRP: ₹25,800

GBH 4-32 DFR Professional



Technical Specifications

06113321F0 Drilling dia. in concrete 6 - 32 mm 13 mm Drilling dia. in steel Drilling dia. in wood 32 mm Power input 900 W No-load speed 0 - 800 rpm 4.2 J Impact energy Weight 4.7 kg

HEAVY DUTY BeCsenected

MRP: ₹49,900

GBH 5-40 D Professional



Technical Specifications

Drilling dia. in concrete Rated power input Impact energy Impact rate at rated speed Rated speed No-load Speed Weight

DUTY BeConnected

06112690F0 12 -40 mm 1,100 W 8.5 J 1,500 - 2,900 bpm 170 - 340 rpm 0 - 760 rpm 6.8 kg MRP: ₹65,300



ROTARY HAMMERS

GBH 8-45 DV Professional



Technical Specifications

Part no. 06112650F0 Rated input power 1,500 W Impact energy 12.5 J Impact rate at rated speed 1,380-2,760 bpm 0 - 305 rpm Rated speed Drilling dia. Hammer drill bits 12-45 mm 20-40 mm Optimum range

Drilling dia. breakthrough drill bits 80 mm Weight without cable 8.9 kg HEAVY DUTY

MRP: ₹1,18,300

GBH 12-52 DV Professional



Technical Specifications

Weight

HEAVY DUTY

Part no. 06112660F0 Input Power 1,700 W Max. Impact Energy 19 J Impact Rate At Rated Speed 1,750 - 2,150 bpm Rated Speed 0 - 220 rpm Drilling dia. in concrete 12 - 52 mm With hammer drill bits

11.9 kg

MRP: ₹1,41,400

MRP: ₹7,250

DIAMOND/STONE CUTTER

GDC 120 Professional





Technical Specifications

Part no Rated Power Input No-load Speed Tool Blade Cutting Depth (At 90°) Cord Length Net Weight

Professional BeCommonton

06013930F1 1,200 W 12,000 rpm 4 Inch 34 mm

1.5 m

2.5 Kg MRP: ₹6,300

New! GDC 141 Professional



Technical Specifications

Part no. 06013A41F0 Rated Power Input 1,450 W No-load Speed Max. Cutting Disc Dia. Max. Cutting Depth Weight

(Tg) BeConnected

12,000 rpm 125 mm 40 mm 3 Kg

New! GDC 140 Professional



Technical Specifications

Part no. 06013A40F1 Rated Power Input 1,400 W No-load Speed 12,000 rpm Max. Cutting Disc Diameter 115 mm Max. Cutting Depth 35 mm 2.9 kg Weight





MRP: ₹6,500





ANGLE GRINDERS

GWS 600 Professional



Technical Specifications

Part no. Power input No-load speed Grinding spindle thread Disc diameter Weight

060137505F 670 W 11,000 rpm

M 10 100 mm 1.8 kg



New! GWS 800 Professional

Technical Specifications

Part no. Power input Disc diameter No-load speed Spindle diameter Weight

06013943F0 800 W 100 mm 11,000 rpm M 10 1.6 kg



MRP: ₹4,100



Professional BeConnection GWS 750-100 Professional

MRP: ₹5,500

New! GWS 800 Promo Professional



Technical Specifications

Part no. Power input Disc diameter No-load speed Spindle diameter Weight

06013943F0 800 W 100 mm 11,000 rpm M 10 1.6 kg

Technical Specifications Part no. Power input Disc diameter

No-load speed Spindle diameter Weight

750 W 100 mm 11,000 rpm M 10 1.8 kg

06013940F0

Professional BeCommunities

GWS 900-100 Professional

MRP: ₹5.500

HEAVY DUTY BeConnector

MRP: ₹5.600

GWS 6-125 Professional



Technical Specifications

Part no. 06013960F0 Power input 900 W 100 mm Disc diameter 11,000 rpm No-load speed Spindle diameter M 10 Weight 1.8 kg



Technical Specifications

Part no. 060137515A 670 W Rated power input No-load speed 11,000 rpm Grinding spindle thread M 14 Disc diameter 125 mm Weight without cable 1.9 kg





MRP: ₹6,900





MRP: ₹6,100

GWS 900-125 S Professional



Technical Specifications

Rated input power No-load speed Disc diameter Grinding spindle thread Weight

06013961F2 900 W 2,800 - 11,000 rpm 125 mm M 14 1.9 kg

New! GWS 12-125 S Professional



Technical Specifications Part no.

06013A60F0 Rated input power 1.200 W No-load speed 2,800 - 11,000 rpm Grinding spindle thread M 14 Weight 1.9 kg



MRP: ₹9,000





MRP: ₹10,400

ANGLE GRINDERS

GWS 14-125 CI Professional



Technical Specifications

Part no. Power input No-load speed Grinding spindle thread Disc diameter Weight without cable

HEAVY DUTY BeConnected

06018242F1 1,400 W 11,000 rpm M 14 125 mm

MRP: ₹13.000

2.2 kg

GWS 18-125 L Professional

Technical Specifications

Part no. 06017A30F1 Power input 1 800 W No-load speed 11,500 rpm Grinding spindle thread M 14 Disc diameter 125 mm Weight 2.5 kg

GWS 24-180 JZ Professional



MRP: ₹22,900

GWX 17-125 S Professional



Technical Specifications

Part no. Power input No-load speed Disc diameter Wire cup brush, diameter

Weight

06017C40F2 1,700 W 2,800 - 11,500 rpm 125 mm 75 mm

2.5 kg

Weight

Part no.

Power input

No-load speed

Disc diameter

HEAVY DUTY BeConnected

Grinding spindle thread

Technical Specifications

MRP: ₹20,400

06018C23F0

2,400 W

180 mm

M 14 5.8 kg

8,500 rpm

HEAVY DUTY BeConnected

MRP: ₹23,300

GWS 2200-230 Professional



Technical Specifications

GWS 30-180 B Professional

06018G00F0 Power input 2,800 W No-load speed 8,500 rpm 180 mm Disc diameter Grinding spindle thread M 14 Weight 5.7 kg

HEAVY (T) BeConnected MRP: ₹39,200

Technical Specifications

84672900 2,200 W Rated power input No-load speed 6,500 rpm M14 Grinding spindle Disc diameter 230 mm Weight 5.5 kg





GWS 30-230 B Professional



Technical Specifications

Part no. 06018G10F0 2.800 W Rated power input No-load speed 6,500 rpm Grinding spindle M 14 Disc diameter 230 mm Weight 5.9 kg

GWS 24-180 Professional



Technical Specifications

Part no. 06018C20F0 2,400 W Rated power input No-Load speed 8,500 rpm Grinding spindle M 14 Disc diameter 180 mm Weight 4.9 kg



CYCLON TECH



RESTART PROTECTION

Prevents accidental restarts

OVERLOAD PROTECTION

Prevents motor burnout Under extended overload conditions

ANGLE GRINDERS

GWS 2200-180 Professional



Technical Specifications

06018C00F0 2,200 W Rated power input No-Load speed 8,500 rpm Grinding spindle M 14 Disc diameter 180 mm Weight 5.5 kg



MRP: ₹14,000

GWS 24-230 Professional



Technical Specifications

Part no. 06018C30F0 2,400 W Power input No-load speed 6,500 rpm Grinding spindle thread M 14 Disc diameter 230 mm Weight without cable 6 kg



HEAVY BeConnected

MRP: ₹21,800

GWS 24-230 JZ Professional



Technical Specifications

Part no. 06018C33F0 Power input 2,400 W No-load speed 6,500 rpm Grinding spindle thread M 14 230 mm Disc diameter Weight 6 kg





MRP: ₹22,300

SPECIALITY TOOLS

New! GAC 250 Professional



Technical Specifications Part No. 06012B60F0

Power Input No-load chain speed Chain bar length Max. cutting capacity Tool weight





MRP: ₹22,300

1.200 W

335 mm

250 mm

4.7 kg

max. 12 m/s

GBL 620 Professional



Technical Specifications 06019805f0

Part No. Power Input No-load Speed Volumetric Flow Rate Standard Accessories Weight Without Cable

16,000 rpm 3.5 m3/min 1 Nozzle 1.7 kg

620 W





MRP: ₹5,000

GBL 650 Professional



Technical Specifications

Part no. Input power No-load Speed Flow Rate Weight

06019M40F0 650 W 16,000 rpm 3.7 m3/min 1.4 kg



MRP: ₹4,700

GBL 82-270 Professional



Technical Specifications

Part no. Input power No-load Speed Flow Rate Weight

06019804F5 820 W 16,000 rpm 4.5 M3/min 2.25 Kg





MRP: ₹8,000

SPECIALITY TOOLS

GHG 180 Professional



Technical Specifications

Part no. Power input Max. temperature Air flow rate Over-heat Protection Weight

DUTY BeConnected

060194D0F0 1,800 W 60 / 350 / 550° C

350 / 350 / 550 lpm

Yes 0.75 kg

MRP: ₹4,300

GHG 20-63 Professional



Technical Specifications

Part no. Power input Temperature range Adjustable temperature Steps Air flow rate

Durability Weight

06012A62F0 2.000 W 50-630°C

Yes 150 - 500 litre/min

600 h

0.65 kg MRP: ₹12,100

GHG 20-60 Professional



Technical Specifications

Part no. Power input Temperature max. Adjustable temp steps Air flow rate

Infinitely variable airflow control Durability

~150 / 500 litre/min No

MRP: ₹13,700

500-750 h

06012A64F0

2,000 W

Yes

50-630°C

HEAVY DUTY (79) BeConnected

GPO 950 Professional



Technical Specifications

Part no. 06013A20F0 Power 950 W Variable speed 600 - 2.100 rpm Grinding spindle thread M 14 Stick pad diameter 165 mm Max. accessory diameter 180mm Weight 2.3 kg

MRP: ₹12.900

GPO 12 CE (Promo) Professional



Technical Specifications

06013890F1 750 - 3,000 rpm No-load speed Grinding spindle thread M 14 Rubber sanding plate 180 mm Power input 1,250 W Weight 2.5 kg



MRP: ₹20,700

GSA 120 Professional



Technical Specifications

Part no. 06016B10F0 1,200 W Power input Stroke rate 0 - 3,000 per min. Stroke length 29 mm Blade change Max. cutting depth in wood 220 mm 20 mm Max. cutting depth in metal

Weight

(T) BeConnected

MRP: ₹20,600

3.7 kg

GSA 1300 PCE Professional



Technical Specifications

Part no. Power input Stroke rate at no load Stroke length Cutting depth in wood Cutting depth in metal Cutting depth in metal profiles and metal pipes HEAVY (Tri) BeCom

060164E2F0 1,300 W 0 - 2,900 spm 28 mm

220 mm 20 mm 175 mm

MRP: ₹27,600

New! GTR 550 Professional



Technical Specifications

Part no. 06017D40F0 Power input 550 W No-load speed 340 - 910 rpm Sanding pad diameter 215 mm Sanding sheet diameter 225 mm Weight 4.8 kg





MRP: ₹40,300

SPECIALITY TOOLS

GAS 15 PS Professional



Technical Specifications

Part no. Power input Container (gross/net) Max. airflow Max. vacuum pressure Weight

HEAVY (T) BeConnected

06019E51F0 1.100 W 15/8L 53 L/Sec 270 mbar 6 kg

MRP: ₹23,100

GAS 12-25 Professional



Technical Specifications

060197COF0 Power input 1.250 W Vacuum pressure 200 mbar Air Flow 63 L/Sec Dust tank capacity gross 25 I Tank capacity net dry/wet 21/16L

HEAVY DUTY

Main filter class

MRP: ₹27,100

H13 HFPA

GAS 35 L SFC+ Professional



Technical Specifications

Max. power input (Turbine) 1,380 W Container volume, gross Container volume, net Container volume, net, water 19.2 L Filter surface area Max. volume flow rate Max. vacuum pressure

06019C30F0 35 I 23.L 6.150 cm2 74 L/sec

254 mbar MRP: ₹90,700

GAS 55 M AFC Professional



Technical Specifications

Part no. 06019C33F0 Max. power input (Turbine) 1,380 W Container volume, gross 55 I Container volume, net 43 L Container volume, net, water 40 L Filter surface area Max. volume flow rate Max. vacuum pressure

6.150 cm2 74 L/sec 254 mbar MRP: ₹1.38.500

ONN New! GAS 400 Professional



Technical Specifications

Part no 06019M00F0 Max. power input (Turbine) 1,200 W 40 L Container volume, gross Container volume, net 28 L Vacuum turbine (Kpa) 24 Airflow turbine (L/s) 80 Speed Adjustment Yes HMI Yes 14 kg BUTY Weight

GBR 15 CAG Professional



Technical Specifications

Part no. 06017760F0 Rated power input 1.500 W No-load speed 9,300 rpm Grinding spindle thread M 14 Grinding head, diameter 125 mm Weight 2.6 kg

MRP: ₹85,200

ROTARY & IMPACT DRILLS

GBM 350 Professional



Technical Specifications

Part no. Power input No-load speed Drilling capacity steel Drilling capacity wood Electronic switch Reversible Weight BeConnected

06011A95F1 350 W 0 - 2,800 rpm 10 mm 20 mm

Yes Yes 1.2 kg

MRP: ₹3,600

GBM 13 RE Professional



Technical Specifications

Part no. 06014775F0 Power input 600 W No-load speed 0 - 2,600 rpm 1.5-13 mm Chuck capacity Drilling dia. in steel 13 mm Drilling dia. in aluminium 13 mm Drilling dia. in wood 30 mm Weight 1.7 kg MRP: ₹7,400 DUTY BeConnected

ROTARY & IMPACT DRILLS

GBM 1600RE Professional



Technical Specifications

Part no. 06011BOOF1 Power input 850 W No-load speed 0 - 630 rpm Rated torque 11 Nm Lock-on button Yes Stirrer capacity 160 mm Wood drilling 40 mm Metal drilling 16 mm

MRP: ₹17.500

GBM 50-2 Professional



Technical Specifications

Part no. 06011B40F0 Power input 1.200 W 50-255 / 100-510 rpm No-load speed 50 mm Annular cutter Max. twist drill 23 mm Max. thread M 16 Magnetic force 14,000 N Weight 14.7 kg

MRP: ₹ 1,29,900

GSB 450 Professional



Technical Specifications

Part no Input Power Impact Rate No-load speed Max. drill capacity: concrete Max. drill capacity: steel Max. drill capacity: wood Weight Professional Be Communication

06012161FK 450 W 0 - 41,600 bpm 0 - 2,600 rpm 10 mm

8 mm 20 mm 1.5 kg MRP: ₹4,300

06012171F3

GSB 501 Professional





Technical Specifications

Part no 06012161FD Input power 500 W No-load speed 0 - 2,600 rpm 0 - 25,700 bpm Impact rate Rated torque 1.5 Nm Max. drill capacity: concrete 13 mm Max. drill capacity: steel 10 mm

Max. drill capacity: wood 25 mm OSCH

Second BeConnected MRP: ₹4.800

GSB 600 Professional



Technical Specifications

Rated input power 600 W No-load speed 0 - 2,800 rpm Impact rate at no-load speed 0 - 44,800 bpm Chuck capacity 13 mm 1.8 kg

Weight

MRP: ₹4,600 T BeConnected

New! GSB 600 RE Kit (100Pc Kit)



Technical Specifications

Part no. 06011A03F1 Rated input power 600 W No-load speed 0 - 3000 rpm Impact rate at no-load speed 0 - 48000 bpm Chuck capacity 13 mm Weight 1.7 kg

(79) BeConnected

Rated torque

1.4 Nm MRP: ₹9,350

GSB 600 RE Kit Professional



Technical Specifications

Part no. 06012171F8 Power input 600 W No-load speed 0 - 2,800 rpm Impact rate at no-load speed 0 - 44,800 bpm

Chuck capacity 13 mm Weight 1.8 kg

Professional BeCommoctors

MRP: ₹7,000

GSB 13 RE Professional



Technical Specifications

Part no. 06012171F3 Rated input power 600 W No-load speed 0 - 2,800 rpm Impact rate at No-load speed 0 - 44,800 bpm Chuck capacity 13 mm Weight 1.8 kg





MRP: ₹7,425

ROTARY & IMPACT DRILLS

GSB 16 RE Professional



Technical Specifications

Rated input power No-load speed Chuck capacity Impact rate at no-load speed Weight

HEAVY DUTY BeConnected

06012281F0 750 W 0 - 3,250 rpm 13 mm

0 - 48,500 bpm 1.8 kg

MRP: ₹12,300

GSB 20-2 RE Professional



Technical Specifications

Part no. Power input No-load speed(1/2" Gear) 1,100/3,000 rpm Impact Rate Max. drilling diameter

(18/24 gear) Brickwork Steel Wood

40/25 mm HEAVY (T) BeConnected MRP: ₹18,600

06011A21F1

48,000 bpm

20/16 mm 13/6 mm

800 W

GSB 600 RE Kit Professional





Technical Specifications

Part no. Power input No-load speed Impact rate at no-load speed Chuck capacity Weight

06012171F8 600 W 0 - 2,800 rpm 0 - 44,800 bpm 13 mm 1.8 kg

MRP: ₹9.375

GSB 500 RE Kit Professional



Technical Specifications

Part no. 06012161F8 Power input 500 W No-load speed, 1st gear 0 - 2,600 rpm Impact rate at no-load speed 0 - 41,600 bpm Chuck capacity, min./max. 1.5 - 10 mm Weight 1.8 kg

Professional Be Communities **GSB 10 RE Kit Professional**



GSB 13 RE Kit Professional



HEAVY DUTY BeCservector



Technical Specifications

Power input No-load speed Impact rate at no-load speed 0 - 41,600 bpm Drilling dia. in masonry wall 10 mm Drilling dia. in steel Drilling dia. in wood Chuck capacity

To BeConnected

06012161F4 500 W 0 - 2,600 rpm

8 mm 20 mm 1-10 mm

MRP: ₹8,800

Drilling diameter in wood Drilling diameter in steel

Weight

Part no.

Power input

Impact rate

No-load speed

Till BeConnected

06012171F6

MRP: ₹8.800

600 W 0 - 2,800 rpm 48,000 bpm Drilling diameter in masonry 13 mm

25 mm 10 mm 1.6 kg

MRP: ₹9,725



CHOPSAWS

GCO 220 Professional



Technical Specifications

Part no. Input power No-load speed Disc diameter Cutting capacity rectangle 100 x 196 mm Cutting capacity square Cutting capacity round Cutting capacity L-profile

BOSCH BeConnected

0601B373F0 2.200 W 3,800 rpm 355 mm

119 x 119 mm 129 x 129 mm 130x130 mm

MRP: ₹19.000

COMING New! GCO 230 Professional



Technical Specifications

Part no. 0601B560F0 2.300 W Input power No-load speed 4,100 rpm Cutting capacity(L-profile) 137 mm Cutting capacity(square bar) 120 x 120 mm Cutting capacity(rectangle) 100 x 200 mm Cutting capacity(L-profile) 137 mm Weight 14 kg





GCO 14-24 Professional



Technical Specifications

Part no. Input power Cutting capacity rectangle 100x196 mm Cutting capacity square Cutting capacity L-profile No-load speed Disc diameter Weight

HEAVY BeCommetted

0601B371F0 2,400 W

119 x 119 mm 130x130 mm 3,800 rpm 355 mm 17.5 kg

MRP: ₹23,100

GCO 14-24 J Professional



Technical Specifications

Part no. Rated power input No-load speed Saw blade diameter Saw blade bore Cutting capacity at rectangle Cutting capacity at square Cutting capacity at L-profile HEAVY (T/) BeCsenected

119x119 mm 130 x 130 mm MRP: ₹25,000

100 x 196 mm

0601B372F0

2,400 W

355 mm

25.4 mm

3,800 rpm

METALWORKING

GGS 3000 L Professional



Technical Specifications

Part no. Power input No-load speed Collet chuck dia. max. Spindle collar diameter Weight without cable

BeConnected

06012240F0 300 W 0 - 28,000 rpm 8 mm

41 mm 1.5 kg

MRP: ₹11,900

GGS 5000 L Professional





Technical Specifications 06012241F0

Part no. Power input No-load speed Collet chuck dia, max. Spindle collar diameter Weight without cable

(Tg) BeConnected

MRP: ₹14,300

500 W

8 mm

41 mm

1.4 kg

33,000 rpm

GGS 28 LCE Professional





Technical Specifications

Part no. 06012211F0 650 W Power input No-load speed 10,000 - 28,000 rpm Tool holder Up to 8 mm Weight without cable 1.6 kg

New! GGS 30 LS Professional



Technical Specifications

Part no. 06012B50F0 750 W Power input No-load speed 17,000 - 33,000 rpm Collet diameter supplied 6 mm

Weight without cable 1.7 kg











MRP: ₹29,900

METALWORKING

GBG 35-15 Professional



Technical Specifications

Part no. Power input No load speed Disc diameter Grinding disc width Grinding disc bore Weight

10 kg MRP: ₹15,000

060127A3F0

3,000 rpm

150 mm

20 mm

20 mm

350 W

GBG 60-20 Professional



Technical Specifications

060127A4F0 Power input 600 W No load speed (50/60Hz) 3,000 rpm Disc diameter 200 mm Grinding disc width 25 mm Grinding disc bore 32 mm 17 kg Weight HEAVY DUTY MRP: ₹23,900

WOODWORKING

GDS 30 Professional



Technical Specifications

Part no. Power input Torque max. (hard/soft) Rated speed Tool holder Bolt diameter Max.

Weight

7.3 kg MRP: ₹1,55,800

06014351F3

1,000 / 500 Nm

920 W

M 30

860 rpm

1" Sq. Drive

New! GKS 130 Professional



Technical Specifications

Part no. Power input Blade diameter/bore size No-load speed Max. depth of cut at Cutting depth at Cutting depth at

Tyl BeConnected

45° 45 mm MRP: ₹11.400

06016C30F0

184/20 mm

5,800 rpm

90° 64 mm

0° 64 +/-1

1,300 W

GKS 190 Professional



Technical Specifications

Part no. Power input No-load speed Saw blade bore Saw blade diameter Cutting depth Cutting depth Weight without cable

DUTY TO Be Connected

06016230F1 1.400 W 5.500 rpm 20 mm 184 mm

(90°) 67 mm (45°) 48 mm 4.1 kg

MRP: ₹16,600

GKS 235 Turbo Professional



Technical Specifications

Part no. 06015A20F0 2,050 W Power input 0 - 5,300 rpm No-load speed Saw blade bore 25 mm Saw blade diameter 235 mm Cutting depth (90°) 85 mm (45°) 65 mm Cutting depth Weight without cable 7.6 kg



MRP: ₹21,600

GTS 10 J Professional



Technical Specifications

Part no. No-load speed Table size Saw blade diameter Cutting height 90° Saw bore diameter Max. cutting on right Max, cutting on left

0601B305F0 3,650 rpm 642 x 634 mm 254 mm 79 mm 30 mm 635 mm 255 mm

MRP: ₹1,13,200

GST 680 Professional



Technical Specifications

Part no. 06015130F0 500 W Power input No-load speed 800 - 3,100 spm Cutting depth 68 mm Weight 2.0 kg





WOODWORKING

GST 90 BE Professional



Technical Specifications

Part no. Power input No-load stroke rate Cable length Cutting depth in wood Cutting depth in aluminium 20 mm Cutting depth in non-alloyed steel

060158F0F0 650 W 500 - 3,100 spm 2.5m 90 mm

10 mm MRP: ₹22,100

GTS 254 Professional



Technical Specifications

0601B450F0 Cutting depth 0"/45" 80/55 mm Rip cut capacity 545 mm Power 1,800 / 15A Saw blade diameter 254 mm Overload / restart protection Yes 55 x 555 mm Table size Weight with stand 24.4 kg MRP: ₹41.200

New! GCM 254 Professional



Technical Specifications

Part no. Power input Cutting capacity,0° Cutting capacity,45° incline No-load speed Saw blade diameter Saw blade bore Weight DUTY BeConnected

0601B520F0 1,750 W 90 mm 130 mm

5,000 rpm 255 mm 25.4 mm 11.5 kg MRP: ₹31.500

GHO 6500 Professional



Technical Specifications

Part no. 06015960F0 Power input 650 W No-load speed 16,500 rpm Planing width 82 mm 2.6 mm Max. cutting depth 2.8 kg Weight



Professional BeCommocted

MRP: ₹12.100

GHO 26-82 D Professional



Technical Specifications

Part no. Power input No-load speed Recess Cutting width Max. cutting depth Weight

DUTY BeCsenected

3 kg MRP: ₹16,900

06015A40F0

16,500 rpm

710 W

9 mm

82 mm

2.6 mm

GHO 10-82 Professional



Technical Specifications

06015940F1 Power input 710 W Adjustable rebating depth 0-9 mm No-load speed 16,500 rpm Cutting width 82 mm Cutting depth max. 1 mm Weight without cable $2.5 \, \text{kg}$



MRP: ₹13,400

New! GEX 125 Professional



Technical Specifications

Part no. Power input Sanding pad diameter No-load speed Orbital stroke rate Eccentricity Weight

HEAVY BECSEROCIO

06013A80F0 290 W 125 mm 7,500 - 12,000 rpm 15,000 - 24,000 opm 1.3 mm 1.4 kg

MRP: ₹7,100

GEX 125-1 AE Professional



Technical Specifications

Part no. 06013875F2 250 W Power input Sanding pad diameter 125 mm No-load speed 7,500 - 12,000 rpm Orbital stroke rate 15,000 - 24,000 opm Eccentricity 1.25 mm Oscillating circuit dia. 2.5 mm Weight 1.3 kg





WOODWORKING

GEX 34-150 Professional



Technical Specifications

Part no. Power input No-load speed Orbital stroke rate Orbit diameter Pad diameter Cord

Weight DUTY BeConnected 06013728F0 340 W 4,500 - 12,000 rpm 9,000 - 24,000 opm

4 mm 150 mm 4 mm 2.4 kg MRP: ₹23,400

GSS 140 Professional



Technical Specifications

Power input No-load speed No-load orbital stroke rate Orbital diameter Sanding sheet dimension Sanding plate dimension Weight Professional BeCommocited

28,000 opm 1.5mm 114x140 mm 101x112 mm 1.2 kg MRP: ₹4,775

06012A80F1

14,000 rpm

220 W

GSS 2300 Professional



Technical Specifications

Part no. Power input No-load speed Sanding sheet size Sanding plate size Weight

06012980F0 190 W 12,000 rpm 230 mm x 93 mm 182 mm x 92 mm 1.5 kg

MRP: ₹9,400

GKF 550 Professional



Technical Specifications

Part no. 06016A00F0 Power input 550 W No-load speed 33,000 rpm Bit size 6 /1/4" mm 1.4 kg Weight



Part no. Power input No-load speed Bit holder Router bit diameter Weight

06016B70F0 1,300 W 11,000 - 28,000 rpm 6 - 8.0 mm 40 mm 3.5 kg



MRP: ₹16,100

GTB 650 Professional

(79) BeConnected



Technical Specifications

Part no. 06014A20F0 Power input 650 W No-load speed 0 - 5,000 rpm 12 Nm Torque, max. Bit holder 1/4" internal hexagon Weight 1.4 kg



(79) BeConnected

MRP: ₹13,400

MRP: ₹8,900



Technical Specifications

Part no. Power input No-load speed Torque, max. Tool holder Speed selection Soft start Carbon brush Weight DUTY BeConnected

06011C40F0 1.400W 480 / 750rpm 35 / 23 Nm M14 2 speed Yes Yes 4.2kg MRP: ₹10,700



STORAGE SOLUTIONS

i-BOXX 53



Technical Specifications

Part number 1600A001RV Material Plastic Application For use with L-Boxx 3D Weight 0.81 kg

MRP: ₹3,100

i-BOXX 72



Technical Specifications

Part number 1600A001RW Material Plastic Application For use with L-Boxx 3D Weight 0.87 kg

L-BOXX 102 Professional



Technical Specifications

Part number Material Suitable for

Weight

All types of Power Tools 1.8 kg

MRP: ₹4,300

1600A012FZ

ΔRS

L-BOXX 136 Professional



Technical Specifications

Part number 1600A012G0 Material ABS Application For use with L-Boxx 3D Weight 2.2 kg

MRP: ₹4,400

MRP: ₹3,000

L-BOXX 238 Professional



Technical Specifications

Part number Material Suitable for Weight

ABS All types of Power Tools 2.8 kg

1600A012G2

MRP: ₹6,000

L-BOXX 374 Professional



Technical Specifications

Part number Material Application

Weight

1600A012G3 All types of

Power Tools 3.0 kg

ABS

MRP: ₹8,000

L-BOXX Mini 2.0 Professional



Technical Specifications

Part number 1600A007SF Material PP 1.5 kg Max. Load Weight 0.3 kg

MRP: ₹1,400

L-BOXX 306 Professional



Technical Specifications

Part number 1600A001RU Material ABS Product Type LS-BOXX Tool Storage Weight 3.85 kg

MRP: ₹10,100



STORAGE SOLUTIONS

LT-BOXX 170 Professional



Technical Specifications

Part number 1600A00222 ABS Material Weight 2.3 kg

MRP: ₹6,800

Technical Specifications Part number 1600A003BJ Length 480 mm Width 300 mm 280 mm Height Weight 1.5 kg

MEDIUM TOOL BAG - 48 x 28 x 30

MRP: ₹3,700

LARGE TOOL BAG - 55 x 35 x 35



Technical Specifications

Part number 1600A003BK Length 550 mm 350 mm Width 350 mm Height Weight $1.5 \, kg$ MRP: ₹4,300





TERMS AND CONDITIONS

- Tradional Trade Price list, subjected to change without any prior notice.
- Standard TT discount is applicable on List Price / Promo List Price.
- Promo prices are subjected to meeting minimum ordering quantity.
- All prices mentioned above are excluding GST. Current rate of GST is 18% and will be charged additionally.
- HSN code and EAN codes are indicative. For more details, please follow the invoice.
- In case of any dispute, system prices will be considred as final prices. Before placing the order, kindly check the latest price in B2B.
- This price list superseds all previous pricess communicated.
- MRP on the tools may be different based on manufacturing / imported date.
- In case if any products not listed above and availble in stock, you may contact PT-BE/MKR-IN
 for pricing prior to invoicing.
- In case of any disputes PT-BE/MKR-IN & PT-BE/SAD decision is final & are subject to Bangalore jurisdiction.



1 year warranty from the date of purchase*



WARRANTY TERMS AND CONDITIONS

Power Tools from Bosch are guaranteed against all material and manufacturing defects for a period of 6 months from the date of purchase *for Professional Tools and 1 year warranty for all professional and Heavy Duty Tools.

In the event of failure of the tools due to material and manufacturing defects, we undertake to repair the tools free of charge, provided we are satisfied that:

- ▶ The Power Tool has not been tampered with.
- > Failure has occurred due to manufacturing/material defects.
- ▶ The Power Tool has been purchased from an accredited dealer.
- The claim has been referred to one of the Bosch Authorized Service Centres along with the Power Tool, guarantee card and original tool purchase receipt or invoice.

This warranty does not cover:

- All normal wear and tear parts like carbon brush, bearings, o-rings etc.
- Installation to wrong voltage, over load and wrong application.
- Use other than in accordance to handling instructions.
- Unauthorized repair carried out.
- Damage due to any unit caused by accident, misuse, wilful damage, normal wear, claims arising from loss, fire or other calamities caused by nature or in any way being tampered with.

*Check with Local Bosch representative for Hot Air Gun Warranty.



								-
								\Box
								\vdash
								\vdash
								-
								\vdash
								-

Bosch Limited, Power Tools Division Post Box No. 3000, Hosur Road, Adugodi Bangalore, Karnataka- 560030

www.facebook.com/BoschPTindia

Bosch Professional India - YouTube



Customer Contact Center 1800 425 8665

Email: bpt@in.bosch.com www.bosch-pt.co.in

Edition: February 2024