



EB120 50W E27 5500lm DAYLIGHT
EB120 50W E27 5500lm WARMLIGHT



Lus-ter®



R63 7W E27 450lm WARMLIGHT





EB40 8W E27 800lm DAYLIGHT

EB40 8W E27 800lm WARMLIGHT

EB40 13W E27 1300lm DAYLIGHT

EB40 13W E27 1300lm WARMLIGHT



Lus-ter

G45 5W E27 12V 450lm DAYLIGHT
A60 9W E27 12V 850lm DAYLIGHT



A60 9W E27 BLUE

A60 9W E27 PURPLE

A60 9W E27 RED

A60 9W E27 GREEN





A60 7W E27 90lm/w DAYLIGHT

A60 7W E27 90lm/w WARMLIGHT

A65 13W E27 90lm/w DAYLIGHT

A65 13W E27 90lm/w WARMLIGHT

A80 15W E27 90lm/w DAYLIGHT

A80 15W E27 90lm/w WARMLIGHT

A95 20W E27 90lm/w DAYLIGHT

A95 20W E27 90lm/w WARMLIGHT



Lus-ter

SPOTLIGHT 1703PR 8W 720lm DAYLIGHT
SPOTLIGHT 1703PR 8W 720lm WARMLIGHT



SPOTLIGHT 1703PR 8W 720lm DAYLIGHT
SPOTLIGHT 1703PR 8W 720lm WARMLIGHT




PROF POWER
محترف الطاقة


Features:

- Ideal replacement for traditional downlight
- High lumen input with even light distribution
- Plastic body with fashionable design
- Built-in Driver inside the housing
- Easy for installation
- Switch dimming

Product Dimensions Fig



Light Distribution Curve



DOWNLIGHT 1708P 15W 1400lm DAYLIGHT
DOWNLIGHT 1708P 15W 1400lm WARMLIGHT
DOWNLIGHT 1708P 26W 2400lm DAYLIGHT
DOWNLIGHT 1708P 26W 2400lm WARMLIGHT



Model	Dimension Ø*H(mm)	Cut-out	Watt(W)	Voltage(V)	Color temp(K)	Beam Angle	LM	CRI	HR
1708	Ø160*70	Ø140	15	220-240	2700-6500	105°	1125	≥80	> 50000
	Ø220*85	Ø200	24	220-240	2700-6500	90°	2040	≥80	> 50000



FLOODLIGHT FLF 40W 5000K 4000lm
FLOODLIGHT FLF 60W 5000K 6000lm
FLOODLIGHT FLF 100W 5000K 10000lm



Lus-ter®