

MORE POWER
MORE POSSIBILITIES



62-811-2240205



62-811-2002445



marketing@finkomodo.com



www.finkomodo.com

PT. FIN KOMODO TEKNOLOGI

Jl. Kol. Masturi No.106-A (Warung Muncang)
Cimahi 405111, Indonesia

FINKOMODO PT FIN KOMODO TEKNOLOGI



CONNECT WITH US



BJ HABIBIE
AWARD



PENGHARGAAN
PRESIDEN RI



GRAND AWARD
IGDS 2020



BANGGA BUATAN
INDONESIA

FIN KOMODO

KD 500

4x4



FIN
KOMODO

Mesin	4 stroke 500cc
Max. Momen Puntir	45 Nm (6000rpm)
Max. Daya Kuda	39 hp (6750rpm)
Perbandingan Komperensi	10.3:1 4katup
Sistem Pendingin	Air
Bahan Bakar	Rekomendasi Pertamina
Kapasitas Tanki	40 Liter
Kapasitas Oli Mesin	3000cc, SAE 40
Kapasitas Oli Mesin (Ganti Filter Oli)	3300cc
Kapasitas Oli Gardan	650cc, SAE 40 (Depan), 750cc, SAE 40 (Belakang)
Starter	Elektrik
Sistem Penggerak	4 x 4 dengan differential lock
Transmisi	Automatic CVT dengan P, R, N, H, L Gear
Rangka	Tubular space frame
Steering Systems	Rack & Pinion
Suspensi Depan	Fully Independent Double Wishbone dengan per Keong (double action shock absorber)
Suspensi Belakang	Fully Independent Double Wishbone dengan per Keong (double action shock absorber)
Rem Depan	Cakram
Rem Belakang	Cakram
Ban Depan	25 x 8 x 12
Ban Belakang	25 x 10 x 12
Jarak Sumbu Roda	2385Mm
Jarak Roda	1575mm
Panjang Total	3250mm
Lebar Total	1595mm
Tinggi Total	1615mm
Kapasitas Angkut	2 Penumpang & 350 Kg Barang
Seat Belt	Menggunakan sistem 4 titik
Warna	Sesuai Pesanan

NEXT LEVEL POWER

4X4, 500 CC



**ALL TERRAIN
COMFORT**

- EFFORTLESS DRIVING
- RIGHT-SIDE STEERS
- SPACIOUS UTILITY BOX



**EXPERIENCE
MORE**



- MULTIPURPOSE
- REACHING UNTOUCHED DESTINATION

Specification	Details
Engine	4-stroke 500cc
Max. Torque	45 Nm (6000 rpm)
Max. Horsepower	39 hp (6750 rpm)
Compression Ratio	10.3:1, 4 valves
Cooling System	Air
Fuel	Recommended Pertamina (high-octane fuel)
Fuel Tank Capacity	40 Liters
Engine Oil Capacity	3000 cc, SAE 40
Engine Oil Capacity (with Filter)	3300 cc
Differential Oil Capacity	650 cc, SAE 40 (Front), 750 cc, SAE 40 (Rear)
Starter	Electric
Drivetrain System	4 x 4 with differential lock
Transmission	Automatic CVT with P, R, N, H, L Gear
Frame	Tubular space frame
Steering System	Rack & Pinion
Front Suspension	Fully Independent Double Wishbone with Coil Spring (double action shock absorber)
Rear Suspension	Fully Independent Double Wishbone with Coil Spring (double action shock absorber)
Front Brake	Disc
Rear Brake	Disc
Front Tire	25 x 8 x 12
Rear Tire	25 x 10 x 12
Wheelbase	2385 mm
Track Width	1575 mm
Overall Length	3250 mm
Overall Width	1595 mm
Overall Height	1615 mm
Passenger Capacity	2 People
Seat Belt	4-point harness system
Color	As Ordered

NEXT LEVEL POWER

4X4, 500 CC



ALL TERRAIN COMFORT

- EFFORTLESS DRIVING
- RIGHT-SIDE STEERS
- SPACIOUS UTILITY BOX



EXPERIENCE MORE

- MULTIPURPOSE
- REACHING UNTOUCHED DESTINATION

