

For Commercial and Industrial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Representative _____

Series SS

Watts SS Series pre-charged all stainless steel shock arrestor with stainless steel bellows and male IPS threaded connection.

Operating Pressure

Designed to operate on all domestic and commercial lines, up to 340psig surge with an exception of SS-AA.

Temperature Range

-100 to 300 Deg F (-73 to 149 Deg C)

Pipe Sizing (Select One)			
Suffix	Description		
AA	1/2" (15) Connection		<input type="checkbox"/>
A	3/4" (19) Connection		<input type="checkbox"/>
B	1" (25) Connection		<input type="checkbox"/>
C	1" (25) Connection		<input type="checkbox"/>
D	1" (25) Connection		<input type="checkbox"/>
E	1" (25) Connection		<input type="checkbox"/>
F	1" (25) Connection		<input type="checkbox"/>



Note : Complies with ASSE 1010



	SS-AA	SS-A	SS-B	SS-C	SS-D	SS-E	SS-F
Fixture Unit	1-11	1-11	12-32	33-60	61-113	114-154	155-330
A connection	1/2" (15)	3/4" (19)	1"(25)	1"(25)	1"(25)	1"(25)	1"(25)
B height	3-1/4"(83)	3-1/4"(83)	4"(102)	4-5/16"(110)	5-1/4"(133)	7"(178)	7"(178)
C diameter	3-1/4"(83)	3-1/4"(83)	3-1/4"(83)	3-1/4"(83)	3-1/4"(83)	3-1/4"(83)	3-1/4"(83)



Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.