



APD10000E
Diesel Generator

FEATURES

- Easy Electric Key Start
- High Performance Alternator
- 498/192cc Powerful Diesel Engine
- 18L Heavy Duty Large Fuel Tank
- Long Run Time @ %50 Load: 10.3 Hours
- Intelligent AVR Delivers Stable Power
- Digital 3-in-1 Hour Meter
- Low Oil Alert Lamp
- 30mm Heavy Duty Full Frame Protection
- Never-Flat Wheel for Effortless Move

SPECIFICATION

| | | |
|------------------------|--------------------------------|------------------------|
| Alternator | Model | APD10000E |
| | Phase/Frequency (Hz) | Single Phase/50 |
| | Max. Output (kW/kVA) | 6.5/8.1 |
| | Rated Output (kW/kVA) | 6.0/7.5 |
| | AVR | ✓ |
| | Voltage (AC)(V) | 230 |
| | Rotating Speed (rpm) | 3000 |
| | Voltage (DC)(V) | 12 |
| | Current (DC)(V) | 8.3 |
| | Rated Current (A) | 26.1 |
| Engine | Model No. | 192 |
| | Run Time - (50 %Load)(Hrs) | 10.3 |
| | Run Time - (100 %Load)(Hrs) | 6.7 |
| | Fuel Consumption (50 %Load)(L) | 1.75 /hr |
| | Low Oil Alert Lamp | ✓ |
| | Display | 3-In-1 Meter |
| | Circuit Breaker (A) | 31 |
| | Socket (A) | 1x16 Industrial, 1x32 |
| | Bore x Stroke | 92x75 |
| | Displacement (ml) | 498 |
| | Cooling | Air Cooling |
| | Lubrication sys. | Forced-Feed and Splash |
| | Oil Capacity (L) | 1.65 |
| Starting sys. | Electric | |
| Fuel Type | Diesel | |
| Fuel Tank Capacity (L) | 18 | |
| Noise (7m)(dB) | 106 | |
| Generator | Steel Frame (mm) | 30 |
| | Built-In-Handle | ✓ |
| | Wheel Kits (inch) | 9 |
| | Battery (Ah) | 36 |
| | Gross/Net Weight (kg) | 130/125 |
| Dimension (LxWxH) (mm) | 750x550x725 | |



Value Starts Here