



AIPOWER INFINITE SERIES GASOLINE GENERATOR SPECIFICATIONS

FEATURES

POWERFUL ENGINE
HIGH PERFORMANCE ALTERNATOR
CAST IRON CYLINDER SLEEVES
INTELLIGENT SILICONED AVR
DIGITAL 3-IN-1 HOUR METER
BUILT-IN FUEL GAUGE
RIGID LOW TONE MUFFLER
TRIP CIRCUIT BREAKERS
EASY ELECTRIC/RECOIL START
DUAL ELEMENT AIR FILTER
LOW OIL LEVEL SHUTDOWN
FUEL EFFICIENT
25L STEEL FUEL TANK
EFFORTLESS MOVE



| MODEL | SPECIFICATIONS | APD20 |
|------------|-------------------------------|-------------------------|
| Powered by | Gasoline / Desiel | Desiel |
| PUMP | Suction Port Diameter | 2 in. NPT |
| | Discharge Port Diameter | 2 in. NPT |
| | Pump type | Self-Priming |
| | Suction Head Lift | 8m |
| | Total Discharge Head Lift | 26m |
| | Discharge Flow | 28M3/h |
| | Volute | Rigid Mounted Cast Iron |
| | Impeller | 5 Vane Cast Iron |
| | Mechanical Seal | Silicon Carbide |
| | Hosing | Aluminum Alloy |
| | Outlet / Inlet Connection | Thread Male (NPT) |
| ENGINE | Engine (OHV) | 211cc / 170F |
| | Starting Method | Manual |
| | Low Oil Shut Down Met | Yes |
| | Fuel Tank Capacity | 2.5L |
| | Engine Oil Capacity | 0.75L |
| | Run time @ 50% Load | 4 |
| | Run time @ 100% Load | 3 |
| | Noise Level, dBA at 23ft (7m) | |
| ACCES | Durable Tubular Steel Frame | 22mm |
| | Spark Plug Socket | N/A |
| PACKING | Net Weight (kgs) | 38 |
| | Gross Weight (kgs) | 40 |
| | Length*Width*Height (mm) | 538 x 456 x 530 |
| | Loading Q'ty (20GP/40GP) | 192 / 400 |