



# HL2050

## AIR COMPRESSOR

### FEATURES

- ◆ DIRECT DRIVE / BELT DRIVE
- ◆ FAST CHARGING SPEED
- ◆ COPPER INDUCTION MOTOR
- ◆ RELIABLE & DURABLE
- ◆ CONDOR PRESSURE SWITCH
- ◆ SMOOTH PERFORMANCE
- ◆ EASY TO USE AND MAINTAIN
- ◆ THERMAL OVERLOAD PROTECTOR



### TECHNICAL DATA

MODEL	HL2050
Air Tank Capacity	50L
Max Pressure	8Bar/120PSI
Displacement	110L/Min
Rated Volts	220V
Frequency	50Hz
Rated Output	850W
Rated Power	2.0HP
Rated Speed	2800RPM
Power Source	Electric
Stage	Single
Tank Type	Horizontal
Lubrication	Oil Free
Noise Level	≤95dB
Net Weight	28Kg
Gross Weight	30Kg
Packing Dimension	720x330x630mm



# HL2025

## AIR COMPRESSOR

### FEATURES

- ◆ DIRECT DRIVE / BELT DRIVE
- ◆ FAST CHARGING SPEED
- ◆ COPPER INDUCTION MOTOR
- ◆ RELIABLE & DURABLE
- ◆ CONDOR PRESSURE SWITCH
- ◆ SMOOTH PERFORMANCE
- ◆ EASY TO USE AND MAINTAIN
- ◆ THERMAL OVERLOAD PROTECTOR

### TECHNICAL DATA

MODEL	HL2025
Air Tank Capacity	25L
Max Pressure	8Bar/120PSI
Displacement	110L/Min
Rated Volts	220V
Frequency	50Hz
Rated Output	850W
Rated Power	2.0HP
Rated Speed	2800RPM
Power Source	Electric
Stage	Single
Tank Type	Horizontal
Lubrication	Oil Free
Noise Level	≤95dB
Net Weight	23.5Kg
Gross Weight	25Kg
Packing Dimension	615x265x580mm



# HL20100B

## AIR COMPRESSOR



### FEATURES

- ◆ DIRECT DRIVE / BELT DRIVE
- ◆ FAST CHARGING SPEED
- ◆ COPPER INDUCTION MOTOR
- ◆ RELIABLE & DURABLE
- ◆ CONDOR PRESSURE SWITCH
- ◆ SMOOTH PERFORMANCE
- ◆ EASY TO USE AND MAINTAIN
- ◆ THERMAL OVERLOAD PROTECTOR

### TECHNICAL DATA

MODEL	HL20100B
Air Tank Capacity	100L
Max Pressure	8Bar/120PSI
Displacement	170L/Min
Rated Volts	220V
Frequency	50Hz
Rated Output	850W*2
Rated Power	2.0HP
Rated Speed	1050RPM
Power Source	Electric
Stage	Single
Tank Type	Horizontal
Lubrication	Oil Free
Noise Level	≤90dB
Net Weight	73Kg
Gross Weight	75Kg
Packing Dimension	1120x430x820mm







# HL20200B

## AIR COMPRESSOR

### FEATURES

- ◆ DIRECT DRIVE / BELT DRIVE
- ◆ FAST CHARGING SPEED
- ◆ COPPER INDUCTION MOTOR
- ◆ RELIABLE & DURABLE
- ◆ CONDOR PRESSURE SWITCH
- ◆ SMOOTH PERFORMANCE
- ◆ EASY TO USE AND MAINTAIN
- ◆ THERMAL OVERLOAD PROTECTOR

### TECHNICAL DATA

MODEL	HL20200B
Air Tank Capacity	200L
Max Pressure	8Bar/120PSI
Displacement	200L/Min
Rated Volts	220V
Frequency	50Hz
Rated Output	850W*2
Rated Power	3.0HP
Rated Speed	1050RPM
Power Source	Electric
Stage	Single
Tank Type	Horizontal
Lubrication	Oil Free
Noise Level	≤90dB
Net Weight	113Kg
Gross Weight	115Kg
Packing Dimension	1340x490x940mm





# HLF2025

## AIR COMPRESSOR

### FEATURES

- ◆ OIL-FREE
- ◆ ULTRA QUIET
- ◆ FAST CHARGING SPEED
- ◆ COPPER INDUCTION MOTOR
- ◆ RELIABLE & DURABLE
- ◆ CONDOR PRESSURE SWITCH
- ◆ SMOOTH PERFORMANCE
- ◆ EASY TO USE AND MAINTAIN
- ◆ THERMAL OVERLOAD PROTECTOR

### TECHNICAL DATA

MODEL	HLF2025
Air Tank Capacity	25L
Max Pressure	8Bar/120PSI
Displacement	80L/Min
Rated Volts	220V
Frequency	50Hz
Rated Output	850W
Rated Power	1.0HP
Rated Speed	1480RPM
Power Source	Electric
Stage	Single
Tank Type	Horizontal
Lubrication	Oil Free
Noise Level	≤65dB
Net Weight	21.5Kg
Gross Weight	23.5Kg
Packing Dimension	615x265x570mm





# HLF2050

## AIR COMPRESSOR

### FEATURES

- ◆ OIL-FREE
- ◆ ULTRA QUIET
- ◆ FAST CHARGING SPEED
- ◆ COPPER INDUCTION MOTOR
- ◆ RELIABLE & DURABLE
- ◆ CONDOR PRESSURE SWITCH
- ◆ SMOOTH PERFORMANCE
- ◆ EASY TO USE AND MAINTAIN
- ◆ THERMAL OVERLOAD PROTECTOR

### TECHNICAL DATA

MODEL	HLF2050
Air Tank Capacity	50L
Max Pressure	8Bar/120PSI
Displacement	80L/Min
Rated Volts	220V
Frequency	50Hz
Rated Output	1100W
Rated Power	1.0HP
Rated Speed	1480RPM
Power Source	Electric
Stage	Single
Tank Type	Horizontal
Lubrication	Oil Free
Noise Level	≤65dB
Net Weight	26Kg
Gross Weight	28Kg
Packing Dimension	720x330x620mm







# HLF20100

## AIR COMPRESSOR

### FEATURES

- ◆ OIL-FREE
- ◆ ULTRA QUIET
- ◆ FAST CHARGING SPEED
- ◆ COPPER INDUCTION MOTOR
- ◆ RELIABLE & DURABLE
- ◆ CONDOR PRESSURE SWITCH
- ◆ SMOOTH PERFORMANCE
- ◆ EASY TO USE AND MAINTAIN
- ◆ THERMAL OVERLOAD PROTECTOR

### TECHNICAL DATA

MODEL	HLF20100
Air Tank Capacity	100L
Max Pressure	8Bar/120PSI
Displacement	160L/Min
Rated Volts	220V
Frequency	50Hz
Rated Output	850W*2
Rated Power	2.0HP
Rated Speed	1480RPM
Power Source	Electric
Stage	Single
Tank Type	Horizontal
Lubrication	Oil Free
Noise Level	≤65dB
Net Weight	61Kg
Gross Weight	63Kg
Packing Dimension	980x420x760mm

