



SM15000Di



SILENT INVERTER GENERATOR

FEATURES

- ◆ Quiet: 70 dBA
- ◆ Powerful: 750cc Powerful Engine
- ◆ Compact: 1000x810x890mm
- ◆ Long Run Time @50 %Load: 9.5 Hours
- ◆ Eco Throttle: More Efficient
- ◆ Starting Method: Push Button or Remote Start
- ◆ Safe Clean Power: Power Sensitive Electronics
- ◆ Stronger Together: Parallel for Double Power
- ◆ Single or Three Phase Output
- ◆ 50/60Hz: Versatile for Powering Worldwide Electronics
- ◆ Built-in Mobility Kit for Easy Transportation

TECHNICAL DATA

| MODEL | SM15000Di |
|-----------------------------|-----------------------|
| Max Starting Power | 15000W |
| Running Power | 12000W |
| AC Load (Volts) | 230/380 |
| Phase, Frequency | Single/Three, 50/60Hz |
| Rated Amperage | 21.6/52.2 |
| Starting Method | E-Start/Remote |
| Engine Type | Gasoline |
| Engine Model/CC/Hp | SV744/750cc/24hp |
| Noise Level | 70dB |
| Fuel Tank Capacity | 40L |
| Run Time-50 %Load | 9.5Hrs |
| Run Time-100 %Load | 6.0Hrs |
| Fuel Consumption (50 %Load) | 4.2L/Hr |
| Engine Oil Capacity | 1.5L |
| Digital Display | 9-in-1 LED Meter |
| Circuit Breaker | 2x1P-16A, 1x3P-22A |
| Remote Control | √ |
| Eco-Throttle | √ |
| Parallel Port | √ |
| Socket | 2x16A, 1x32A, 1x63A |
| DC Port | √ |
| THD | <%3 |
| Battery | 14AH |
| Wheel | 7 inch |
| Plug | 1x32A, 1x63A |
| Net Weight | 164Kg |
| Gross Weight | 206Kg |
| Packing Dimension(LxWxH) | 1000x810x890mm |
| Prodcut Dimension(LxWxH) | 972x783x873mm |
| Q'ty (20GP/40HQ) | 28/56 |

